

A Policy on Geometric Design of Highways and Streets
2018
7th Edition

TABLE OF CONTENTS

CHAPTER 1 NEW FRAMEWORK FOR GEOMETRIC DESIGN

1.1	INTRODUCTION.....	1-1
1.2	PROJECT PURPOSE AND NEED	1-3
1.3	OVERVIEW OF THE NEW FRAMEWORK FOR GEOMETRIC DESIGN	1-5
1.4	FUNCTIONAL CLASSIFICATION FOR MOTOR VEHICLES	1-7
1.4.1	Hierarchy of Motor Vehicle Movement	1-8
1.4.2	Access Control and Mobility Needs	1-10
1.4.3	Functional System Characteristics	1-11
1.4.3.1	Definitions of Urban and Rural Areas	1-11
1.4.3.2	Functional Categories	1-12
1.4.3.3	Functional Systems for Rural Areas	1-12
1.4.3.3.1	Rural Principal Arterial System	1-12
1.4.3.3.2	Rural Minor Arterial System	1-13
1.4.3.3.3	Rural Collector System	1-13
1.4.3.3.4	Rural Local Road System	1-13
1.4.3.4	Functional Systems for Urban Areas	1-14
1.4.3.4.1	Urban Principal Arterial System	1-14
1.4.3.4.2	Urban Minor Arterial Street System	1-15
1.4.3.4.3	Urban Collector Street System	1-15
1.4.3.4.4	Urban Local Street System	1-15
1.4.4	Functional Classification as a Design Type	1-16
1.5	CONTEXT CLASSIFICATION FOR GEOMETRIC DESIGN	1-16
1.5.1	Context Classes for Roads and Streets in Rural Areas	1-20
1.5.1.1	Rural Context	1-20
1.5.1.2	Rural Town Context	1-20
1.5.2	Context Classes for Roads and Streets in Urban Areas	1-21
1.5.2.1	Suburban Context	1-21
1.5.2.2	Urban Context	1-21

1.5.2.3	Urban Core Context	1-22
1.5.3	Design Guidance for Specific Context Classes	1-22
1.6	MULTIMODAL CONSIDERATIONS	1-23
1.6.1	Road and Street User Groups/Transportation Modes.	1-23
1.6.1.1	Automobiles.	1-23
1.6.1.2	Bicyclists.	1-23
1.6.1.3	Pedestrians.	1-24
1.6.1.4	Transit.	1-25
1.6.1.5	Trucks	1-25
1.6.2	Consideration of All Transportation Modes in Design	1-26
1.7	DESIGN PROCESS TO ADDRESS SPECIFIC PROJECT TYPES	1-28
1.7.1	New Construction Projects	1-28
1.7.2	Reconstruction Projects.	1-29
1.7.3	Construction Projects on Existing Roads.	1-30
1.8	DESIGN FLEXIBILITY	1-32
1.9	PERFORMANCE-BASED DESIGN	1-34
1.10	REFERENCES	1-36
 CHAPTER 2 DESIGN CONTROLS AND CRITERIA		
2.1	INTRODUCTION	2-1
2.2	DRIVER PERFORMANCE AND HUMAN FACTORS.	2-1
2.2.1	Introduction	2-1
2.2.2	Older Drivers and Older Pedestrians	2-2
2.2.3	The Driving Task	2-2
2.2.4	The Guidance Task.	2-3
2.2.4.1	Lane Placement and Road Following.	2-3
2.2.4.2	Car Following	2-3
2.2.4.3	Passing Maneuvers.	2-4
2.2.4.4	Other Guidance Activities	2-4
2.2.5	The Information System.	2-4
2.2.5.1	Traffic Control Devices	2-4

2.2.5.2	The Roadway and Its Environment.	2-4
2.2.6	Information Handling.	2-5
2.2.6.1	Reaction Time	2-5
2.2.6.2	Primacy.	2-8
2.2.6.3	Expectancy.	2-8
2.2.7	Driver Error	2-8
2.2.7.1	Errors Due to Driver Deficiencies.	2-9
2.2.7.1.1	Older Drivers	2-9
2.2.7.2	Errors Due to Situation Demands.	2-11
2.2.8	Speed and Design	2-11
2.2.9	Design Assessment	2-12
2.3	TRAFFIC CHARACTERISTICS.	2-13
2.3.1	General Considerations.	2-13
2.3.2	Volume.	2-13
2.3.2.1	Average Daily Traffic.	2-13
2.3.2.2	Design Hour Traffic: Rural Areas.	2-14
2.3.2.3	Design Hour Traffic: Urban Areas.	2-17
2.3.3	Directional Distribution	2-18
2.3.4	Composition of Traffic	2-19
2.3.5	Projection of Future Traffic Demands	2-20
2.3.6	Speed.	2-21
2.3.6.1	Operating Speed	2-22
2.3.6.2	Running Speed.	2-22
2.3.6.3	Design Speed.	2-23
2.3.7	Traffic Flow Relationships	2-27
2.4	HIGHWAY CAPACITY	2-29
2.4.1	General Characteristics	2-29
2.4.2	Application	2-29
2.4.3	Capacity as a Design Control	2-30
2.4.3.1	Design Service Flow Rate versus Design Volume	2-30
2.4.3.2	Measures of Congestion	2-30
2.4.3.3	Relation between Congestion and Traffic Flow Rate	2-32

2.4.3.4	Acceptable Degrees of Congestion	2-32
2.4.4	Factors Other Than Traffic Volume That Affect Operating Conditions	2-33
2.4.4.1	Roadway Factors	2-33
2.4.4.2	Alignment.	2-34
2.4.4.3	Weaving Sections	2-34
2.4.4.4	Ramp Terminals	2-34
2.4.4.5	Traffic Factors	2-35
2.4.4.6	Peak Hour Factor	2-35
2.4.5	Levels of Service	2-36
2.4.6	Design Service Flow Rates.	2-38
2.4.6.1	Weaving Sections	2-38
2.4.6.2	Multilane Highways without Access Control	2-41
2.4.6.3	Arterial Streets and Highways in Urban Areas	2-41
2.4.6.4	Intersections.	2-41
2.5	ACCESS CONTROL AND ACCESS MANAGEMENT	2-41
2.5.1	General Conditions	2-41
2.5.2	Basic Principles of Access Management	2-43
2.5.3	Access Classifications	2-44
2.5.4	Methods of Controlling Access	2-45
2.5.5	Benefits of Controlling Access.	2-45
2.6	PEDESTRIANS	2-50
2.6.1	General Considerations	2-50
2.6.2	General Characteristics	2-50
2.6.3	Walking Speeds	2-52
2.6.4	Walkway Level of Service.	2-52
2.6.5	Intersections	2-52
2.6.6	Reducing Pedestrian–Vehicular Conflicts	2-53
2.6.7	Accommodating Persons with Disabilities	2-53
2.6.7.1	Mobility Disabilities	2-53
2.6.7.2	Vision Disabilities	2-54
2.6.7.3	Cognitive Disabilities	2-54

2.6.7.4	Hearing Disabilities	2-54
2.7	BICYCLISTS	2-54
2.8	DESIGN VEHICLES	2-55
2.8.1	General Characteristics	2-55
2.8.2	Minimum Turning Paths of Design Vehicles	2-58
2.8.3	Vehicle Performance	2-86
2.8.4	Vehicular Pollution	2-89
2.9	SAFETY	2-90
2.9.1	Key Factors Related to Traffic Crashes	2-90
2.9.1.1	Roadway Design	2-91
2.9.1.2	Roadside Design	2-92
2.9.1.3	Traffic Control Devices	2-93
2.9.2	Key Safety Resources	2-93
2.9.3	Safety Improvement Programs	2-94
2.9.4	Project Development Process	2-94
2.10	ENVIRONMENT	2-95
2.11	REFERENCES	2-95

CHAPTER 3 ELEMENTS OF DESIGN

3.1	INTRODUCTION	3-1
3.2	SIGHT DISTANCE	3-1
3.2.1	General Considerations	3-1
3.2.2	Stopping Sight Distance	3-2
3.2.2.1	Brake Reaction Time	3-2
3.2.2.2	Braking Distance	3-3
3.2.2.3	Design Values	3-5
3.2.2.4	Effect of Grade on Stopping	3-5
3.2.2.5	Variation for Trucks	3-6
3.2.2.5.1	New Construction vs. Projects on Existing Roads	3-7
3.2.3	Decision Sight Distance	3-7
3.2.4	Passing Sight Distance for Two-Lane Highways	3-10

3.2.4.1	Criteria for Design	3-10
3.2.4.2	Design Values.	3-10
3.2.4.3	Effect of Grade on Passing Sight Distance.	3-12
3.2.4.4	Frequency and Length of Passing Sections	3-12
3.2.5	Sight Distance for Multilane Highways	3-14
3.2.6	Criteria for Measuring Sight Distance	3-15
3.2.6.1	Height of Driver's Eye.	3-15
3.2.6.2	Height of Object	3-15
3.2.6.3	Sight Obstructions	3-16
3.2.6.4	Measuring Sight Distance	3-16
3.3	HORIZONTAL ALIGNMENT	3-19
3.3.1	Theoretical Considerations	3-19
3.3.2	General Considerations.	3-20
3.3.2.1	Superelevation	3-20
3.3.2.2	Side Friction Factor	3-21
3.3.2.3	Distribution of e and f over a Range of Curves	3-26
3.3.3	Design Considerations.	3-31
3.3.3.1	Normal Cross Slope	3-31
3.3.3.2	Maximum Superelevation Rates for Streets and Highways	3-31
3.3.3.3	Minimum Radius.	3-33
3.3.3.4	Effects of Grades	3-35
3.3.4	Design for Rural Highways, Urban Freeways, and High-Speed Urban Streets	3-36
3.3.4.1	Side Friction Factors.	3-36
3.3.4.2	Superelevation	3-37
3.3.4.3	Procedure for Development of Method 5 Superelevation Distribution	3-37
3.3.5	Design Superelevation Tables	3-41
3.3.5.1	Minimum Radius of Curve for Section with Normal Crown	3-52
3.3.6	Design for Low-Speed Urban Streets	3-53
3.3.6.1	Side Friction Factors.	3-53
3.3.6.2	Superelevation	3-53

3.3.7	Turning Roadways	3-59
3.3.7.1	Design Speed.	3-59
3.3.7.2	Maximum Superelevation for Turning Roadways.	3-59
3.3.7.3	Use of Compound Curves	3-60
3.3.8	Transition Design Controls.	3-61
3.3.8.1	General Considerations	3-61
3.3.8.2	Tangent-to-Curve Transition.	3-62
3.3.8.2.1	Minimum Length of Superelevation Runoff	3-62
3.3.8.2.2	Minimum Length of Tangent Runout	3-70
3.3.8.2.3	Location with Respect to End of Curve	3-70
3.3.8.2.4	Limiting Superelevation Rates	3-72
3.3.8.3	Spiral Curve Transitions	3-73
3.3.8.4	Length of Spiral	3-74
3.3.8.4.1	Length of Spiral	3-74
3.3.8.4.2	Maximum Radius for Use of a Spiral.	3-75
3.3.8.4.3	Minimum Length of Spiral	3-76
3.3.8.4.4	Maximum Length of Spiral	3-76
3.3.8.4.5	Desirable Length of Spiral	3-77
3.3.8.4.6	Length of Superelevation Runoff	3-78
3.3.8.4.7	Limiting Superelevation Rates	3-78
3.3.8.4.8	Length of Tangent Runout	3-79
3.3.8.4.9	Location with Respect to End of Curve	3-81
3.3.8.5	Compound Curve Transition	3-81
3.3.8.6	Methods of Attaining Superelevation	3-81
3.3.8.7	Design of Smooth Profiles for Traveled-Way Edges.	3-85
3.3.8.8	Axis of Rotation with a Median	3-86
3.3.8.8.1	Case I	3-86
3.3.8.8.2	Case II.	3-86
3.3.8.8.3	Case III	3-86
3.3.8.8.4	Divided Highway	3-87
3.3.8.9	Minimum Transition Grades and Drainage Considerations	3-87
3.3.8.10	Transitions and Compound Curves for Turning Roadways.	3-88

3.3.8.11	Length of Spiral for Turning Roadways	3-89
3.3.8.12	Compound Circular Curves	3-90
3.3.9	Offtracking.	3-91
3.3.9.1	Derivation of Design Values for Widening on Horizontal Curves	3-91
3.3.10	Traveled-Way Widening on Horizontal Curves	3-97
3.3.10.1	Design Values for Traveled-Way Widening	3-101
3.3.10.2	Application of Widening on Curves.	3-101
3.3.11	Widths for Turning Roadways at Intersections	3-103
3.3.11.1	Three Cases	3-105
3.3.11.1.1	Case I	3-105
3.3.11.1.2	Case II.	3-105
3.3.11.1.3	Case III	3-105
3.3.11.2	Design Values	3-107
3.3.11.3	Widths Outside the Traveled Way	3-112
3.3.12	Sight Distance on Horizontal Curves.	3-113
3.3.12.1	Stopping Sight Distance	3-114
3.3.12.2	Passing Sight Distance	3-119
3.3.13	General Controls for Horizontal Alignment.	3-119
3.4	VERTICAL ALIGNMENT	3-121
3.4.1	Terrain	3-121
3.4.2	Grades	3-122
3.4.2.1	Vehicle Operating Characteristics on Grades	3-122
3.4.2.1.1	Passenger Cars	3-122
3.4.2.1.2	Trucks	3-122
3.4.2.1.3	Recreational Vehicles	3-126
3.4.2.2	Control Grades for Design.	3-130
3.4.2.2.1	Maximum Grades	3-130
3.4.2.2.2	Minimum Grades	3-130
3.4.2.2.3	Pedestrian Considerations	3-130
3.4.2.3	Critical Lengths of Grade for Design	3-130
3.4.3	Climbing Lanes	3-137

3.4.3.1	Climbing Lanes for Two-Lane Highways	3-137
3.4.3.1.1	General	3-137
3.4.3.1.2	Trucks	3-139
3.4.3.1.3	Summary	3-141
3.4.3.2	Climbing Lanes on Freeways and Multilane Highways	3-142
3.4.3.2.1	General	3-142
3.4.3.2.2	Trucks	3-142
3.4.4	Methods for Increasing Passing Opportunities on Two-Lane Roads	3-145
3.4.4.1	Passing Lanes	3-145
3.4.4.2	2+1 Roadways	3-149
3.4.4.3	Turnouts	3-152
3.4.4.4	Shoulder Driving	3-153
3.4.4.5	Shoulder Use Sections	3-154
3.4.5	Emergency Escape Ramps	3-154
3.4.5.1	General	3-154
3.4.5.2	Need and Location for Emergency Escape Ramps	3-156
3.4.5.3	Types of Emergency Escape Ramps	3-157
3.4.5.4	Design Considerations	3-159
3.4.5.5	Brake-Check Areas	3-164
3.4.5.6	Maintenance	3-164
3.4.6	Vertical Curves	3-164
3.4.6.1	General Considerations	3-164
3.4.6.2	Crest Vertical Curves	3-166
3.4.6.2.1	Design Controls: Stopping Sight Distance	3-167
3.4.6.2.2	Design Controls: Passing Sight Distance	3-171
3.4.6.3	Sag Vertical Curves	3-172
3.4.6.4	Sight Distance at Undercrossings	3-177
3.4.6.5	General Controls for Vertical Alignment	3-179
3.5	COMBINATIONS OF HORIZONTAL AND VERTICAL ALIGNMENT	3-180
3.5.1	General Considerations	3-180
3.5.2	General Design Controls	3-181

3.5.3	Alignment Coordination in Design	3-182
3.6	OTHER FEATURES AFFECTING GEOMETRIC DESIGN	3-186
3.6.1	Erosion Control and Landscape Development	3-186
3.6.2	Rest Areas, Information Centers, and Scenic Overlooks.	3-187
3.6.3	Lighting	3-188
3.6.4	Utilities.	3-190
3.6.4.1	General.	3-191
3.6.4.2	Rural Areas	3-192
3.6.4.3	Urban Areas	3-192
3.6.5	Traffic Control Devices.	3-193
3.6.5.1	Traffic Signs, Pavement Markings, and Traffic Signals	3-193
3.6.5.2	Intelligent Transportation Systems	3-194
3.6.6	Traffic Management Plans for Construction	3-195
3.7	REFERENCES	3-196

CHAPTER 4 CROSS-SECTION ELEMENTS

4.1	GENERAL	4-1
4.2	TRAVELED WAY	4-1
4.2.1	Surface Type	4-1
4.2.2	Cross Slope	4-2
4.2.2.1	Rate of Cross Slope	4-6
4.2.2.2	Weather Considerations.	4-7
4.2.2.3	Unpaved Surfaces.	4-7
4.2.3	Skid Resistance	4-8
4.2.4	Hydroplaning	4-8
4.3	LANE WIDTHS	4-9
4.4	SHOULDERS	4-10
4.4.1	General Characteristics	4-10
4.4.2	Shoulder Width	4-12
4.4.3	Shoulder Cross Sections	4-13
4.4.4	Shoulder Stability.	4-14

4.4.5	Shoulder Contrast	4-15
4.4.6	Turnouts	4-16
4.5	RUMBLE STRIPS	4-16
4.6	ROADSIDE DESIGN	4-17
4.6.1	Clear Zones	4-17
4.6.2	Lateral Offset	4-18
4.7	CURBS	4-19
4.7.1	General Considerations	4-19
4.7.2	Curb Configurations	4-19
4.7.2.1	Gutters	4-21
4.7.3	Curb Placement	4-22
4.8	DRAINAGE CHANNELS AND SIDESLOPES	4-23
4.8.1	General Considerations	4-23
4.8.2	Drainage	4-23
4.8.3	Drainage Channels	4-26
4.8.4	Sideslopes	4-28
4.9	ILLUSTRATIVE OUTER CROSS SECTIONS	4-32
4.9.1	Normal Crown Sections	4-32
4.9.2	Superelevated Sections	4-32
4.10	TRAFFIC BARRIERS	4-33
4.10.1	General Considerations	4-33
4.10.2	Longitudinal Barriers	4-34
4.10.2.1	Roadside Barriers	4-34
4.10.2.2	Median Barriers	4-35
4.10.3	Bridge Railings	4-37
4.10.4	Crash Cushions	4-38
4.11	MEDIANS	4-38
4.12	FRONTAGE ROADS	4-41
4.13	OUTER SEPARATIONS	4-45
4.14	ROADWAY TRAFFIC NOISE ABATEMENT	4-46

4.14.1	General Considerations	4-46
4.14.2	Noise Evaluation Procedures.	4-47
4.14.3	Noise Reduction	4-48
4.15	ROADSIDE CONTROL	4-52
4.15.1	General Considerations.	4-52
4.15.2	Driveways.	4-52
4.15.3	Mailboxes	4-56
4.15.4	Fencing	4-57
4.16	TUNNELS	4-57
4.16.1	General Considerations.	4-57
4.16.2	Types of Tunnels	4-58
4.16.3	General Design Considerations.	4-59
4.16.4	Tunnel Sections	4-60
4.16.5	Examples of Tunnels	4-63
4.17	PEDESTRIAN FACILITIES	4-65
4.17.1	Sidewalks	4-65
4.17.2	Grade-Separated Pedestrian Crossings	4-67
4.17.3	Curb Ramps.	4-70
4.18	BICYCLE FACILITIES	4-77
4.19	TRANSIT FACILITIES	4-77
4.19.1	Bus Turnouts on Freeways.	4-79
4.19.2	Bus Turnouts on Arterials.	4-80
4.19.3	Park-and-Ride Facilities	4-82
4.19.3.1	Location	4-82
4.19.3.2	Design	4-82
4.20	ON-STREET PARKING	4-85
4.21	REFERENCES	4-88
 CHAPTER 5 LOCAL ROADS AND STREETS		
5.1	INTRODUCTION.	5-1
5.2	LOCAL ROADS IN RURAL AREAS	5-2

5.2.1	General Design Considerations	5-2
5.2.1.1	Design Speed	5-2
5.2.1.2	Design Traffic Volume	5-3
5.2.1.3	Levels of Service	5-3
5.2.1.4	Alignment	5-3
5.2.1.5	Grades	5-3
5.2.1.6	Cross Slope	5-4
5.2.2	Cross-Sectional Elements	5-6
5.2.2.1	Width of Roadway	5-6
5.2.2.2	Number of Lanes	5-6
5.2.2.3	Right-of-Way Width	5-7
5.2.2.4	Medians	5-7
5.2.2.5	Bicycle and Pedestrian Facilities	5-8
5.2.2.6	Driveways	5-8
5.2.2.7	Structures	5-9
5.2.2.7.1	New and Reconstructed Structures	5-9
5.2.2.7.2	Vertical Clearance	5-9
5.2.2.8	Roadside Design	5-9
5.2.2.8.1	Clear Zones	5-10
5.2.2.8.2	Lateral Offset	5-10
5.2.2.8.3	Foreslopes	5-10
5.2.2.9	Intersection Design	5-11
5.2.2.10	Railroad–Highway Grade Crossings	5-11
5.2.2.11	Traffic Control Devices	5-12
5.2.2.12	Drainage	5-12
5.2.2.13	Erosion Control and Landscaping	5-12
5.2.2.14	Design of Local Streets in the Rural Town Context	5-12
5.3	LOCAL STREETS IN URBAN AREAS	5-12
5.3.1	General Design Considerations	5-13
5.3.1.1	Design Speed	5-14
5.3.1.2	Design Traffic Volume	5-14
5.3.1.3	Levels of Service	5-14

5.3.1.4	Alignment	5-14
5.3.1.5	Grades	5-15
5.3.1.6	Cross Slope	5-15
5.3.1.7	Superelevation	5-15
5.3.1.8	Sight Distance	5-16
5.3.2	Cross-Sectional Elements	5-16
5.3.2.1	Width of Traveled Way	5-16
5.3.2.2	Number of Lanes	5-16
5.3.2.3	Parking Lanes	5-16
5.3.2.4	Medians	5-17
5.3.2.5	Curbs	5-17
5.3.2.6	Right-of-Way Width	5-17
5.3.2.7	Provision for Utilities	5-17
5.3.2.8	Border Area	5-18
5.3.2.9	Bicycle and Pedestrian Facilities	5-18
5.3.2.10	Cul-de-Sacs and Turnarounds	5-19
5.3.2.11	Alleys	5-20
5.3.2.12	Driveways	5-21
5.3.3	Structures	5-22
5.3.3.1	New and Reconstructed Structures	5-22
5.3.3.2	Vertical Clearance	5-23
5.3.4	Roadside Design	5-23
5.3.4.1	Clear Zones	5-23
5.3.4.2	Lateral Offset	5-23
5.3.5	Intersection Design	5-23
5.3.6	Railroad–Highway Grade Crossings	5-25
5.3.7	Traffic Control Devices	5-25
5.3.8	Roadway Lighting	5-25
5.3.9	Drainage	5-26
5.3.10	Erosion Control	5-26
5.3.11	Landscaping	5-27
5.4	RECREATIONAL ROADS	5-27

5.4.1	General Design Considerations	5-27
5.4.1.1	Design Speed	5-28
5.4.1.2	Design Vehicle	5-29
5.4.1.3	Grades	5-29
5.4.1.4	Vertical Alignment	5-30
5.4.1.5	Horizontal Alignment and Superelevation	5-31
5.4.1.6	Sight Distance	5-32
5.4.1.7	Passing Sight Distance	5-32
5.4.1.8	Cross Slope	5-33
5.4.2	Cross-Sectional Elements	5-33
5.4.2.1	Width of Roadway	5-33
5.4.2.2	Number of Lanes	5-34
5.4.3	Structures	5-35
5.4.4	Roadside Design	5-36
5.4.4.1	Clear Zones	5-36
5.4.4.2	Roadside Slopes	5-36
5.4.4.3	Roadside Barriers	5-37
5.4.5	Signing and Marking	5-37
5.4.6	Bicycle and Pedestrian Facilities	5-37
5.5	RESOURCE RECOVERY AND LOCAL SERVICE ROADS	5-37
5.6	LOW-VOLUME ROADS	5-39
5.7	REFERENCES	5-39

CHAPTER 6 COLLECTOR ROADS AND STREETS

6.1	INTRODUCTION	6-1
6.2	COLLECTORS IN RURAL AREAS	6-2
6.2.1	General Design Considerations	6-2
6.2.1.1	Design Speed	6-2
6.2.1.2	Design Traffic Volumes	6-3
6.2.1.3	Level of Service	6-3
6.2.1.4	Alignment	6-3

6.2.1.5	Grades	6-4
6.2.1.6	Cross Slope	6-4
6.2.1.7	Superelevation	6-4
6.2.1.8	Sight Distance	6-4
6.2.2	Cross-Sectional Elements	6-6
6.2.2.1	Width of Roadway	6-6
6.2.2.2	Number of Lanes	6-6
6.2.2.3	Parking Lanes	6-7
6.2.2.4	Medians	6-7
6.2.2.5	Right-of-Way Width	6-7
6.2.2.6	Bicycle/Pedestrian Facilities	6-7
6.2.3	Structures	6-7
6.2.3.1	New and Reconstructed Structures	6-7
6.2.3.2	Vertical Clearance	6-8
6.2.4	Roadside Design	6-8
6.2.4.1	Clear Zones	6-8
6.2.4.2	Lateral Offset	6-8
6.2.4.3	Foreslopes	6-9
6.2.5	Intersection Design	6-9
6.2.6	Railroad–Highway Grade Crossings	6-10
6.2.7	Traffic Control Devices	6-10
6.2.8	Drainage	6-10
6.2.9	Erosion Control and Landscaping	6-10
6.2.10	Speed Transitions Entering Rural Towns	6-10
6.2.11	Design of Collectors in the Rural Town Context	6-12
6.3	COLLECTORS IN URBAN AREAS	6-12
6.3.1	General Design Considerations	6-13
6.3.1.1	Design Speed	6-13
6.3.1.2	Design Traffic Volumes	6-14
6.3.1.3	Level of Service	6-14
6.3.1.4	Alignment	6-14
6.3.1.5	Grades	6-14

6.3.1.6	Cross Slope	6-15
6.3.1.7	Superelevation	6-15
6.3.1.8	Sight Distance	6-15
6.3.2	Cross-Sectional Elements	6-16
6.3.2.1	Width of Roadway	6-16
6.3.2.2	Number of Lanes	6-16
6.3.2.3	Parking Lanes	6-16
6.3.2.4	Medians	6-17
6.3.2.5	Curbs	6-18
6.3.2.6	Right-of-Way Width	6-18
6.3.2.7	Provision for Utilities	6-19
6.3.2.8	Border Area	6-19
6.3.2.9	Bicycle/Pedestrian Facilities	6-19
6.3.2.10	Driveways	6-20
6.3.3	Structures	6-20
6.3.3.1	New and Reconstructed Structures	6-20
6.3.3.2	Vertical Clearance	6-20
6.3.4	Roadside Design	6-21
6.3.4.1	Clear Zones	6-21
6.3.4.2	Lateral Offset	6-21
6.3.5	Intersection Design	6-22
6.3.6	Railroad–Highway Grade Crossings	6-23
6.3.7	Traffic Control Devices	6-23
6.3.8	Roadway Lighting	6-23
6.3.9	Drainage	6-24
6.3.10	Erosion Control	6-24
6.3.11	Landscaping	6-24
6.4	REFERENCES	6-25

CHAPTER 7 ARTERIAL ROADS AND STREETS

7.1	INTRODUCTION	7-1
7.2	ARTERIALS IN RURAL AREAS	7-2

7.2.1	General Characteristics	7-2
7.2.2	General Design Considerations.	7-3
7.2.2.1	Design Speed.	7-3
7.2.2.2	Design Traffic Volumes.	7-3
7.2.2.3	Level of Service	7-4
7.2.2.4	Sight Distance	7-4
7.2.2.5	Alignment.	7-5
7.2.2.6	Grades	7-5
7.2.2.7	Cross Slope	7-6
7.2.2.8	Superelevation	7-6
7.2.3	Cross-Sectional Elements	7-6
7.2.3.1	Roadway Width	7-6
7.2.3.2	Number of Lanes	7-7
7.2.3.3	Cross Section and Right-of-Way.	7-7
7.2.4	Roadside Design	7-8
7.2.4.1	Clear Zones	7-8
7.2.4.2	Lateral Offset	7-8
7.2.5	Structures.	7-9
7.2.5.1	Vertical Clearances.	7-9
7.2.6	Traffic Control Devices.	7-9
7.2.7	Erosion Control	7-9
7.2.8	Provision for Passing	7-9
7.2.9	Ultimate Development of Multilane Divided Arterials in Rural Areas	7-11
7.2.10	Multilane Undivided Arterials in Rural Areas.	7-13
7.2.11	Divided Arterials in Rural Areas.	7-15
7.2.11.1	General Features	7-15
7.2.11.2	Lane Widths	7-15
7.2.11.3	Cross Slope	7-15
7.2.11.4	Shoulders	7-16
7.2.11.5	Median Barrier Clearance.	7-17
7.2.11.6	Medians	7-17

7.2.11.7	Alignment and Profile	7-18
7.2.11.8	Climbing Lanes on Multilane Arterials in Rural Areas.	7-19
7.2.11.9	Superelevated Cross Sections	7-20
7.2.11.10	Cross Section and Right-of-Way Widths	7-24
7.2.11.11	Sections with Widely Separated Roadways	7-28
7.2.12	Intersections	7-29
7.2.13	Access Management	7-29
7.2.14	Bicycle and Pedestrian Facilities	7-30
7.2.15	Bus Turnouts	7-30
7.2.16	Railroad–Highway Grade Crossings	7-31
7.2.17	Lighting	7-31
7.2.18	Rest Areas	7-32
7.2.19	Speed Transitions Entering Rural Towns	7-32
7.2.20	Design of Arterials in the Rural Town Context	7-34
7.3	ARTERIALS IN URBAN AREAS	7-34
7.3.1	General Characteristics	7-35
7.3.2	General Design Considerations.	7-36
7.3.2.1	Design Speed.	7-36
7.3.2.2	Design Traffic Volumes	7-36
7.3.2.3	Level of Service	7-37
7.3.2.4	Sight Distance	7-37
7.3.2.5	Alignment.	7-37
7.3.2.6	Grades	7-37
7.3.2.7	Superelevation	7-38
7.3.2.8	Cross Slope	7-38
7.3.3	Cross-Sectional Elements	7-39
7.3.3.1	Roadway Widths.	7-39
7.3.3.2	Lane Widths	7-39
7.3.3.3	Curbs and Shoulders	7-40
7.3.3.4	Number of Lanes	7-40
7.3.3.5	Medians	7-40
7.3.3.6	Drainage.	7-45

7.3.3.7	Parking Lanes	7-45
7.3.3.8	Borders and Sidewalks	7-46
7.3.3.9	Right-of-Way Width	7-48
7.3.4	Roadside Design	7-49
7.3.4.1	Clear Zones	7-49
7.3.4.2	Lateral Offset	7-49
7.3.5	Structures	7-50
7.3.5.1	New and Reconstructed Structures	7-50
7.3.5.2	Vertical Clearances	7-51
7.3.6	Traffic Barriers	7-51
7.3.7	Railroad–Highway Grade Crossings	7-51
7.3.8	Access Management	7-51
7.3.8.1	General Features	7-51
7.3.8.2	Access Control by Statute	7-52
7.3.8.3	Access Control by Zoning	7-52
7.3.8.4	Access Control through Driveway Regulations	7-53
7.3.8.5	Access Control through Geometric Design	7-53
7.3.9	Bicycle and Pedestrian Facilities	7-54
7.3.9.1	Bicycle Facilities	7-54
7.3.9.2	Pedestrian Facilities	7-54
7.3.10	Provision for Utilities	7-56
7.3.11	Intersection Design	7-56
7.3.12	Operational Control	7-56
7.3.12.1	Traffic Control Devices	7-57
7.3.12.2	Provision and Management of Curb Parking	7-58
7.3.13	Speed Management in Design	7-58
7.3.14	Directional Lane Usage	7-59
7.3.14.1	One-Way Operation	7-59
7.3.14.2	Reverse-Flow Operation	7-60
7.3.15	Frontage Roads and Outer Separations	7-62
7.3.16	Grade Separations and Interchanges	7-63
7.3.17	Erosion Control	7-64

7.3.18	Lighting	7-64
7.3.19	Public Transit Facilities.	7-65
7.3.19.1	Location of Bus Stops.	7-66
7.3.19.2	Bus Turnouts.	7-67
7.3.19.3	Reserved Bus Lanes	7-68
7.3.19.4	Traffic Control Measures.	7-69
7.4	REFERENCES	7-69

CHAPTER 8 FREEWAYS

8.1	INTRODUCTION.	8-1
8.2	GENERAL DESIGN CONSIDERATIONS.	8-2
8.2.1	Design Speed	8-2
8.2.2	Design Traffic Volumes.	8-2
8.2.3	Levels of Service	8-3
8.2.4	Traveled Way and Shoulders	8-3
8.2.5	Curbs	8-4
8.2.6	Superelevation.	8-4
8.2.7	Grades	8-4
8.2.8	Structures.	8-5
8.2.9	Vertical Clearance	8-5
8.2.10	Roadside Design	8-6
8.2.11	Ramps and Terminals.	8-6
8.2.12	Outer Separations, Borders, and Frontage Roads	8-6
8.3	FREEWAYS IN RURAL AREAS.	8-7
8.3.1	Alignment and Profile	8-7
8.3.2	Medians	8-9
8.3.3	Sideslopes	8-11
8.3.4	Frontage Roads	8-12
8.4	FREEWAYS IN URBAN AREAS	8-12
8.4.1	General Design Characteristics	8-12
8.4.2	Medians	8-13

8.4.3	Depressed Freeways	8-13
8.4.3.1	General Characteristics	8-13
8.4.3.2	Slopes and Walls	8-14
8.4.3.3	Typical Cross Section	8-15
8.4.3.4	Restrictive Cross Section	8-15
8.4.3.5	Walled Cross Section	8-16
8.4.3.6	Example of Depressed Freeway	8-17
8.4.4	Elevated Freeways	8-19
8.4.4.1	General Characteristics	8-19
8.4.4.2	Medians	8-20
8.4.4.3	Ramps and Terminals	8-20
8.4.4.4	Frontage Roads	8-20
8.4.4.5	Building Offset	8-20
8.4.4.6	Typical Cross Section	8-21
8.4.4.7	Freeways on Earth Embankment	8-23
8.4.4.8	Examples of Elevated Freeways	8-24
8.4.5	Ground-Level Freeways	8-26
8.4.5.1	General Characteristics	8-26
8.4.5.2	Typical Cross Section	8-26
8.4.5.3	Restrictive Cross Section	8-27
8.4.5.4	Example of a Ground-Level Freeway	8-28
8.4.6	Combination-Type Freeways	8-28
8.4.6.1	General Characteristics	8-28
8.4.6.2	Profile Control	8-28
8.4.6.2.1	Rolling Terrain	8-28
8.4.6.2.2	Level Terrain	8-29
8.4.6.3	Cross-Section Control	8-30
8.4.7	Special Freeway Designs	8-33
8.4.7.1	Reverse-Flow Roadways	8-33
8.4.7.2	Dual-Divided Freeways	8-36
8.4.7.3	Freeways with Collector–Distributor Roads	8-39
8.4.8	Accommodation of Managed Lanes and Transit Facilities	8-39

8.4.8.1	General Considerations	8-39
8.4.8.2	Buses	8-41
8.4.8.2.1	Exclusive HOV Lanes	8-41
8.4.8.2.2	Bus Stops	8-41
8.4.8.2.3	Bus-Stop Arrangements	8-41
8.4.8.2.4	Bus Stops at Freeway Level	8-41
8.4.8.2.5	Bus Stops at Street Level	8-45
8.4.8.2.6	Stairs, Ramps, Escalators, and Elevators.	8-46
8.4.8.3	Rail Transit	8-47
8.4.8.3.1	Typical Sections	8-48
8.4.8.3.2	Stations.	8-49
8.4.8.3.3	Example of Rail Transit Combined with a Freeway	8-50
8.5	REFERENCES	8-51

CHAPTER 9 INTERSECTIONS

9.1	INTRODUCTION.	9-1
9.2	GENERAL DESIGN CONSIDERATIONS AND OBJECTIVES	9-2
9.2.1	Characteristics of Intersections	9-2
9.2.2	Intersection Functional Area	9-3
9.2.3	Design Objectives	9-4
9.2.4	Design Considerations for Intersection User Groups	9-6
9.2.5	Intersection Capacity.	9-9
9.2.6	Intersection Design Elements	9-10
9.3	TYPES AND EXAMPLES OF INTERSECTIONS.	9-11
9.3.1	Three-Leg Intersections.	9-14
9.3.1.1	Basic Types of Intersections	9-14
9.3.1.2	Channelized Three-Leg Intersections.	9-15
9.3.2	Four-Leg Intersections.	9-18
9.3.2.1	Basic Types.	9-18
9.3.2.2	Channelized Four-Leg Intersections.	9-19
9.3.3	Multileg Intersections	9-24

9.3.4	Roundabouts	9-26
9.3.4.1	Mini-Roundabouts	9-28
9.3.4.2	Single-Lane Roundabouts	9-29
9.3.4.3	Multilane Roundabouts	9-30
9.4	ALIGNMENT AND PROFILE	9-31
9.4.1	General Considerations	9-31
9.4.2	Alignment	9-31
9.4.3	Profile	9-33
9.5	INTERSECTION SIGHT DISTANCE	9-35
9.5.1	General Considerations	9-35
9.5.2	Sight Triangles	9-36
9.5.2.1	Approach Sight Triangles	9-36
9.5.2.2	Departure Sight Triangles	9-38
9.5.2.3	Identification of Sight Obstructions within Sight Triangles	9-38
9.5.3	Intersection Control	9-39
9.5.3.1	Case A—Intersections with No Control	9-40
9.5.3.2	Case B—Intersections with Stop Control on the Minor Road	9-42
9.5.3.2.1	Case B1—Left Turn from the Minor Road	9-43
9.5.3.2.2	Case B2—Right Turn from the Minor Road	9-47
9.5.3.2.3	Case B3—Crossing Maneuver from the Minor Road	9-48
9.5.3.3	Case C—Intersections with Yield Control on the Minor Road	9-50
9.5.3.3.1	Case C1—Crossing Maneuver from the Minor Road	9-51
9.5.3.3.2	Case C2—Left- and Right-Turn Maneuvers	9-53
9.5.3.4	Case D—Intersections with Traffic Signal Control	9-55
9.5.3.5	Case E—Intersections with All-Way Stop Control	9-56
9.5.3.6	Case F—Left Turns from the Major Road	9-56
9.5.3.7	Case G—Roundabouts	9-58
9.5.4	Effect of Skew	9-58
9.6	TURNING ROADWAYS AND CHANNELIZATION	9-59
9.6.1	Turning Roadways	9-60

- 9.6.1.1 General 9-60
- 9.6.1.2 Channelized Right-Turn Lanes 9-60
- 9.6.1.3 Design Considerations 9-63
- 9.6.1.4 Curb Radius 9-65
- 9.6.2 Channelization 9-67
- 9.6.3 Islands 9-69
 - 9.6.3.1 General Characteristics 9-69
 - 9.6.3.2 Channelizing Islands. 9-70
 - 9.6.3.3 Divisional Islands 9-72
 - 9.6.3.4 Refuge Islands 9-74
 - 9.6.3.5 Island Size and Designation 9-74
 - 9.6.3.6 Island Delineation and Approach Treatment 9-75
 - 9.6.3.7 Corner Islands for Turning Roadways. 9-82
- 9.6.4 Superelevation for Turning Roadways at Intersections 9-83
 - 9.6.4.1 General Design Guidelines 9-83
 - 9.6.4.2 Superelevation Runoff 9-83
 - 9.6.4.3 Development of Superelevation at Turning Roadway
Terminals 9-84
- 9.6.5 Stopping Sight Distance at Intersections for Turning Roadways . . 9-91
 - 9.6.5.1 General Considerations 9-91
 - 9.6.5.2 Vertical Control. 9-91
 - 9.6.5.3 Horizontal Control 9-92
- 9.7 AUXILIARY LANES 9-92
 - 9.7.1 General Design Considerations. 9-92
 - 9.7.2 Deceleration Lanes 9-94
 - 9.7.2.1 Perception—Reaction Distance 9-94
 - 9.7.2.2 Storage Length. 9-96
 - 9.7.2.3 Taper Length 9-100
 - 9.7.3 Design Treatments for Left-Turn Maneuvers 9-105
 - 9.7.3.1 Guidelines for Provision and Design of Left-Turn and Bypass
Lanes 9-105
 - 9.7.3.2 Median Left-Turn Lanes 9-110

9.7.3.3	Median End Treatment.	9-113
9.7.3.4	Offset Left-Turn Lanes	9-113
9.7.3.5	Simultaneous Left Turns	9-115
9.7.3.6	Double or Triple Left-Turn Lanes	9-116
9.8	MEDIAN OPENINGS	9-118
9.8.1	General Design Considerations.	9-118
9.8.2	Control Radii for Minimum Turning Paths	9-119
9.8.2.1	Shape of Median End.	9-120
9.8.3	Effect of Skew	9-121
9.8.4	Design Considerations for Higher Speed Left Turns.	9-122
9.9	INDIRECT LEFT TURNS AND U-TURNS.	9-124
9.9.1	General Design Considerations.	9-124
9.9.2	Intersections with Jughandle or Loop Roadways	9-126
9.9.3	Displaced Left-Turn Intersections	9-129
9.9.4	Wide Medians with U-Turn Crossover Roadways	9-130
9.9.5	Location and Design of U-Turn Median Openings	9-136
9.10	ROUNDBOUT DESIGN.	9-141
9.10.1	Geometric Elements of Roundabouts	9-143
9.10.1.1	Size and Space Needs	9-144
9.10.2	Fundamental Principles	9-145
9.10.2.1	Slow Speeds Using Deflection	9-146
9.10.2.2	Lane Balance and Lane Continuity.	9-146
9.10.2.3	Appropriate Natural Path Alignment	9-148
9.10.2.4	Design Vehicle	9-149
9.10.2.5	Nonmotorized Users	9-150
9.10.2.6	Sight Distance and Visibility.	9-151
9.11	OTHER INTERSECTION DESIGN CONSIDERATIONS.	9-151
9.11.1	Intersection Design Elements with Frontage Roads	9-151
9.11.2	Traffic Control Devices.	9-155
9.11.3	Bicyclists.	9-156
9.11.4	Pedestrians	9-156

9.11.5	Lighting	9-156
9.11.6	Driveways.	9-157
9.11.7	Left Turns at Midblock Locations and at Unsignalized Intersections on Streets with Flush Medians	9-158
9.12	RAILROAD–HIGHWAY GRADE CROSSINGS	9-159
9.12.1	Horizontal Alignment.	9-159
9.12.2	Vertical Alignment	9-160
9.12.3	Crossing Design.	9-161
9.12.4	Sight Distance	9-162
9.13	REFERENCES	9-168

CHAPTER 10 GRADE SEPARATIONS AND INTERCHANGES

10.1	INTRODUCTION AND GENERAL TYPES OF INTERCHANGES	10-1
10.2	WARRANTS FOR INTERCHANGES AND GRADE SEPARATIONS	10-3
10.3	ADAPTABILITY OF HIGHWAY GRADE SEPARATIONS AND INTERCHANGES.	10-6
10.3.1	Traffic and Operation.	10-6
10.3.2	Site Conditions	10-7
10.3.3	Type of Highway and Intersecting Facility.	10-7
10.4	ACCESS SEPARATIONS AND CONTROL ON THE CROSSROAD AT INTER- CHANGES.	10-8
10.5	SAFETY	10-9
10.6	STAGE DEVELOPMENT	10-10
10.7	ECONOMIC FACTORS.	10-11
10.7.1	Initial Costs	10-11
10.7.2	Maintenance Costs	10-11
10.7.3	Vehicular Operating Costs.	10-11
10.8	GRADE SEPARATION STRUCTURES	10-11
10.8.1	Introduction	10-11
10.8.2	Types of Separation Structures	10-12
10.8.3	Overpass versus Underpass Roadways	10-18

10.8.3.1	General Design Considerations	10-18
10.8.3.2	Structure Widths.	10-21
10.8.4	Underpass Roadways.	10-22
10.8.4.1	Lateral Offset	10-22
10.8.4.2	Vertical Clearance.	10-24
10.8.5	Overpass Roadways.	10-25
10.8.5.1	Bridge Railings	10-25
10.8.5.2	Lateral Offset	10-26
10.8.5.3	Medians	10-27
10.8.6	Longitudinal Distance to Attain Grade Separation	10-27
10.8.7	Grade Separations without Ramps	10-29
10.9	INTERCHANGES.	10-30
10.9.1	General Considerations.	10-30
10.9.2	Three-Leg Designs.	10-31
10.9.3	Four-Leg Designs.	10-39
10.9.3.1	Ramps in One Quadrant	10-39
10.9.3.2	Diamond Interchanges.	10-40
10.9.3.3	Roundabout Interchanges	10-47
10.9.3.4	Single-Point Diamond Interchanges.	10-48
10.9.3.5	Diverging Diamond Interchanges	10-53
10.9.3.6	Cloverleaf Interchanges	10-57
10.9.3.6.1	Partial Cloverleaf Ramp Arrangements.	10-60
10.9.3.7	Directional Interchanges	10-63
10.9.3.7.1	With Loops and Weaving	10-66
10.9.3.7.2	With Loops and No Weaving	10-67
10.9.3.7.3	Fully Directional	10-67
10.9.4	Other Interchange Configurations.	10-72
10.9.4.1	Offset Interchanges	10-72
10.9.4.2	Combination Interchanges.	10-72
10.9.5	General Design Considerations.	10-76
10.9.5.1	Determination of Interchange Configuration.	10-76
10.9.5.2	Approaches to the Structure	10-79

10.9.5.2.1	Alignment, Profile, and Cross Section	10-79
10.9.5.2.2	Sight Distance.	10-81
10.9.5.3	Interchange Spacing	10-82
10.9.5.4	Uniformity of Interchange Patterns	10-82
10.9.5.5	Route Continuity	10-83
10.9.5.6	Overlapping Routes.	10-84
10.9.5.7	Signing and Marking	10-86
10.9.5.8	Basic Number of Lanes	10-86
10.9.5.9	Coordination of Lane Balance and Basic Number of Lanes. . .	10-87
10.9.5.10	Auxiliary Lanes	10-90
10.9.5.11	Lane Reductions.	10-93
10.9.5.12	Weaving Sections.	10-94
10.9.5.13	Collector–Distributor Roads.	10-95
10.9.5.14	Two-Exit versus Single-Exit Interchange Design	10-96
10.9.5.15	Wrong-Way Entry.	10-98
10.9.6	Ramps	10-102
10.9.6.1	Types and Examples.	10-102
10.9.6.2	General Ramp Design Considerations	10-105
10.9.6.2.1	Design Speed.	10-105
10.9.6.2.2	Portion of Ramp to Which Design Speed Is Applicable	10-105
10.9.6.2.3	Ramps for Right Turns.	10-105
10.9.6.2.4	Loop Ramps	10-106
10.9.6.2.5	Two-Lane Loop Ramps	10-106
10.9.6.2.6	Semidirect Connections	10-106
10.9.6.2.7	Direct Connections.	10-106
10.9.6.2.8	Different Design Speeds on Intersecting Highways	10-106
10.9.6.2.9	At-Grade Terminals.	10-106
10.9.6.2.10	Curvature	10-107
10.9.6.2.11	Sight Distance.	10-109
10.9.6.2.12	Grade and Profile Design	10-109

	10.9.6.2.13	Vertical Curves	10-111
	10.9.6.2.14	Superelevation and Cross Slope.	10-111
	10.9.6.2.15	Gores	10-114
10.9.6.3		Ramp Traveled-Way Widths	10-121
	10.9.6.3.1	Width and Cross Section	10-121
	10.9.6.3.2	Shoulder Widths and Lateral Offset	10-121
	10.9.6.3.3	Shoulders and Curbs	10-122
10.9.6.4		Ramp Terminals	10-123
	10.9.6.4.1	Left-Side Entrances and Exits	10-123
	10.9.6.4.2	Terminal Location and Sight Distance	10-123
	10.9.6.4.3	Ramp Terminal Design	10-124
	10.9.6.4.4	Traffic Control	10-124
	10.9.6.4.5	Distance between a Free-Flow Terminal and Structure	10-124
	10.9.6.4.6	Distance between Successive Ramp Terminals	10-126
	10.9.6.4.7	Speed-Change Lanes	10-128
10.9.6.5		Single-Lane Free-Flow Terminals, Entrances	10-128
	10.9.6.5.1	Taper-Type Entrances	10-128
	10.9.6.5.2	Parallel-Type Entrances.	10-130
10.9.6.6		Single-Lane Free-Flow Terminals, Exits	10-135
	10.9.6.6.1	Taper-Type Exits	10-135
	10.9.6.6.2	Parallel-Type Exits.	10-136
	10.9.6.6.3	Free-Flow Terminals on Curves.	10-139
	10.9.6.6.4	Multilane Free-Flow Terminals	10-143
	10.9.6.6.5	Two-Lane Entrances	10-143
	10.9.6.6.6	Two-Lane Exits	10-146
	10.9.6.6.7	Two-Lane Terminals on Curved Alignment.	10-147
	10.9.6.6.8	Major Forks and Branch Connections.	10-147
10.9.7		Other Interchange Design Features	10-150
	10.9.7.1	Testing for Ease of Operation	10-150
	10.9.7.2	Pedestrian and Bicycle Accommodation	10-151

10.9.7.3	Managed Lanes and Transit Facilities	10-152
10.9.7.4	Ramp Metering	10-152
10.9.7.5	Grading and Landscape Development	10-153
10.9.7.5.1	Contour Grading Design	10-153
10.9.7.5.2	Plantings	10-154
10.9.7.6	Models	10-154
10.10	REFERENCES	10-155

LIST OF FIGURES

CHAPTER 1 HIGHWAY FUNCTIONS

Figure 1-1. Framework for Roadway Design Based on Functional Classification and Roadway Context	1-6
Figure 1-2. Hierarchy of Movement	1-9
Figure 1-3. Relationship of Functionally Classified Systems Serving Traffic Mobility and Land Access for Motor-Vehicle Traffic	1-11
Figure 1-4. Typical Road in the Rural Context	1-18
Figure 1-5. Typical Street in the Rural Town Context.	1-18
Figure 1-6. Typical Street in the Suburban Context.	1-19
Figure 1-7. Typical Street in the Urban Context	1-19
Figure 1-8. Typical Street in the Urban Core Context	1-20

CHAPTER 2 DESIGN CONTROLS AND CRITERIA

Figure 2-1. Median Driver Reaction Time to Expected and Unexpected Information	2-6
Figure 2-2. 85th-Percentile Driver Reaction Time to Expected and Unexpected Information	2-7
Figure 2-3. Relation between Peak-Hour and Average Daily Traffic Volumes on Arterials in Rural Areas	2-15
Figure 2-4. Generalized Speed-Volume-Density Relationships (44)	2-28
Figure 2-5. Weaving Sections	2-39
Figure 2-6. Simple and Multiple Weaving Sections	2-40
Figure 2-7. Estimated Crash Rates by Type of Median—Urban and Suburban Areas (25)	2-47
Figure 2-8. Estimated Crash Rates by Type of Median—Rural Areas (25).	2-48
Figure 2-9. Estimated Crash Rates by Unsignalized and Signalized Access Density—Urban and Suburban Areas (25)	2-49
Figure 2-10. Minimum Turning Path for Passenger Car (P) Design Vehicle	2-64
Figure 2-11. Minimum Turning Path for Single-Unit Truck (SU-30 [SU-9]) Design Vehicle	2-65
Figure 2-12. Minimum Turning Path for Single-Unit Truck (SU-40 [SU-12]) Design Vehicle	2-66
Figure 2-13. Minimum Turning Path for Intercity Bus (BUS-40 [BUS-12]) Design Vehicle	2-67
Figure 2-14. Minimum Turning Path for Intercity Bus (BUS-45 [BUS-14]) Design Vehicle	2-68
Figure 2-15. Minimum Turning Path for City Transit Bus (CITY-BUS) Design Vehicle.	2-69
Figure 2-16. Minimum Turning Path for Conventional School Bus (S-BUS-36 [S-BUS-11]) Design Vehicle	2-70

Figure 2-17. Minimum Turning Path for Large School Bus (S-BUS-40 [S-BUS-12]) Design Vehicle 2-71

Figure 2-18. Minimum Turning Path for Articulated Bus (A-BUS) Design Vehicle 2-72

Figure 2-19. Turning Characteristics of a Typical Tractor–Semitrailer Combination Truck 2-73

Figure 2-20. Computational Method for Determining the Centerline Turning Radius for Tractor–Semitrailer Combination Trucks 2-73

Figure 2-21. Lengths of Commonly Used Truck Tractors 2-74

Figure 2-22. Minimum Turning Path for Intermediate Semitrailer (WB-40 [WB-12]) Design Vehicle . . 2-75

Figure 2-23. Minimum Turning Path for Interstate Semitrailer (WB-62 [WB-19]) Design Vehicle 2-76

Figure 2-24. Minimum Turning Path for Interstate Semitrailer (WB-67 [WB-20]) Design Vehicle 2-77

Figure 2-25. Minimum Turning Path for Double-Trailer Combination (WB-67D [WB-20D]) Design Vehicle 2-78

Figure 2-26. Minimum Turning Path for Rocky Mountain Double-Trailer Combination (WB-92D [WB-28D]) Design Vehicle. 2-79

Figure 2-27. Minimum Turning Path for Triple-Trailer Combination (WB-100T [WB-30T]) Design Vehicle 2-80

Figure 2-28. Minimum Turning Path for Turnpike-Double Combination (WB-109D [WB-33D]) Design Vehicle 2-81

Figure 2-29. Minimum Turning Path for Motor Home (MH) Design Vehicle 2-82

Figure 2-30. Minimum Turning Path for Passenger Car and Camper Trailer (P/T) Design Vehicle . . . 2-83

Figure 2-31. Minimum Turning Path for Passenger Car and Boat Trailer (P/B) Design Vehicle 2-84

Figure 2-32. Minimum Turning Path for Motor Home and Boat Trailer (MH/B) Design Vehicle 2-85

Figure 2-33. Acceleration of Passenger Cars, Level Conditions 2-87

Figure 2-34. Deceleration Distances for Passenger Vehicles Approaching Intersections. 2-88

CHAPTER 3 ELEMENTS OF DESIGN

Figure 3-1. Illustration of the Method for Measuring Sight Distance. 3-18

Figure 3-2. Geometry for Ball-Bank Indicator 3-23

Figure 3-3. Side Friction Factors for Streets and Highways. 3-25

Figure 3-4. Side Friction Factors Assumed for Design 3-27

Figure 3-5. Methods of Distributing Superelevation and Side Friction. 3-28

Figure 3-6. Method 5 Procedure for Development of the Superelevation Distribution 3-37

Figure 3-7. Superelevation, Radius, and Design Speed for Low-Speed Street Design in Urban Areas 3-58

Figure 3-8. Diagrammatic Profiles Showing Methods of Attaining Superelevation for a Curve to the Right 3-82

Figure 3-9. Track Width for Widening of Traveled Way on Curves	3-94
Figure 3-10. Front Overhang for Widening of Traveled Way on Curves	3-95
Figure 3-11. Widening Components on Open Highway Curves (Two-Lane Highways, One-Way or Two-Way)	3-97
Figure 3-12. Derivation of Turning Roadway Widths on Curves at Intersections	3-104
Figure 3-13. Diagram Illustrating Components for Determining Horizontal Sight Distance.	3-115
Figure 3-14. Horizontal Sightline Offset (HSO) to Provide Stopping Sight Distance on Horizontal Curves	3-116
Figure 3-15. Speed–Distance Curves for a Typical Heavy Truck of 140 lb/hp [85 kg/kW] for Deceleration on Upgrades	3-124
Figure 3-16. Speed–Distance Curves for Acceleration of a Typical Heavy Truck of 140 lb/hp [85 kg/kW] on Upgrades and Downgrades	3-125
Figure 3-17. Speed–Distance Curves for a Typical Heavy Truck of 200 lb/hp [120 kg/kW] for Deceleration on Upgrades	3-127
Figure 3-18. Speed–Distance Curves for Acceleration of a Typical Heavy Truck of 200 lb/hp [120 kg/kW] on Upgrades and Downgrades.	3-128
Figure 3-19. Speed–Distance Curves for a Typical Recreational Vehicle on the Selected Upgrades (75)	3-129
Figure 3-20. Crash Involvement Rate of Trucks for Which Running Speeds Are Reduced below Average Running Speed of All Traffic (25)	3-132
Figure 3-21. Critical Lengths of Grade for Design, Assumed Typical Heavy Truck of 200 lb/hp [120 kg/kW], Entering Speed = 70 mph [110 km/h]	3-134
Figure 3-22. Critical Lengths of Grade Using an Approach Speed of 55 mph [90 km/h] for Typical Recreational Vehicle (23)	3-135
Figure 3-23. Climbing Lanes on Two-Lane Highways	3-138
Figure 3-24. Climbing Lane on Freeways and Multilane Highways	3-145
Figure 3-25. Passing Lanes Sections on Two-Lane Roads	3-147
Figure 3-26. Schematic for 2+1 Roadway	3-149
Figure 3-27. Schematic for Three-Leg Intersection on a 2+1 Roadway	3-150
Figure 3-28. Schematic for Four-Leg Intersection on a 2+1 Roadway	3-150
Figure 3-29. Schematic for Adjacent Lane Drop Tapers on a 2+1 Roadway	3-151
Figure 3-30. Schematic for Adjacent Lane Addition Tapers on a 2+1 Roadway	3-151
Figure 3-31. Forces Acting on a Vehicle in Motion	3-155
Figure 3-32. Basic Types of Emergency Escape Ramps.	3-158
Figure 3-33. Typical Emergency Escape Ramp	3-163
Figure 3-34. Types of Vertical Curves.	3-165

Figure 3-35. Parameters Considered in Determining the Length of a Crest Vertical Curve to Provide Sight Distance	3-167
Figure 3-36. Design Controls for Crest Vertical Curves—Open Road Conditions	3-169
Figure 3-37. Design Controls for Sag Vertical Curves—Open Road Conditions	3-174
Figure 3-38. Sight Distance at Undercrossings	3-177
Figure 3-39. Vertical Clearance at Undercrossings	3-180
Figure 3-40. Alignment and Profile Relationships in Roadway Design (43).	3-184

CHAPTER 4 CROSS-SECTION ELEMENTS

Figure 4-1. Typical Cross Section, Normal Crown	4-3
Figure 4-2. Typical Cross Section, Superelevated	4-4
Figure 4-3. Roadway Sections for Divided Highway (Basic Cross Slope Arrangements)	4-5
Figure 4-4. Graded and Usable Shoulders.	4-11
Figure 4-5. Typical Highway Curbs.	4-20
Figure 4-6. Designation of Roadside Regions	4-28
Figure 4-7. Typical Frontage Road Arrangements	4-43
Figure 4-8. One-Way Frontage Roads, Entrance and Exit Ramps.	4-44
Figure 4-9. Typical Outer Separations for Various Types of Arterials	4-46
Figure 4-10. Effects of Depressing the Roadway.	4-50
Figure 4-11. Effects of Elevating the Roadway.	4-51
Figure 4-12. Driveway Vertical Alignment and Profile Elements	4-55
Figure 4-13. Typical Two-Lane Tunnel Sections	4-61
Figure 4-14. Diagrammatic Tunnel Sections.	4-63
Figure 4-15. Entrance to a Freeway Tunnel	4-64
Figure 4-16. Interior of a Two-Lane Directional Tunnel	4-64
Figure 4-17. Typical Pedestrian Overpasses on Major Highways.	4-69
Figure 4-18. Curb Ramp Details	4-72
Figure 4-19. Median Refuge	4-74
Figure 4-20. Examples of Sidewalk Curb Ramps	4-75
Figure 4-21. Midblock Bus Turnout	4-80
Figure 4-22. Sawtooth Bus Loading Area.	4-82
Figure 4-23. Typical Application of Diagonal Back-In/Head-Out Parking.	4-84
Figure 4-24. Parking Lane Transition at Intersection	4-86

CHAPTER 5 LOCAL ROADS AND STREETS

Figure 5-1. Types of Cul-de-Sacs and Dead-End Streets.	5-20
Figure 5-2. Alley Turnarounds.	5-22
Figure 5-3. Actual Curb Radius and Effective Radius for Right-Turn Movements at Intersections . . .	5-24
Figure 5-4. Potential Road Network.	5-28
Figure 5-5. Turnout Design.	5-35

CHAPTER 6 COLLECTOR ROADS AND STREETS

Chapter 6 has no figures.

CHAPTER 7 RURAL AND URBAN ARTERIALS

Figure 7-1. Climbing Lane on Two-Lane Arterial in a Rural Area	7-10
Figure 7-2. Two-Lane Arterial Cross Section with Ultimate Development to a Four-Lane Arterial. . . .	7-14
Figure 7-3. Methods of Attaining Superelevation on Divided Arterials in Rural Areas.	7-23
Figure 7-4. Typical Medians on Divided Arterials in Rural Areas.	7-24
Figure 7-5. Cross Sectional Arrangements on Divided Arterials in Rural Areas	7-26
Figure 7-6. Cross Sectional Arrangements on Divided Arterials with Frontage Roads	7-27
Figure 7-7. Transition Zone Areas (37).	7-33
Figure 7-8. Continuous Two-Way Left-Turn Lane	7-43
Figure 7-9. Arterial Street in a Residential Area	7-47
Figure 7-10. Divided Arterial Street with Parking Lane	7-48
Figure 7-11. Divided Arterial Street with Two-Way Frontage Road	7-63
Figure 7-12. Reserved Bus Lane	7-68

CHAPTER 8 FREEWAYS

Figure 8-1. Typical Ground-Level Freeway in a Rural Area	8-8
Figure 8-2. Typical Rural Medians	8-10
Figure 8-3. Typical Cross Section for Depressed Freeways.	8-15
Figure 8-4. Restricted Cross Sections for Depressed Freeways	8-16
Figure 8-5. Cross Sections with Retaining Walls on Depressed Freeways without Ramps.	8-17
Figure 8-6. Depressed Freeway	8-18
Figure 8-7. Typical Cross Sections for Elevated Freeways on Structures without Ramps	8-22

Figure 8-8. Typical and Restricted Cross Sections for Elevated Freeways on Structures with Frontage Roads 8-23

Figure 8-9. Typical and Restricted Cross Sections for Elevated Freeways on Embankment. 8-24

Figure 8-10. Viaduct Freeway 8-25

Figure 8-11. Two-Level Viaduct Freeway 8-25

Figure 8-12. Typical Cross Sections for Ground-Level Freeways 8-27

Figure 8-13. Restricted Cross Sections for Ground-Level Freeways 8-27

Figure 8-14. Profile Control—Combination-Type Freeway in Rolling Terrain 8-29

Figure 8-15. Profile Control—Combination-Type Freeway in Level Terrain. 8-30

Figure 8-16. Cross-Section Control—Combination-Type Freeway 8-31

Figure 8-17. Combination-Type Freeway 8-32

Figure 8-18. Typical Cross Sections for Reverse-Flow Operation 8-33

Figure 8-19. Typical Reverse Roadway Terminals 8-35

Figure 8-20. Reverse-Flow Freeway 8-36

Figure 8-21. Dual-Divided Freeway 8-38

Figure 8-22. Typical Dual-Divided Freeway 8-38

Figure 8-23. Bus Roadway Located between a Freeway and a Parallel Frontage Road 8-41

Figure 8-24. Bus Stops at Freeway Level 8-43

Figure 8-25. Bus Stops at Freeway-Level Diamond Interchange 8-44

Figure 8-26. Bus Stops at Street Level on Diamond Interchange 8-46

Figure 8-27. Joint Freeway–Transit Right-of-Way 8-48

Figure 8-28. Typical Sections with Rail Transit in Freeway Median 8-49

Figure 8-29. Example of Transit Station Layout 8-50

Figure 8-30. Freeway with Rail Rapid Transit in the Median 8-51

CHAPTER 9 INTERSECTIONS

Figure 9-1. Conflict Points at Various Intersection Types 9-3

Figure 9-2. Physical and Functional Area of an Intersection 9-3

Figure 9-3. Elements of the Functional Area of an Intersection 9-4

Figure 9-4. General Types of Intersections 9-12

Figure 9-5. Three-Leg Intersections 9-14

Figure 9-6. Channelized Three-Leg Intersections 9-16

Figure 9-7. Unchannelized Four-Leg Intersections, Plain and Flared. 9-18

Figure 9-8. Channelized Four-Leg Intersections 9-20

Figure 9-9. Four-Leg Intersections with Skew 9-21

Figure 9-10. Channelized Multilane Four-Leg Intersections 9-23

Figure 9-11. Realigning Multileg Intersections 9-25

Figure 9-12. Typical Mini-Roundabout 9-29

Figure 9-13. Typical Single-Lane Roundabout 9-30

Figure 9-14. Typical Multilane Roundabout 9-31

Figure 9-15. Realignment Variations at Intersections 9-32

Figure 9-16. Approach Sight Triangles at Intersections 9-37

Figure 9-17. Departure Sight Triangles for Intersections 9-38

Figure 9-18. Sight Triangles at Skewed Intersections 9-59

Figure 9-19. Channelized Right-Turn Lanes 9-63

Figure 9-20. Effective Corner Radius 9-64

Figure 9-21. Variations in Length of Crosswalk with Different Curb Radii (*10*) 9-66

Figure 9-22. General Types and Shapes of Islands and Medians 9-71

Figure 9-23. Alignment for Addition of Divisional Islands at Intersections 9-73

Figure 9-24. Details of Corner Island Designs for Turning Roadways (Urban Area Location) 9-78

Figure 9-25. Details of Corner Island Designs for Turning Roadways (Rural Cross Section on Approach) 9-79

Figure 9-26. Nose Ramping at Approach End of Median or Corner Island 9-80

Figure 9-27. Details of Divisional Island Design 9-81

Figure 9-28. Development of Superelevation at Turning Roadway Terminals on a Tangent Roadway 9-85

Figure 9-29. Development of Superelevation at Turning Roadway Terminals on a Curved Roadway (Same Direction of Curve). 9-86

Figure 9-30. Development of Superelevation at Turning Roadway Terminals on a Curved Roadway (Opposite Direction of Curve) 9-87

Figure 9-31. Development of Superelevation at Turning Roadway Terminals on a Tangent Roadway with a Deceleration Lane 9-88

Figure 9-32. Functional Area Upstream of an Intersection Illustrating Components of Deceleration Lane Length 9-95

Figure 9-33. Key Dimensions for Maneuvers and Physical Boundaries at Left-Turn Auxiliary Lanes. 9-101

Figure 9-34a. Examples of Taper Design for Left- and Right-Turn Auxiliary Lanes (U.S. Customary) 9-103

Figure 9-34b. Examples of Taper Design for Left- and Right-Turn Auxiliary Lanes (Metric) 9-104

Figure 9-35. Suggested Left-Turn Lane Warrants Based on Results from Benefit–Cost Evaluations for Intersections on Arterials in Urban Areas (16) 9-106

Figure 9-36. Suggested Left-Turn Treatment Warrants Based on Results from Benefit–Cost Evaluations for Intersections on Two-Lane Highways in Rural Areas (16) 9-107

Figure 9-37. Suggested Left-Turn Lane Warrants Based on Results from Benefit–Cost Evaluations for Intersections on Four-Lane Highways in Rural Areas (16). 9-108

Figure 9-38. 14- to 18-ft [4.2- to 5.4-m] Median Width Left-Turn Design 9-111

Figure 9-39. Median Left-Turn Design for Median Width of 16 ft [4.8 m] or More 9-112

Figure 9-40. Examples of Left-Turn Lanes with Negative, Zero, and Positive Offset (10) 9-114

Figure 9-41. Parallel and Tapered Offset Left-Turn Lane 9-115

Figure 9-42. Four-Leg Intersection Providing Simultaneous Left Turns 9-116

Figure 9-43. Above-Minimum Design of Median Openings (Typical Bullet-Nose Ends) 9-123

Figure 9-44. Intersection with Jughandle Roadways for Indirect Left Turns Showing Vehicular Conflict Points. 9-126

Figure 9-45. Vehicular Movements at an Intersection with Jughandle Roadways 9-127

Figure 9-46. Intersection with Loop Roadways for Indirect Left Turns 9-128

Figure 9-47. Diagram of a Displaced Left-Turn Intersection Showing Vehicular Conflict Points. 9-129

Figure 9-48. Vehicular Movements at a Displaced Left-Turn Intersection. 9-129

Figure 9-49. Typical Arrangement of U-Turn Roadways for Indirect Left Turns on Arterials with Wide Medians 9-131

Figure 9-50. Vehicular Movements at an Intersection with U-Turn Roadways for Indirect Left Turns. 9-132

Figure 9-51. Typical Restricted Crossing U-Turn (RCUT) Intersection 9-132

Figure 9-52. Illustration of Pedestrian Path through a Restricted Crossing U-Turn (RCUT) Intersection (12). 9-133

Figure 9-53. Conflict Diagram for Median U-Turn Configuration Showing Vehicular Conflict Points. 9-135

Figure 9-54. Conflict Diagram for Restricted Crossing U-Turn Configuration Showing Vehicle Conflict Points. 9-135

Figure 9-55. Bidirectional (Conventional) and Directional Median Openings. 9-137

Figure 9-56. Typical Loon Design to Facilitate U-Turning Traffic on Arterials with Restricted Median Widths (27). 9-138

Figure 9-57. Dual U-Turn Directional Crossover Design (27) 9-139

Figure 9-58. Special Indirect U-Turn Roadways with Narrow Medians 9-141

Figure 9-59. Example of a Roundabout in an Urban Area 9-142

Figure 9-60. Example of a Roundabout in a Rural Area. 9-142

Figure 9-61. Basic Geometric Elements of a Roundabout 9-144

Figure 9-62. Roundabout Lane Configuration Example9-148

Figure 9-63. Path Overlap at a Multilane Roundabout9-149

Figure 9-64. Intersections with Frontage Roads9-154

Figure 9-65. Arterial with Flush or Traversable Median Turn Lanes9-159

Figure 9-66. Railroad–Highway Grade Crossing9-160

Figure 9-67. Case A: Moving Vehicle to Cross or Stop at Railroad Crossing.9-164

Figure 9-68. Case B: Departure of Vehicle from Stopped Position to Cross Single Railroad Track . .9-166

CHAPTER 10 GRADE SEPARATIONS AND INTERCHANGES

Figure 10-1. Interchange Configurations 10-3

Figure 10-2. Factors Influencing Length of Access Control along an Interchange Crossroad 10-10

Figure 10-3. Typical Grade Separation Structures with Closed Abutments10-17

Figure 10-4. Typical Grade Separation Structure with Open-End Span10-18

Figure 10-5. Multilevel Grade Separation Structures.10-19

Figure 10-6. Lateral Offset for Major Roadway Underpasses 10-23

Figure 10-7. Typical Overpass Structures 10-26

Figure 10-8. Flat Terrain, Distance Needed to Achieve Grade Separation. 10-29

Figure 10-9. Three-Leg Interchanges with Single Structures. 10-33

Figure 10-10. Three-Leg Interchanges with Multiple Structures 10-35

Figure 10-11. Three-Leg Interchange (T-Type or Trumpet) 10-36

Figure 10-12. Three-Leg Interchange Directional Design 10-37

Figure 10-13. Directional Three-Leg Interchange at a River Crossing. 10-38

Figure 10-14. Trumpet Freeway-to-Freeway Interchange 10-38

Figure 10-15. Four-Leg Interchanges, Ramps in One Quadrant 10-40

Figure 10-16. Typical Four-Leg Diamond Interchange. 10-41

Figure 10-17. Diamond Interchanges, Conventional Arrangements 10-43

Figure 10-18. Diamond Interchange Arrangements to Reduce Traffic Conflicts. 10-44

Figure 10-19. Diamond Interchanges with Additional Structures 10-45

Figure 10-20. Freeway with a Three-Level Diamond Interchange. 10-46

Figure 10-21. X-Pattern Ramp Arrangement 10-47

Figure 10-22. Diamond Interchange with Roundabouts at the Crossroad Ramp Terminals. 10-47

Figure 10-23. Underpass Single-Point Diamond Interchange 10-49

Figure 10-24. Typical SPDI Underpass Configuration in Restricted Right-of-Way. 10-49

Figure 10-25. Overpass Layout for an SPDI with a Frontage Road and a Separate U-Turn Movement 10-51

Figure 10-26. Underpass SPDI and Overpass SPDI 10-52

Figure 10-27. Underpass and Overpass Diverging Diamond Interchanges 10-54

Figure 10-28. Partial Cloverleaf Interchange 10-59

Figure 10-29. Four-Leg Interchange, Cloverleaf with Collector–Distributor Roads 10-59

Figure 10-30. Schematic of Partial Cloverleaf Ramp Arrangements, Exit and Entrance Turns 10-61

Figure 10-31. Four-Leg Interchange (Partial or Two-Quadrant Cloverleaf with Ramps before Main Structure) 10-62

Figure 10-32. Four-Leg Interchange (Partial or Two-Quadrant Cloverleaf with Ramps before Main Structure) 10-63

Figure 10-33. Directional Interchanges with Weaving Areas 10-65

Figure 10-34. Directional Interchanges with No Weaving 10-66

Figure 10-35. Directional Interchanges with Multilevel Structures 10-68

Figure 10-36. Directional Interchange, Two Semidirect Connections 10-69

Figure 10-37. Four-Level Directional Interchange 10-70

Figure 10-38. Four-Level Directional Interchange 10-70

Figure 10-39. Directional Interchange with Semidirect Connection and Loops 10-71

Figure 10-40. Offset Interchange via Ramp Highway 10-72

Figure 10-41. Four-Leg Interchange, Diamond with a Direct Connection 10-73

Figure 10-42. Four-Leg Interchange, Cloverleaf with a Semidirect Connection 10-74

Figure 10-43. Cloverleaf Interchange with Semidirect Connection 10-75

Figure 10-44. Complex Interchange Arrangement 10-76

Figure 10-45. Adaptability of Interchanges on Freeways as Related to Types of Intersecting Facilities 10-79

Figure 10-46. Widening for Divisional Island at Interchanges 10-81

Figure 10-47. Interchange Spacing as Measured between Successive Crossroads (18) 10-82

Figure 10-48. Arrangement of Exits between Successive Interchanges 10-83

Figure 10-49. Interchange Forms to Maintain Route Continuity 10-84

Figure 10-50. Collector–Distributor Road on Major–Minor Roadway Overlap 10-85

Figure 10-51. Schematic of Basic Number of Lanes 10-87

Figure 10-52. Typical Examples of Lane Balance 10-88

Figure 10-53. Coordination of Lane Balance and Basic Number of Lanes 10-89

Figure 10-54. Alternative Methods of Reducing or Dropping Auxiliary Lanes 10-91

Figure 10-55. Coordination of Lane Balance and Basic Number of Lanes through Application of Auxiliary Lanes	10-92
Figure 10-56. Auxiliary Lane Dropped at Two-Lane Exit	10-93
Figure 10-57. Interchange Forms with One and Two Exits	10-98
Figure 10-58. Two-Lane Crossroad Designs to Discourage Wrong-Way Entry	10-100
Figure 10-59. Divided Crossroad Designs to Discourage Wrong-Way Entry	10-101
Figure 10-60. General Types of Ramps	10-104
Figure 10-61. Ramp Shapes	10-108
Figure 10-62. Development of Superelevation at Free-Flow Ramp Terminals	10-113
Figure 10-63. Typical Exit Gore Area Characteristics	10-114
Figure 10-64. Typical Gore Details	10-117
Figure 10-65. Traveled-Way Narrowing on Entrance Ramps	10-118
Figure 10-66. Gore Area, Single-Lane Exit	10-119
Figure 10-67. Gore Area, Major Fork	10-119
Figure 10-68. Gore Area, Two-Lane Exit	10-120
Figure 10-69. Entrance Terminal	10-120
Figure 10-70. Recommended Minimum Ramp Terminal Spacing	10-127
Figure 10-71. Ramp Spacing Dimension	10-127
Figure 10-72. Typical Single-Lane Entrance Ramps	10-129
Figure 10-73. Exit Ramps—Single Lane	10-137
Figure 10-74a. Layout of Taper-Type Terminals on Curves (U.S. Customary)	10-140
Figure 10-74b. Layout of Taper-Type Terminals on Curves (Metric).	10-141
Figure 10-75. Parallel-Type Ramp Terminals on Curves.	10-142
Figure 10-76. Typical Two-Lane Entrance Ramps	10-145
Figure 10-77. Two-Lane Exit Terminals	10-146
Figure 10-78. Major Forks.	10-148
Figure 10-79. Branch Connections.	10-149
Figure 10-80. Diagram of Freeway Configuration with Closely Spaced Ramps but Limited Weaving	10-151

LIST OF TABLES

CHAPTER 2 DESIGN CONTROLS AND CRITERIA

Table 2-1. Corresponding Design Speeds in Metric and U.S. Customary Units	2-25
Table 2-2. General Definitions of Levels of Service	2-36
Table 2-3. Guidelines for Selection of Design Levels of Service	2-37
Table 2-4a. Design Vehicle Dimensions (U.S. Customary Units)	2-56
Table 2-4b. Design Vehicle Dimensions (Metric Units).	2-57
Table 2-5a. Minimum Turning Radii of Design Vehicles (U.S. Customary Units)	2-59
Table 2-5b. Minimum Turning Radii of Design Vehicles (Metric Units)	2-60

CHAPTER 3 ELEMENTS OF DESIGN

Table 3-1. Stopping Sight Distance on Level Roadways	3-4
Table 3-2. Stopping Sight Distance on Grades	3-6
Table 3-3. Decision Sight Distance.	3-8
Table 3-4. Passing Sight Distance for Design of Two-Lane Highways.	3-11
Table 3-5. Minimum Passing Zone Lengths to Be Included in Traffic Operational Analyses	3-14
Table 3-6. Average Running Speeds	3-30
Table 3-7. Minimum Radius Using Limiting Values of e and f	3-34
Table 3-8. Minimum Radii for Design Superelevation Rates, Design Speeds, and $e_{\max} = 4\%$	3-42
Table 3-9. Minimum Radii for Design Superelevation Rates, Design Speeds, and $e_{\max} = 6\%$	3-43
Table 3-10. Minimum Radii for Design Superelevation Rates, Design Speeds, and $e_{\max} = 8\%$	3-45
Table 3-11. Minimum Radii for Design Superelevation Rates, Design Speeds, and $e_{\max} = 10\%$	3-47
Table 3-12. Minimum Radii for Design Superelevation Rates, Design Speeds, and $e_{\max} = 12\%$	3-49
Table 3-13. Minimum Radii and Superelevation for Low-Speed Streets in Urban Areas.	3-54
Table 3-14. Lengths of Circular Arcs for Different Compound Curve Radii.	3-61
Table 3-15. Adjustment Factor for Number of Lanes Rotated	3-64
Table 3-16a. Superelevation Runoff L_r (ft) for Horizontal Curves.	-66
Table 3-16b. Superelevation Runoff L_r (m) for Horizontal Curves.	3-68
Table 3-17. Limiting Superelevation Rates	3-73
Table 3-18. Maximum Radius for Use of a Spiral Curve Transition.	3-75
Table 3-19. Desirable Length of Spiral Curve Transition	3-78
Table 3-20. Superelevation Rates Associated with Large Relative Gradients.	3-79

Table 3-21. Tangent Runout Length for Spiral Curve Transition Design 3-80

Table 3-22. Minimum Lengths of Spiral for Intersection Curves 3-89

Table 3-23. Length of Circular Arc for a Compound Intersection Curve When Followed by a Curve of One-Half Radius or Preceded by a Curve of Double Radius 3-91

Table 3-24a. Calculated and Design Values For Traveled Way Widening on Open Highway Curves (Two-Lane Highways, One-Way Or Two-Way) (U.S. Customary) 3-99

Table 3-24b. Calculated and Design Values for Traveled Way Widening on Open Highway Curves (Two-Lane Highways, One-Way or Two-Way) (Metric) 3-100

Table 3-25. Adjustments for Traveled Way Widening Values on Open Highway Curves (Two-Lane Highways, One-Way or Two-Way). 3-102

Table 3-26a. Derived Pavement Widths for Turning Roadways for Different Design Vehicles (U.S. Customary) 3-106

Table 3-26b. Derived Pavement Widths for Turning Roadways for Different Design Vehicles (Metric) 3-107

Table 3-27. Design Widths of Pavements for Turning Roadways 3-109

Table 3-28. Design Width Modifications for Edge Conditions of the Traveled Way for Turning Roadways 3-110

Table 3-29. Cases and Traffic Conditions by Design 3-111

Table 3-30. Cases and Traffic Conditions for Larger Vehicles 3-111

Table 3-31. Range of Usable Shoulder Widths or Equivalent Lateral Clearances outside of Turning Roadways, Not on Structure 3-113

Table 3-32. Optimal Passing Lane Lengths for Traffic Operational Efficiency (30, 31) 3-149

Table 3-33. Recommended Lengths of Turnouts Including Taper. 3-153

Table 3-34. Rolling Resistance of Roadway Surfacing Materials 3-156

Table 3-35. Design Controls for Crest Vertical Curves Based on Stopping Sight Distance 3-170

Table 3-36. Design Controls for Crest Vertical Curves Based on Passing Sight Distance 3-172

Table 3-37. Design Controls for Sag Vertical Curves 3-176

CHAPTER 4 CROSS-SECTION ELEMENTS

Table 4-1. Normal Traveled-Way Cross Slope 4-7

Table 4-2. Design Guidelines and Countermeasures to Reduce Median-Related Crashes on High-Speed Roadways (36) 4-42

Table 4-3. Noise-Abatement Criteria for Various Land Uses (27) 4-48

Table 4-4. Driveway Width Guidelines (31) 4-54

CHAPTER 5 LOCAL ROADS AND STREETS

Table 5-1. Minimum Design Speeds for Local Roads in Rural Areas	5-3
Table 5-2. Maximum Grades for Local Roads in Rural Areas	5-4
Table 5-3. Design Controls for Stopping Sight Distance and for Crest and Sag Vertical Curves	5-5
Table 5-4. Design Controls for Crest Vertical Curves Based on Passing Sight Distance	5-5
Table 5-5. Minimum Width of Traveled Way and Shoulders for Two-Lane Local Roads in Rural Areas	5-7
Table 5-6. Minimum Clear Roadway Widths and Design Loadings for New and Reconstructed Bridges	5-9
Table 5-7. Maximum Grades for Recreational Roads	5-30
Table 5-8. Design Controls for Stopping Sight Distance and for Crest and Sag Vertical Curves— Recreational Roads	5-31
Table 5-9. Guidelines for Minimum Radius of Curvature for New Construction of Unpaved Surfaces with No Superelevation [adapted from (20)]	5-32
Table 5-10. Design Controls for Passing Sight Distance for Crest Vertical Curves—Recreational Roads	5-33
Table 5-11. Widths of Traveled Way and Shoulders—Recreational Roads	5-34
Table 5-12. Design Speeds for Resource Recovery and Local Service Roads	5-38

CHAPTER 6 COLLECTOR ROADS AND STREETS

Table 6-1. Minimum Design Speeds for Collectors in the Rural Context	6-3
Table 6-2. Maximum Grades for Collectors in Rural Areas	6-4
Table 6-3. Design Controls for Stopping Sight Distance and for Crest and Sag Vertical Curves	6-5
Table 6-4. Design Controls for Crest Vertical Curves Based on Passing Sight Distance	6-5
Table 6-5. Minimum Width of Traveled Way and Shoulders	6-6
Table 6-6. Minimum Roadway Widths and Design Loadings for New and Reconstructed Bridges	6-8
Table 6-7. Maximum Grades for Collectors in the Urban and Urban Core Contexts	6-15

CHAPTER 7 RURAL AND URBAN ARTERIALS

Table 7-1. Minimum Sight Distances for Arterials in Rural Areas	7-5
Table 7-2. Maximum Grades for Arterials in Rural Areas	7-6
Table 7-3. Minimum Width of Traveled Way and Usable Shoulder for Arterials in Rural Areas	7-7
Table 7-4a. Maximum Grades for Urban Arterials, U.S. Customary	7-38
Table 7-4b. Maximum Grades for Urban Arterials, Metric	7-38

CHAPTER 8 FREEWAYS

Table 8-1. Maximum Grades for Freeways in Rural and Urban Areas	8-5
---	-----

CHAPTER 9 INTERSECTIONS

Table 9-1. Key Dimensions of Specific Types of Nonmotorized Users.	9-8
Table 9-2. Motor Vehicle Level of Service Definitions for Signalized Intersections (49)	9-10
Table 9-3. Comparison of Roundabout Types (41)	9-28
Table 9-4. Length of Sight Triangle Leg—Case A, No Traffic Control	9-41
Table 9-5. Adjustment Factors for Intersection Sight Distance Based on Approach Grade	9-42
Table 9-6. Time Gap for Case B1, Left Turn from Stop	9-44
Table 9-7. Design Intersection Sight Distance—Case B1, Left Turn from Stop	9-46
Table 9-8. Time Gap for Case B2—Right Turn from Stop	9-47
Table 9-9. Design Intersection Sight Distance—Case B2, Right Turn from Stop	9-48
Table 9-10. Time Gap for Case B3, Crossing Maneuver from the Minor Road	9-49
Table 9-11. Design Intersection Sight Distance—Case B3, Crossing Maneuver	9-50
Table 9-12. Case C1—Crossing Maneuvers from Yield-Controlled Approaches, Length of Minor Road Leg and Travel Times	9-52
Table 9-13. Length of Sight Triangle Leg along Major Road—Case C1, Crossing Maneuver at Yield-Controlled Intersections	9-54
Table 9-14. Time Gap for Case C2, Left or Right Turn at Yield-Controlled Intersections	9-55
Table 9-15. Design Intersection Sight Distance—Case C2, Left or Right Turn at Yield-55 Controlled Intersections	9-55
Table 9-16. Time Gap for Case F, Left Turns from the Major Road	9-57
Table 9-17. Intersection Sight Distance—Case F, Left Turn from the Major Road	9-57
Table 9-18. Maximum Algebraic Difference in Cross Slope at Turning Roadway Terminals	9-89
Table 9-19. Stopping Sight Distance for Turning Roadways	9-91
Table 9-20. Desirable Lane Change and Deceleration Distances	9-96
Table 9-21. Calculated Storage Lengths to Accommodate the 50th Percentile Critical Gap (16)	9-98
Table 9-22. Calculated Storage Lengths to Accommodate the 85th Percentile Critical Gap (16)	9-99
Table 9-23. Queue Storage Length Adjustments for Trucks (48)	9-99
Table 9-24. Suggested Left-Turn Lane Guidelines Based on Results from Benefit–Cost Evaluations for Unsignalized Intersections on Arterials in Urban Areas (16)	9-106
Table 9-25. Suggested Left-Turn Treatment Guidelines Based on Results from Benefit–Cost Evaluations for Intersections on Two-Lane Highways in Rural Areas (16)	9-107

Table 9-26. Suggested Left-Turn Lane Guidelines Based on Results from Benefit–Cost Evaluations for Unsignalized Intersections on Four-Lane Highways in Rural Areas (16)	9-108
Table 9-27. Swept Path Widths for 90-Degree Left Turns (23)	9-117
Table 9-28. Minimum Designs for U-Turns	9-140
Table 9-29. Design Sight Distance for Combination of Motor Vehicle and Train Speeds; 73.5-ft [22.4-m] Truck Crossing a Single Set of Tracks at 90 Degrees	9-167

CHAPTER 10 GRADE SEPARATIONS AND INTERCHANGES

Table 10-1. Guide Values for Ramp Design Speed as Related to Highway Design Speed	10-105
Table 10-2. Guidelines for Maximum Ramp Grade	10-110
Table 10-3. Minimum Length of Taper beyond an Offset Nose	10-118
Table 10-4. Minimum Acceleration Lane Lengths for Entrance Terminals with Flat Grades of Less Than 3 Percent	10-132
Table 10-5. Speed Change Lane Adjustment Factors as a Function of Grade	10-133
Table 10-6. Minimum Deceleration Lane Lengths for Exit Terminals with Flat Grades of Less Than 3 Percent	10-138

PREFACE

Public works projects of all scales are more sensitive to funding than ever before. In many cases, cost magnitude and cost effectiveness play increasingly large roles in scoping projects. Often, reconstruction projects are limited in scope or available funding, or may be affected by physical constraints or social or environmental considerations. In some locations, especially constrained locations, designing to the criteria recommended herein simply is not feasible. Adaptive, flexible, and cost-effective designs customized to each project context are encouraged. Flexibility in the application of design criteria herein is recommended to encourage a sustainable approach to highway design decision making by weighing and balancing choices among the environmental, economic, and social aspects while meeting the project's performance objectives.

Designers should recognize the joint use of transportation corridors by motorists, pedestrians, bicyclists, public transit, and freight vehicles. Designers are encouraged to consider not only vehicular movement, but also movement of people, distribution of goods, and provision of essential services. A more comprehensive transportation program is thereby emphasized.

A Policy on Geometric Design of Highways and Streets provides geometric design guidance based on established practices that are supplemented by recent research. This document is intended as a comprehensive reference manual to assist in administrative, planning, and educational efforts pertaining to design formulation. This policy is not intended to be a prescriptive design manual that supersedes engineering judgment by the knowledgeable design professional.

The design concepts and criteria in this policy are intended for use when designing new construction projects on new location or designing reconstruction projects on an existing location. Projects on existing roads particularly call for a flexible, performance-based approach to design. The policy also encourages flexible design, which emphasizes the role of the planner and designer in determining appropriate design dimensions based on project-specific conditions and existing and future roadway performance more than on meeting specific nominal design criteria. This publication is not intended as a policy for resurfacing, restoration, or rehabilitation (3R); traffic engineering; safety; and preventive maintenance-type projects that include very minor or no roadway work. When designing 3R projects, the designer should refer to the design guidelines presented in *NCHRP Report 876, Guidelines for Integrating Safety and Cost-Effectiveness into Resurfacing, Restoration, and Rehabilitation (3R) Projects*, for more information. *NCHRP Report 876* was developed as a replacement for *TRB Special Report 214, Designing Safer Roads: Practices for Resurfacing, Restoration, and Rehabilitation*.

The fact that new design values and concepts are presented herein does not imply that existing streets and highways are unsafe, nor does it mandate the initiation of improvement projects. The highway, vehicle, and individual users are all integral parts of transportation safety and efficiency. While this document primarily addresses geometric design issues, a properly equipped and maintained vehicle and reasonable and prudent performance by the user are also needed for safe and efficient operation of the transportation facility.

Chapter 1 of this edition has been rewritten entirely and provides a new framework for geometric design. It expands the land use contexts from two (urban or rural) to five (rural, rural town, suburban, urban, or urban core). It emphasizes design flexibility provided in this policy and encourages designers to take advantage of that flexibility. Chapter 1 also introduces a performance-based approach to geometric design which, when used, will allow practitioners to quantify and convey design tradeoffs in meaningful terms to a broad audience and, ultimately, for consideration by decision makers.

Design values are presented in this document in both U.S. customary and metric units and were developed independently within each system. The relationship between the U.S. customary and metric values is neither an exact (soft) conversion nor a completely rationalized (hard) conversion; and the use of brackets around metric values does not indicate as in some AASHTO publications that these are soft conversions. The U.S. customary values are those that would have been used if the policy had been presented exclusively in U.S. customary units; the metric values are those that would have been used had the policy been presented exclusively in metric units. Therefore, the user is advised to work entirely in one system and not attempt to convert directly between the two.

This publication supersedes the 2011 AASHTO publication of the same name. Because the concepts presented cannot be completely covered in this one document, references to additional literature are given at the end of each chapter. These references include works that were cited or consulted in the development of the chapter or are of interest to the discussion of the subject matter therein. Of these documents, only those balloted and published by AASHTO represent AASHTO policy.

The Committee on Design and the Technical Committee on Geometric Design would like to extend a special thank you to Doug Harwood of MRI Global for his technical editing expertise during the development of the seventh edition.

1 New Framework for Geometric Design

1.1 INTRODUCTION

This seventh edition of the *A Policy on Geometric Design of Highways and Streets* incorporates recent research that provides insight into the effect of specific geometric design elements of roads and streets for all transportation modes. This edition of the policy also introduces the consideration of five specific context classifications as an element of the geometric design process and emphasizes the consideration of multimodal needs in design. Together, context classification and functional classification constitute a new framework for geometric design. The policy also encourages flexible design, which emphasizes the role of the planner and designer in determining appropriate design dimensions based on project-specific conditions and existing and future roadway performance more than on meeting specific nominal design criteria. In the past, designers sought to assure good traffic operational and safety performance for the design of specific projects primarily by meeting the dimensional design criteria in this policy. This approach was appropriate in the past because the relationship between design dimensions and future performance was poorly understood. Traditional applications of this policy took the approach that, if the geometric design of a project met or exceeded specific dimensional design criteria, it would be likely to perform well. In some cases, this may have led to overdesign, constructing projects that were more costly than they needed to be or were inappropriate for the roadway context.

Recent research has improved our knowledge of the relationship between geometric design features and traffic operations for all modes of transportation and has developed new knowledge about the relationship of geometric design features to crash frequency and severity. Much of the recently developed information about assessing traffic operations for all transportation modes is presented in the TRB *Highway Capacity Manual* (25), while the recently developed information about estimating future crash frequencies and severities is presented in the AASHTO *Highway Safety Manual* (4, 7).

This edition of the policy introduces new definitions of project types—new construction, reconstruction, and projects on existing roads—and explains how design flexibility is provided for each project type as part of the project development process.

Project development is broader than just geometric design and should consider many factors for all transportation modes, including:

- Project purpose and need
- Existing and expected future traffic operational efficiency
- Existing and expected future crash frequency and severity
- Construction cost
- Future maintenance cost
- Context classification
- Service and ease of use for each transportation mode:
 - automobile
 - bicycle
 - pedestrian
 - transit
 - truck
- Accessibility for persons with disabilities
- Available right-of-way
- Existing and potential future development
- Operational flexibility during future incidents and maintenance activities
- Stakeholder input
- Community goals and plans and potential community impacts
- Historical structures
- Impacts on the natural environment:
 - air quality
 - noise
 - wetlands preservation
 - wildlife and endangered species
- Preservation of archeological artifacts

These factors are not necessarily presented in priority order and, indeed, the priorities placed on them vary from project to project. None of these factors is uniquely important and geometric design should complement other aspects of project development in seeking the appropriate balance among their potential effects.

A 2016 resolution of the AASHTO Standing Committee on Highways (8) has directed that geometric design policy and practice should become more flexible and performance-based to more fully address the needs of all transportation modes and the challenges to transportation agencies created by funding and right-of-way constraints. This AASHTO resolution is consistent with the direction set by Federal legislation in the *Fixing America's Surface Transportation (FAST) Act (14)*. This seventh edition of the policy takes a first step toward implementing a new framework for geometric design to accomplish this goal. There was already substantial flexibility in the geometric design guidance presented in previous editions of this policy, and this seventh edition expands that flexibility. This chapter explains how the flexible, performance-based approach should be applied and describes how Chapters 2 through 10, together with other available resources, can be used in implementing the new framework and the performance-based approach for all transportation modes. The next edition of this policy will more fully incorporate this approach, with full implementation of the new framework and the flexible, performance-based approach in each chapter.

I Index

2+1 roadways; see *Two-lane highways*

Acceleration

- Distance, 2-86–87
- Effects of grade, 3-12
- Intersections, 9-53, 9-63
- Lateral, 3-19
- Lanes; see *Speed-change lanes*
- Rates, 2-86–87

Acceleration lanes; see *Speed-change lanes*

Accelerometer, 3-24

Access control; see *Control of access and access management*

Access management; see *Control of access and access management*

Accessibility; see *Persons with disabilities*

Accidents; see *Safety*

Aesthetics

- Alignment
 - Combination, horizontal and vertical, 3-121
 - Horizontal, 3-62–63
 - Vertical, 3-164
- Interchanges, 10-12–13
- Landscaping, 3-186–187, 9-143
- Medians, 4-40
- Recreational roads, 5-27–28
- Sideslopes, 4-29–31

Alignment—Combinations of

- Arterials; see *Arterials*
- Collectors, 6-3, 6-14
- Coordination in design, 3-182–186, 4-6, 4-8
- Freeways, 8-7–8
- General design controls, 3-181–182

Horizontal; see *Alignment—Horizontal*

Horizontal and vertical, general considerations of, 3-180–181

Interchanges; see *Interchanges*

Intersections at grade, 9-1–3

Local roads and streets; see *Local roads and streets*

Sight distance, 9-35

Vertical; see *Alignment—Vertical*

Alignment—Horizontal

Aesthetics; see *Aesthetics*

Arterials, 7-11

Changes in, 6-3, 7-19

Collectors; see *Collector roads and streets*

Combination with vertical alignment, 4-6

Controls, 3-119–121

Curves; see *Curves—Horizontal*

Design considerations, 3-31–36, 4-6

Design speed, 3-19–20

Divided highways, 3-87

Effect of grade on, 3-35–36

Freeways, 8-7–8

Friction factor, 3-21–30

General considerations, 3-20

Interchanges; see *Interchanges*

Intersections at grade, 9-1–3

Minimum radius, 3-33–35

Offtracking, 3-91–97

Pavement widening; see *Traveled way*

Ramps; see *Ramps*

Recreational roads, 5-31–32

Residential areas, 3-182

Resource recovery and local service roads; see *Local roads and streets*

- Sharpest curve without superelevation, 3-20
- Safety, 3-22–24, 3-33, 3-60
- Side friction factor, 3-21–30
- Sight distance, 3-113–119; see also *Sight distance*
- Speed-change lanes; see *Speed-change lanes*
- Spiral curves, 3-73–74; see also *Transitions*
- Superelevation, 3-20–21, 3-31–52; see also *Superelevation*
- Theoretical considerations, 3-19–20
- Transitions; see *Transitions*
- Traveled way widening, 3-97–103
- Alignment—Vertical**
 - Arterials, 7-5, 7-11
 - Broken back, 3-121, 3-179–180
 - Collectors; see *Collector roads and streets*
 - Combination with horizontal, 4-6
 - Critical length of grade; see *Grades*
 - Curves; see *Curves—Vertical*
 - Design, 3-141–176
 - Escape ramps; see *Ramps*
 - Freeways, 8-7–8
 - General design controls for, 3-179–180
 - Grades, 3-122–136; see also *Grades*
 - Grade separations, 3-177
 - Interchanges; see *Interchanges*
 - Intersections; see *Intersections*
 - Local roads and streets; see *Local roads and streets*
 - Railroad–highway grade crossings; see *Railroad–highway grade crossings*
 - Ramps; see *Ramps*
 - Recreational roads, 5-30
 - Resource recovery and local service roads; see *Local roads and streets*
 - Safety, 3-137
 - Terrain, 3-121–122
 - Traveled way edge, design of smooth profiles for, 3-85
 - Vertical curves; see *Curves—Vertical*
- Alleys**, 5-20–21
- Americans with Disabilities Act Accessibility Guidelines**, 1-24–25, 4-70; see also *Persons with disabilities*
- Americans with Disabilities Act of 1990 (ADA)**, 1-24–25; see also *Americans with Disabilities Act Accessibility Guidelines*
- Approach nose**
 - Bullet, 9-113, 9-119–123
 - Curbs, 9-76–77
 - Offset, 9-76
 - Superelevation, 9-84–89
 - Taper, 9-113
 - Treatment; see *Markings*
- Arterials**, 7-1–2; see also *Divided highways, Multilane highways*
 - Bikeways, 7-30
 - Bus lanes, 7-68
 - Bus stops, 7-30–31, 7-66–67
 - Bus turnouts, 7-30–31, 7-67–68
 - Borders and sidewalks, 7-25, 7-46–47
 - Clearances, 7-9, 7-51
 - Cross section, 7-6–8, 7-14, 7-23–27
 - Cross slope, 4-7, 7-6, 7-15, 7-38–39
 - Curbs, 7-40
 - Definitions, 7-1
 - Directional lane usage, 7-59–62
 - Divided, 7-11–28; see also *Divided highways*
 - Drainage, 7-45
 - Examples, 7-10, 7-42–43, 7-46–48
 - Frontage roads; see *Frontage roads*
 - Grade separations and interchanges, 7-63–64; see also *Interchanges*
 - Intersections, 7-28–29, 7-56
 - Lane width, 7-15, 7-24–26, 7-39–40
 - Left turns, 7-13, 7-15, 7-18, 7-37, 7-55, 7-57, 9-106
 - Medians, 7-17–18, 7-28, 7-40–45
 - Parking, 4-86, 7-45–46, 7-58
 - Right turns, 7-39–40, 7-53, 7-55, 7-57
 - Rural, 1-12–1-13
 - access management, 7-29–30
 - alignment, 7-5, 7-11, 7-18–19
 - characteristics, 7-2–3
 - clear zones, 7-8
 - cross slope, 7-6, 7-15

- design speed, 7-3
- design traffic volumes, 7-3–4
- divided, 7-11–28
- erosion control, 7-9
- grades, 7-5–6
- lateral offset, 7-8
- level of service, 7-4
- lighting, 7-31–32
- number of lanes, 7-7
- passing, 7-9–11
- railroad–highway grade crossings, 7-31
- rest areas, 7-32
- right-of-way, 7-7–8
- roadside design, 7-8
- roadway width, 7-6–7
- sight distance, 7-4–5
- structures, 7-9
- superelevation, 7-6, 7-20–24
- traffic control devices, 7-9
- Rural town context, 7-34, 7-32–34
- Shoulders, 7-16, 7-30, 7-40
- Signal control, 7-57
- Speed, 2-26–27, 7-3, 7-36; see also *Design speed*
- Traffic control devices, 7-9, 7-57; see also *Traffic control devices*
- Transit facilities, 7-65–68
- Ultimate development of four-lane, 7-11–14
- Undivided, 7-13–14
- Urban, 7-34–35
 - access management, 7-51–54
 - alignment, 7-37
 - bicycle facilities, 7-54
 - clear zones, 7-49
 - cross slope, 7-38–39
 - design speed, 7-36
 - design traffic volumes, 7-36
 - driveways, 7-53
 - erosion control, 7-64
 - general, 7-35–36
 - grades, 7-37–38
 - lane width, 7-39–40
 - lateral offset, 7-49–50
 - level of service, 7-37
 - lighting, 7-64–65
 - number of lanes, 7-40
 - pedestrians, 7-54–56
 - railroad–highway grade crossings, 7-51
 - right-of-way width, 7-48–49
 - roadside design, 7-49
 - roadway width, 7-39
 - sight distance, 7-37
 - structures, 7-50–51
 - superelevation, 7-38
 - traffic barriers, 7-51
- Utilities, 7-56
- Arterial systems**
 - Characteristics, 1-12–15, 7-2–3
 - Minor, 1-11–12, 7-35
 - Principal, Rural, 1-12
 - Urban, 1-14–15
- At-grade intersections**; see *Intersections*
- Auxiliary lanes**
 - At interchanges, 4-3–4, 10-90–93
 - At intersections, 4-3–4
 - Bus turnouts, 4-80–81, 7-68
 - Bypass lanes, 9-17–18, 9-105–109, 9-147
 - Climbing lanes; see *Climbing lanes*
 - Cross slope, 4-7
 - Definition, 10-90
 - Left-turn, 9-105–117
 - Length, 9-94, 10-123, 10-128
 - Median lanes; see *Median lanes*
 - Midblock, 9-158–159
 - Offset left-turn, 9-113–115
 - On overpasses, 10-27
 - Passing lanes; see *Passing lanes*
 - Right-turn, 9-15, 9-60–65
 - Speed-change lanes; see *Speed-change lanes*
 - Storage, 9-96–99
 - Taper, 10-90–94
 - Warrants, 9-93
 - Width, 9-92

Average daily traffic (ADT); see *Traffic*

Ball-bank indicator, 3-23

Barriers; see *Traffic barriers* or *Noise*

Benefit analyses; see *Economic evaluation*

Benefit/cost ratio; see *Economic evaluation*

Bicycle facilities, 4-77, 6-7, 6-19

Bicycle lane considerations, 2-54

Borders

Arterials, 7-25, 7-46–47

Collectors, 4-1, 6-19

Freeways; see *Freeways*

Function, 4-65

Local roads and streets, 5-17

Sidewalks; see *Sidewalks*

Width, 6-19

Braking; see also *Drivers*

Brake reaction time, 3-2–3

Distance, 3-3–6

Effects of grades, 3-5–6; see also *Grades*

Buses; see also *Public transit*

Arterials, 4-80–82, 7-66–68

Classification, 2-19–20

Design vehicles, 2-55–60, 2-63, 2-67–72

Freeways, 4-79–80; see also *Freeways*

Lanes, 7-68

Park-and-ride facilities, 4-82–84

Stops, 7-66–67, 8-42–47

Turnouts, 4-79–82

Capacity, see also *Traffic*

ADT, 2-13–18

Analysis, 2-29–30, 7-36

Applications, 2-29–30

Arterials, 7-3–7, 7-36

Climbing lanes, 3-139–144

Definition, 2-29

Degree of congestion, see *Degree of congestion*

Design, 2-30–33

DHV, 2-13–18

Effect of alignment and profile, 2-34

Entrance terminal; see *Terminals*

Exit terminal; see *Terminals*

Flow rate, 2-37–2-38

Freeways; see *Freeways*

General characteristics, 2-29

Highway factors, 2-33, 2-41

Interchanges; see *Interchanges*

Interrupted flow, 2-31

Intersections, 9-9–10; see also *Intersections*

Lateral offsets, 4-11, 4-18

Level of service, 2-36–2-37; see also *Levels of service*

Parking, 2-37, 4-85–87

Passing lanes, 3-145–149

Passing opportunities, 3-12–13, 3-145–154

PHF (peak-hour factor), 2-35–36

Ramps and ramp terminals, 2-34–35

Reverse-flow operations, 7-60–62

Roadside interference, 4-52

Shoulders, 4-11

Terrain type; see *Topography*

Trucks, 3-142–144

Two-lane highways, 2-18–20

Weaving sections, 2-32, 2-34; see also *Weaving sections*

Width of lanes, 4-9–10

Work zones, 3-195

Channelization

Advantages, 9-67

Definition, 9-12

Design principles, 9-68–69

Examples, 9-16–17, 9-20–23

Islands, 9-70–72

Median lanes; see *Median lanes*

Pavement markings; see *Markings*

Safety, 9-67

Warrants, 9-69

Channels—drainage, 4-23–28; see also *Drainage*

Linings, 4-24–28; see also *Erosion control*

Medians, 4-5–6

Classification, context, 1-16–22

- Rural context, 1-11–13, 1-17, 1-20
- Rural town context, 1-16–17, 1-20
- Suburban context, 1-17, 1-21
- Urban context, 1-11, 1-14–17, 1-21–22
- Urban core context, 1-17, 1-22

Classification, functional, 1-7–16

- Access control and mobility needs, 1-10–11
- As a design type, 1-16
- Concept, 1-5–8
- Movement, 1-8–9
- Systems, 1-11–16
 - rural areas, 1-11–13
 - urban areas, 1-11, 1-14–16

Clear zones, 4-17–18**Clearances**

- At tunnels, 4-62
- At walls, 3-113, 4-60, 8-14
- Structures, 3-113, 5-9, 5-35–36, 6-8, 6-20, 7-9, 7-50–51, 8-5
- Divided highways, on left, 3-184
- Grade separation structures; see *Grade separations*
- Guardrail, 10-24
- Horizontal, 4-49
- Luminaire supports (poles), 3-190
- On arterials; see *Arterials*
- On collectors; see *Collector roads and streets*
- On curves, for sight distance, 3-180
- On local roads and streets; see *Local roads and streets*
- Sign supports, 5-9
- To building line, 8-21
- To bus transit facilities, 7-65–68
- To obstructions, 8-14
- Turning roadways, 3-113
- Underpasses, 3-180, 10-24–25
- Vertical, 1-5
 - on arterials; see *Arterials*
 - on collectors; see *Collector roads and streets*
 - on freeways, 8-5

- on local roads and streets; see *Local roads and streets*
- on recreational roads, 5-30–33
- on resource recovery and local service roads; see *Local roads and streets*

Climbing lanes

- Arrangements, 3-138, 3-145
- Beginning of, 3-140–141
- Critical length of grade, 3-139–140, 3-143
- Cross slope; see *Cross slope*
- Definition, 3-137
- Ending of, 3-141
- Examples, 7-10
- General, 3-137
- On freeways, 3-144–145, 8-4
- On multilane highways, 3-144–145, 7-19–20
- On two-lane highways, 3-137–139, 7-19
- Recreational vehicles; see *Recreational vehicles*
- Shoulders on, 3-141, 7-10
- Signing, 3-141
- Taper, 3-141
- Trucks, 3-139–144, 7-10
- Warrants, 3-140–143
- Width, 3-141

Cloverleaves; see *Interchanges***Collector roads and streets**; see also *Local roads and streets*

- Functional classification, 1-5, 1-16, 6-1
- General design considerations, 6-1–2
- Parking on, 4-86, 6-7, 6-16–17
- Rural areas, 1-13
 - alignment, 6-3
 - bicycle facilities, 6-7
 - clearances, 6-8
 - clear zones, 4-17, 6-8
 - cross slope, 6-4
 - curbs, 6-7
 - design speed, 6-2–3, 6-11–12
 - design traffic volumes, 6-3
 - drainage, 6-11
 - driveways, 4-54

- erosion control and landscaping, 6-11
 - foreslopes, 6-9
 - intersection design, 6-9–10
 - grades, 6-4
 - lane width, 6-6
 - lateral offset, 6-8–9
 - levels of service, 6-3
 - medians, 6-7
 - number of lanes, 6-6
 - railroad–highway grade crossings, 6-10
 - right-of-way width, 6-7
 - sight distance, 6-4–5
 - signs and markings, 6-12
 - shoulder width, 6-6
 - structures, 6-7–8
 - superelevation, 4-33, 6-4
 - traffic control devices, 6-11
 - vertical clearance, 6-8
 - width of roadway, 6-6
- Urban areas, 1-15, 6-12
- alignment, 6-14
 - alleys; see *Alleys*
 - bicycle facilities, 6-19
 - border area, 4-1, 6-19
 - clearances, 6-8–9, 6-20–22
 - clear zones, 4-17, 6-21
 - cross slope, 6-15
 - curb return radius, 9-65
 - curbs, 6-18
 - cul-de-sacs and turnarounds, 5-19–20
 - definition, 6-13
 - design speed, 6-13–6-14
 - design traffic volume, 6-13–14
 - drainage, 6-14, 6-17, 6-24
 - driveways, 4-54, 6-20
 - erosion control, 6-24
 - general, 1-15–16, 6-13
 - grades, 6-14–15
 - intersection design, 6-22
 - landscaping, 6-19, 6-24
 - lane width, 6-16
 - lateral offset, 4-18, 6-21–22
 - levels of service, 2-36–37, 6-14
 - lighting, 6-23–24
 - medians, 6-17
 - number of lanes, 6-16
 - parking lanes, 6-16–17
 - railroad–highway grade crossings, 6-23
 - right-of-way width, 6-18–19
 - sidewalk curb ramps, 4-70–76, 6-20
 - sidewalks, 6-19–20
 - sight distance, 6-5, 6-15, 6-23
 - signs and markings, 6-17, 6-19, 6-22–23
 - structures, 6-20
 - superelevation, 4-33, 6-15
 - traffic control devices, 6-23
 - utilities, 6-19
 - vertical clearance, 6-20
 - width of roadway, 6-16
 - widths for bridges, 6-20
- Rural town context, 6-11–12
- Collector–distributor roads;** see *Interchanges*
- Congestion;** see *Degree of congestion*
- Connections;** see *Ramps*
- Construction areas,** 3-195
- Construction Projects on Existing Roads;** see *Project types*
- Context;** see *Classification, context*
- Contrasting surfaces**
- Auxiliary lanes, 9-153
 - Curb and gutter, 4-22
 - Islands, 9-75–76
 - Median lanes, 9-42, 9-113
 - Ramps; see *Ramps*
 - Shoulders, 4-15–16
 - Turnouts, 4-70
- Control devices;** see *Traffic control devices*
- Control of access and access management**
- Arterials, 7-51–54
 - Benefits, 2-45–49
 - Classifications, 2-44
 - Collectors, 6-13

- Crossroad, interchanges, 10-8-10
- Definition, 2-41, 2-43
- Design considerations, 2-43-44, 7-53-54
- Driveway control, 2-43, 4-52-55
- Freeways; see *Freeways*
- Full, 2-41, 2-43
- General, 2-41-44
- Interchanges, 10-8-10
- Intersections, 9-2, 9-6-7, 9-155
- Methods, 2-42, 2-45
- Partial, 2-41
- Principles, 2-43-44
- Safety effects, 2-91-93
- Signals, 2-93, 3-193-194
- With frontage roads, 4-41-44
- Control radii**; see *Radii*
- Crossover crown line**; see *Crown*
- Cross section**
 - Curbs; see *Curbs*
 - Definition, 4-1
 - Divided highways, 4-13, 7-26
 - with frontage roads, 7-27
 - Drainage from shoulders, 4-13-14
 - Elements, 4-1
 - collectors, 6-6-7, 6-16-20
 - Examples, 4-3-5
 - Freeways; see *Freeways*
 - Medians, 4-5-4-6
 - Shoulders, 4-13-14
 - Superelevated, 4-32-33
 - Two-lane rural arterials, 7-14
 - Typical, 4-3-4
 - Tunnel, 4-61, 4-63
 - Ultimate four-lane, 7-14; see also *Arterials*
- Crashes**; see *Safety*
- Cross slope**
 - Arterials; see *Arterials*
 - Auxiliary lanes, 4-7
 - Change in, 3-61, 3-78; see also *Superelevation, runoff*
 - Climbing lanes, 3-141
 - Collectors; see *Collector roads and streets*
 - Crosswalk, 3-130, 3-180
 - Crossover crown line; see *Crown*
 - Divided highways, 4-5
 - Drainage, 3-87, 4-5, 4-14
 - Freeways; see *Freeways*
 - Intersecting roadways, 4-2
 - Local roads and streets, 3-54; see also *Local roads and streets*
 - Maximum, 4-7
 - Minimum, 4-6-7
 - Normal, 4-3, 4-5
 - Parking lanes, 7-39
 - Ramps; see *Ramps*
 - Rates, 4-6-9
 - Recreational roads, 5-33
 - Resource recovery and local service roads; see *Local roads and streets*
 - Removing, for superelevation, 3-52, 3-70, 3-81, 6-15
 - Rollover, control for, 9-89
 - pavement crown, 4-6, 4-32
 - shoulders, 4-33, 7-6, 8-4
 - Shape, 3-31
 - Shoulder slope break, 4-13-14
 - Sidewalk, 4-66
 - Superelevated, 3-31, 4-4-5, 4-32-33
 - Tunnels; see *Tunnels*
 - Turnouts, bus; see *Turnouts*
- Crosswalks**
 - Roundabouts, 9-150-151
 - Turning roadways and channelization; see *Turning roadways*
- Crown**
 - Crossover crown line, 4-6, 9-89
 - Cross slope, 3-52; see also *Cross slope*
 - Freeways, 8-3
 - General, 4-2-6
 - Pavement, 4-6
- Cul-de-sacs**, 5-19-20
- Curbs**
 - Arterials; see *Arterials*

- Asphaltic concrete, 4-19
- Bituminous, 4-19
- Collectors; see *Collector roads and streets*
- Concrete, 4-19
- Configurations, 4-19–21
- Considerations for pedestrians and bicycles, 4-21–22
- Cross section, 4-20
- Drainage, 4-21–22, 4-23–28
- Driveway access, 4-53
- Freeways, 4-20–21, 4-23; see also *Freeways*
- General, 4-19
- Granite, 4-19
- Gutter, 4-21–23
- Islands; see *Islands*
- Local roads and streets; see *Local roads and streets*
- Medians, 4-21
- Near overpasses, 10-26
- Offset from traveled way, 4-18
- Placement, 4-22–23
- Radii; see *Radii*
- Ramps; see *Ramps*
- Shoulder, with and without, 4-12
- Sloping, 4-19–4-21
- Turning roadways, 9-65–67
- Types, 4-19
- Underpasses, 10-23
- Utilities, 3-192
- Vertical, 4-19–21
- Width, 4-20–21

Curves—Horizontal

- Broken back, 3-121
- Compound, 3-60–61
- Design speed and curvature, 3-70–72
- Design tables, 3-34–35, 3-42–51, 3-54–57
- Low-speed urban, 3-53–59
- Formula; see *Formulas*
- Friction factors, 3-21–30
- Intersection; see *Curves—Intersection*
- Maximum curvature, 3-31, 3-52
- Ramp; see *Ramps*

- Sight distance on, 3-113–119, 4-37
- Spirals; see *Transitions*
- Superelevation, 3-20–21
- Transitions; see *Transitions*
- Traveled way widening on; see *Widening*
- Turning roadways, 3-59–61

Curves—Intersection

- Compound, 3-59
- Control radii for left turns, 9-119–121
- Encroachment; see *Turning*
- Maximum curvature, 3-31, 3-52
- Minimum designs for sharpest turn, 9-28
- Minimum radii, 9-122
- Choice of design, 9-64
- Oblique-angle, 9-65, 9-82
- Passenger vehicles, 9-66
- Ramps; see *Ramps*
- Single-unit trucks and buses, 9-53–55, 9-124
- Speed–curvature relations, 3-96
- Spiral; see *Transitions*

Curves—Vertical

- Asymmetrical, 3-166
- Broken back, 3-179–180
- Crest, 3-166–172
- Design controls for, 3-167–172
 - passing sight distance, 3-15–16, 3-171
 - stopping sight distance, 3-15–16, 3-167–171
- Drainage requirements on, 3-165, 4-24
- General considerations, 3-164–166
- Lengths, 3-166–179
- Parabolic, 3-165–166
- Ramps; see *Ramps*
- Sag, 3-172–176
- Sight distance on, 3-166–180
- Turning roadway, 3-113
- Types, 3-165

Dead-end streets; see *Cul-de-sacs*

Deceleration

- Adjusting speed approaching intersections, 2-88, 9-40
- Turning roadways, 9-62

- Braking, 3-2-4
 - Intersections, 9-62
 - Lanes, 9-62; see also *Speed-change lanes*
 - Length at auxiliary lane, 3-152
 - Rates, 2-86-88
 - Tapers, 9-100-104
 - Trucks, on grades, 3-6-7, 3-122-123
- Decision sight distance**, 3-7-9
- Definition, 3-7
- Degree of congestion**
- Acceptable limits, 2-32-33
 - Alignment, 3-139, 3-143
 - Definition, 2-31
 - Design speed; see *Design speed*
 - Levels of service, 2-36-37
 - Measures, 2-31
 - Peak-hour factor, 2-35-36
 - Ramps and ramp terminals, 2-35
 - Relation to traffic flow, 2-31-32
 - Weaving, 2-34, 2-38
- Delineators**; see *Markings*
- Design**
- Capacity; see *Capacity*
 - Controls and criteria, 2-1
 - bicycle facilities, 1-23-24, 2-54-55, 4-77
 - driver performance, 2-1-2-3
 - economic analysis, 1-36
 - environment, 2-95
 - pedestrians, 1-24-25, 2-50-54
 - safety, 2-44-49, 2-91-95
 - traffic characteristics, 2-13-29
 - vehicles; see *Design vehicles*
 - Elements of, 3-1
 - alignment—combinations; see *Alignment—Combinations of*
 - alignment—horizontal; see *Alignment—Horizontal*
 - alignment—vertical; see *Alignment—Vertical*
 - decision sight distance, 3-7-9
 - drainage, 4-32-28
 - erosion control and landscape development, 3-186-187
 - fencing, 4-57
 - grade separations and interchanges, 10-1-3
 - information centers, 3-187
 - intersections, 2-41, 9-10-11
 - low-speed urban streets, 3-53-59
 - maintenance of traffic through construction areas, 3-195
 - noise barriers, 4-48-51
 - passing sight distance, 3-10-14
 - rest areas, 3-187-188
 - scenic overlooks, 3-187
 - sight distance, 3-1-19
 - stopping sight distance, 3-2-7, 3-114-119
 - traffic control devices, 2-93, 3-193-194
 - traveled way widening on curves, 3-91-104
 - turning roadways, 3-59-61
 - utilities, 3-190-192
 - flexibility, 1-32-33
 - performance-based, 1-33-36, 2-86
 - Period, 2-21
 - Speed; see *Design speed*
 - Vehicles; see *Design vehicles*
- Design hourly volume (DHV)**; see *Traffic*
- Design speed**
- Alignment—combinations, 3-181
 - Alignment—horizontal, 2-26
 - Alignment—vertical, 3-167-176
 - Arterials, 2-26-2-27; see also *Arterials*
 - Channelization, 9-67-68
 - Collectors; see *Collector roads and streets*
 - Freeways; see *Freeways*
 - General, 2-11-2-12, 2-23-2-27
 - Local roads and streets; see *Local roads and streets*
 - Intersections, 9-40-42
 - Operating speed, 2-22
 - Ramps; see *Ramps*
 - Recreational roads, 5-28-29
 - Relation to average running speed, 2-24, 3-30
 - average trip length, 2-25

grades, lengths, 10-132
 maximum grades, 3-130
 maximum relative gradients, 3-78-79
 Resource recovery and local service roads, 5-38
 Running speed; see *Speed*
 Sight distance, 3-4-6, 3-8-9, 3-11-14, 9-40-42
 Speed-change lane length; see *Speed-change lanes*
 Speed transitions entering rural towns, 6-11-12
 Superelevation, 2-23, 3-30
 Traffic volumes, 2-23
 Use of spirals, 10-32

Design vehicles

Bus, 2-55, 2-58
 Characteristics, 2-55-58
 Control radii for left turns, 9-119
 Definition, 2-55
 Dimensions, 2-55-57
 For profile design; see *Alignment—Vertical*
 Height; see *Height*
 Intersections, 9-4, 9-63, 9-117
 Median openings, 9-123, 9-138
 Minimum turning radius and paths, 2-58-85;
 see also *Design vehicles—Intersections*
 Overhang, 3-93-95
 Passenger car (P), 2-55
 Performance, 2-86
 Recreational vehicles; see *Recreational vehicles*
 Semitrailer; see *Design vehicles*
 Track width, 3-94-95, 3-98-112
 Tractor-semitrailer combinations; see *Design vehicles—Truck combinations*
 Truck combinations, 2-58, 2-61; see also *Trucks*
 Vehicular pollution, 2-89-90

Design volume; see *Capacity* or *Traffic*

Detours, 3-195

Diamond interchanges; see *Interchanges*

Directional; see also *Interchanges*

Distribution; see *Traffic*

Lane usage, 7-59-62

Disabilities; see *Persons with disabilities*

Divided highways (other than freeways)

Alignment; see *Alignment—Combinations of*
 Clearances; see *Clearances*
 Cross sections; see *Cross section*
 Cross slope, pavement, 3-87
 Definition, 3-87
 General features, 3-87
 Lane widths, 4-3
 Median openings; see *Median openings*
 Median width, 4-40
 Medians; see *Medians*
 Operational problems, 7-28
 Profile, 7-18-19
 Right-of-way; see *Right-of-way*
 Runoff, 3-87
 Shoulders, 4-13
 Stopping sight distance, 3-14
 Superelevated cross sections, 4-32-33
 Widely separated roadways, 7-17-18, 7-28

Drainage

Channels, 4-25-28
 Controls, 4-32
 on vertical curves, 3-175
 Curb and gutter, 4-14, 4-21-23
 Erosion; see *Erosion Control*
 Pavement, 3-62-64
 Shoulders, 4-13-14
 Storm frequencies, for design, 4-25

Drivers

Alertness, 9-94
 Brake reaction time, 2-5, 3-2-3
 Comfort, 3-164, 4-5, 4-9, 4-59
 Decision maneuver time, 3-7-9
 Error, 2-3, 2-8-2-11
 Expectancy, 2-8
 General, 2-1-2
 Guidance, 2-3-2-4
 Height of eye and object; see *Height*
 Information processing, 2-4-8
 Older, 2-2, 2-9-11
 Perception-reaction times, 9-94-96

- Performance, 2-1–2-3
 - Primacy, 2-8
 - Safety, 2-2–3, 2-8
 - Speed, effects of, 3-24
 - Tasks, 2-2–3
- Driveways**, 4-52–55, 5-8, 6-20, 9-157–158
- Dual-divided freeways**
- Advantages, 8-36–37
 - Arrangements, 8-37
 - Cross section, 8-38; see also *Cross section*
 - Design, 8-36–38
 - Disadvantages, 8-37
 - Examples, 8-38
- Ecology**; see *Environmental evaluation*
- Economic evaluation**
- General, 1-36
 - Motor vehicle operating costs, 10-11
 - Road user costs and benefits, 1-36
- Emergency escape ramps**; see *Ramps*
- Environmental evaluation**
- Drainage channels, 4-24, 4-28
 - Erosion control; see *Erosion control*
 - General, 3-186–187
 - Seeding and planting, 6-11
 - Sideslopes, 4-29–31
- Erosion control**
- Drainage channels, 4-25, 4-28
 - General, 3-186–187
 - Seeding and planting, 6-11
 - Sideslopes, 4-29–31
- Escape Ramps**; see *Ramps*
- Esthetics**; see *Aesthetics*
- Fencing**, 4-57
- Flexibility**
- In Design, 1-32–33
- Formulas**
- Braking distance, 3-4
 - e* and *f* distribution, 3-26
 - Horizontal sightline offset, 3-115
 - Intersection sight distance, 9-45, 9-51
 - Minimum length of runoff, 3-63
 - Minimum length of tangent runout, 3-70
 - Minimum radius, 3-33
 - Offtracking, vehicle turning, 3-92
 - Passing sight distance, elements of, 3-10–14
 - crest vertical curves, 3-171
 - Profile grade and effective maximum relative gradient, 3-88
 - Railroad–highway grade crossing sight distance, 9-163
 - Relative overhang, 3-93
 - Side friction factor, 3-22
 - Sight triangles, see *Formulas—Intersection sight distance*
 - Spiral length, 3-74, 3-76–77, 3-80
 - Stopping, effects of grades on, 3-5
 - Stopping sight distance, 3-5
 - crest vertical curves, 3-166–167
 - horizontal curves, 3-5
 - sag vertical curves, 3-173
 - Storage Length, 9-97
 - Traveled way widening, 3-96, 3-98
 - Traveled way width on curve, 3-103
 - Vehicle operation on a curve, 3-20
 - Weaving sections; see *Weaving sections*
- Four-lane highways**
- Capacity; see *Capacity*
 - Divided; see *Divided highways*
 - Superelevation runoff; see *Superelevation*
 - Ultimate development of, 7-11–14; see also *Arterials*
 - Undivided, 10-80–81
- Freeways**
- Alignment, 8-7–8
 - Borders, 8-6–7
 - Bus facilities, 8-41–47
 - Bus stops, 8-42–47
 - Bus turnouts, 8-42
 - Capacity, 8-2–3
 - Clearances, vertical and horizontal, 8-5
 - Classification, 8-12
 - Collector–distributor roads, 8-39; see also *Interchanges*

- Combination-type, 8-28–32
 - Control of access; see *Control of access and access management*
 - Cross section, 8-10, 8-15–17, 8-21–24, 8-26–27, 8-29–31, 8-33
 - Curbs along, 4-20–21, 8-4
 - Definition, 8-1
 - Depressed, 8-13–18, 10-25
 - Design speed, 3-36–53, 8-2
 - Dual-divided; see *Dual-divided freeways*
 - Elevated, 8-19–25
 - Examples, 8-8, 8-18, 8-24–25, 8-32
 - Frontage roads, 4-43–44, 8-6–7, 8-12, 8-20
 - General design considerations, 8-2–7, 8-12
 - Grades, 8-4–5
 - Ground-level, 8-26–28
 - Lane width, 8-3, 8-21
 - Levels of service, 8-3
 - Maximum grades; see *Grades*
 - Medians, 4-40, 8-3, 8-9–8-11, 8-13, 8-20
 - On embankment, 8-19, 8-23–24
 - Outer separations, 8-6–7
 - Overpasses; see *Grade separations*
 - Pavement, 8-3
 - Profile control, 8-7–8, 8-28–32
 - Rail, 8-47–51
 - Ramps, 8-6, 8-20; see also *Ramps*
 - Reverse-flow, 8-33–36; see also *Reverse-flow roadways*
 - Rural, 8-7–12
 - Safety, 8-1
 - Shoulders, 8-3–4
 - Sideslopes, 4-30, 8-11
 - Structures, 8-5
 - Superelevation, 8-4; see also *Superelevation*
 - Terminals, 8-6, 8-20; see also *Terminals*
 - Terrain, 8-5, 8-28–30
 - Transit facilities, 8-39–51; see also *Public transit*
 - Traveled way, 8-3
 - Tunnels; see *Tunnels*
 - Urban, 8-12
 - Viaduct, 8-19–25
 - Volume, 8-2
 - Walls, 8-6, 8-14, 8-16–17
 - Width, 8-3
- Friction;** see also *Superelevation*
- Ice and snow, 3-24–25
 - Side friction factors
 - open highways, 3-23
 - turning roadways, 3-33
 - urban streets, low-speed, 3-53
- Frontage roads**
- Access control, with and without; see *Control of access and access management*
 - Arterials, 4-41–43
 - Cross street connections to, 9-151–154
 - Cross sections with, 4-43–44
 - Freeways, 4-43–44; see also *Freeways*
 - Functions, 4-41–42
 - General, 4-41
 - Interchanges with, 10-14
 - Intersections with, 9-151–159
 - Means of driveway control, 4-55
 - Outer separation, 4-45; see also *Outer separations*
 - Problems with, 4-43–44
 - Two-way, 4-43–45
- Functional classification;** see *Classification, functional*
- Grades**
- Arterials; see *Arterials*
 - Alignment coordination, 3-182–186
 - At intersections, 9-31–35
 - Climbing lanes; see *Climbing lanes*
 - Collectors; see *Collector roads and streets*
 - Control for design, 3-130–136
 - maximum, 3-130
 - minimum, 3-130
 - Critical lengths, 3-130–136
 - Effect on acceleration, 3-35–36
 - deceleration, 3-5–7
 - drainage, 3-87–88
 - intersection sight distance, 3-5–6
 - noise, 2-89

- passing sight distance, 3-12
- Freeways; see *Freeways*
- General, 3-122
- Grade separations; see *Grade separations*
- Grates, 6-24
- Gutter, 6-24
- Intersections, 9-1
- Local roads and streets; see *Local roads and streets*
- Maximum
 - on arterials, 7-38
 - on collectors; see *Collector roads and streets*
 - on freeways, 8-5
 - relation to design speed, 3-130
- Pedestrian considerations, 3-130
- Profile pertaining to intersections; see *Intersections*
- Ramps; see *Ramps*
- Recreational roads, 5-29-30
- Resource recovery and local service roads, 5-37-38
- Stopping sight distance, 3-5-6
- Superelevation, see *Superelevation*
- Vehicle operations, 3-122
 - passenger cars, 3-122
 - trucks, 3-6-7, 3-122-126
- Weight/power ratio, 3-122-123, 3-126, 3-131
- Grade separations**
 - Arterials, 7-26-7-27
 - Bicycles, 10-151
 - Distance to effect grade separation, 10-27-30
 - Overpass versus underpass, 10-18-21
 - Pedestrian, 10-151
 - Safety; see *Safety*
 - Spacing, 10-8, 10-14
 - Span arrangements, 10-15
 - Stage construction; see *Stage construction*
 - Structures
 - arterials; see *Arterials*
 - bridge railings, 10-25-26
 - clearances, 10-24-25
 - curbs; see *Curbs*
 - design considerations, 10-12
 - freeways; see *Freeways*
 - general, 10-1
 - guardrail at; see *Guardrail*
 - long-span, 10-21
 - medians, 10-12, 10-22
 - overpasses, 10-25-30
 - overpass versus underpass, 10-13, 10-18-21
 - pedestrians, 10-151
 - railroads, 10-28
 - shoulders, 10-22 see also *Shoulders*
 - sidewalks and pedestrian facilities, 4-66-69
 - types, 10-12-18
 - underpasses, 10-22-25; see also *Clearances*
 - Warrants for, 10-3-5
 - With frontage roads, 10-2, 10-14
 - Without ramps, 10-29
- Grading**; see also *Erosion control* and *Landscape development*
 - Grading design, 10-153-154
 - Interchanges, 10-153-154
 - Stage construction; see *Stage construction*
- Guardrail**; see also *Traffic barriers* and *Structures—Railings*
 - Additional width for, 5-34
 - At overpasses, 10-27
 - At underpasses, 10-24
 - Clearance from pavement edge, 4-11
 - Contribution to driver guidance, 2-4-5
 - Damage, as warrant for escape ramps, 3-156
 - Design of, 2-93
 - Gores, 10-115
 - Local roads and streets, 5-23; see also *Local roads and streets*
 - Location of luminaire supports; see *Lighting*
 - Median; see *Medians*
 - Near mailboxes, 4-56
 - Near shoulders, 4-12
 - Placement, 4-11-12
- Guideposts**, see also *Guardrail*
- Gutter**; see *Curbs*

Headlight

- Glare, 2-9, 7-15
- Height of, 3-15
- Sight distance, 3-15–16

Height

- Eye, 3-15
- Headlight, 3-15
- Object, 3-15
- Vehicles, 3-15

High-occupancy vehicle (HOV) facilities, 4-78**Horizontal alignment; see *Alignment—Horizontal*****Horizontal curves; see *Curves—Horizontal*****Horizontal sightline offset, 3-116–117, 10-122****Hydroplaning, 3-20–21, 4-8–9****Information centers; see *Rest areas*****Interchanges**

- Acceleration lanes; see *Speed-change lanes*
- Adaptability, 10-6–8
- Alignment, 10-79–81
- Approaches to, 10-79–82
- Arterials, 7-29, 7-63–64
- Bicycles, 10-151–152
- Capacity, 10-6–7
- Cloverleaf, 10-57–71, 10-95–97
- Collector–distributor roads, 8-39, 10-82, 10-95–97
- Combinations, 10-72–76
- Configurations, 10-76–79
- Continuity, 10-83–84
- Deceleration lanes; see *Speed-change lanes*
- Definition, 10-1
- Design considerations, 10-76–102
- Diamond, 10-40–47
- Directional, 10-63–71
- Diverging diamond, 10-53–57
- Economic factors, 10-11
- Four-leg, 10-39–71
- General, 10-1–2, 10-30–31
- Grading, 10-153–154
- Landscape development, 10-153–154
- Lane balance, 10-87–90

Lane reductions, 10-93–94

Lanes, basic number of, 10-86–90

Lighting; see *Lighting*

Major forks, 10-147–150

Managed lanes, 8-39–40, 10-152

Models, 10-154

Multiple-level, 10-68

Offset, 10-72

Operation, 10-6–7

Overlapping routes, 10-84–85

Partial cloverleaf, 10-60–63

Pedestrians, 10-151–152

Preliminary design, 10-27–29

Profile, 10-79–81

Ramps; see *Ramps*

Ramps in one quadrant, 10-39–40

Ramp metering, 10-152–153

Roundabout, 9-141–151, 10-47

Route continuity, 10-83–84

Safety, 10-9

Semidirectional, 10-73, 10-77

Signing and marking, 10-86

Single-exit design, 10-96–98

Single-point urban, 10-48–52

Site conditions, 10-7

Sight distance, 10-81–82

Spacing, 10-82

Speed-change lanes; see *Speed-change lanes*

Split diamond, 10-42

Stage development, 10-10; see also *Stage construction*

Three-leg, 10-31–38

Transit facilities, 10-152

Trumpet, 10-32–38

Two-exit design, 10-96–98

Type selection, 10-7–8

Types, 10-2–3

Uniformity, 10-82–83

Warrants for, 10-3–5

Weaving sections, 2-38–40, 10-94–95

Wrong way entry at, 10-98–102

Intersection design elements; see *Intersections*

Intersections

- Alignment, 9-31–33
- Angle, 9-14, 9-19
- Arterials, see *Arterials*
- Bicycles, 9-7
- Capacity, 9-9–10
- Channelized, 9-15–23, 9-67–69
- Characteristics, 9-2–3
- Collectors, 6-22
- Continuous left-turn lanes, 7-42–43
- Control devices; see *Traffic control devices*, *Signal control*, or *Signs*
- Curb return radii, 9-65–67
- Curves, see *Curves—Intersection*
- Definition, 9-1
- Design, 2-41, 9-4–9
- Examples
 - four-leg, 9-18, 9-20–21
 - multileg, 9-25
 - roundabouts, 9-29–31, 9-142
 - three-leg, 9-14–17
- Four-leg, 9-18–24
- Frontage roads, 9-151–159
- Functional area of, 9-3–4
- General, 9-1–2
- Grades; see *Grades*
- Illumination levels, 9-156–157
- Islands, 9-69–82
- Lighting, 3-189, 9-156–157
- Local roads and streets; see *Local roads and streets*
- Median lanes; see *Median lanes*
- Median openings; see *Median openings*
- Median width at intersections, 4-39–40
- Multileg, 9-24–26
- Pavement edge design; see *Turning roadways*
- Pedestrians, 2-52–53, 9-7
- Profile, 9-33–35
- Railroad–highway grade crossings; see *Railroad–highway grade crossings*
- Ramp terminals, see also *Terminals*

- Roundabouts, 9-26–31, 9-141–151
- Safety, 9-3–5
- Shoulders; see *Shoulders*
- Sight distance, 9-31, 9-35–60, 9-91–92
- Sight triangles, 9-36–39
- Signal control, effect of; see *Signal control*
- Signs; see *Signs*
- Skew, 9-19–22, 9-58–59
- Storage, 9-96–99
- Superelevation, see also *Superelevation*
- Taper, 9-100–104
- Three-leg, 9-14–18
- Traffic control devices; see *Traffic control devices*, *Signal control*, or *Signs*
- Transitions; see *Transitions*
- Turning movements, 9-42–48, 9-53–58
- Turning roadways; see *Turning roadways*
- Two-way left-turn lanes; see *Median lanes*
- Types, 9-11–31
- U-turns and indirect left turns, 9-124–141; see also *U-turns*
- Wheelchair ramps, 9-74

Islands

- Approach-end treatment, 9-75–81
- Approach nose, 9-76, 9-80–81
 - offset, 9-76
- Channelized; see *Channelization*, *Intersections*
- Corner, 9-82
- Cross section, 9-78–79
- Curbed, 4-19, 4-22, 9-61
- Definition, 9-69–70
- Delineation, 9-70, 9-75–81
- Divisional, 9-72–73
 - intersection with, 9-73
- Examples with; see *Intersections*
- Functions, 9-61, 9-69
- General, 9-69–70
- Non-paved, 9-75
- Refuge, 9-61, 9-74
- Shoulders adjacent to, 9-76–79
- Size and designation, 3-112, 9-74–75

Types, 9-69–70

Landscape development

Collectors; see *Collector roads and streets*

Erosion control; see *Erosion control*

General, 3-186–187

Interchanges, 10-7–8

Local roads and streets; see *Local roads and streets*

Noise control, 2-89–90, 4-51; see also *Noise*

Land Use

Management (controls), 2-45

Zoning, 7-52–53

Lanes

Climbing; see *Climbing lanes*

Exclusive bus, 7-68

Exclusive HOV, 8-41–42

Left turn; see also *Auxiliary lanes*

on arterials; see *Arterials*

on collectors, 6-16

on local roads and streets, 5-16

Parking lanes; see *Parking*

Passing lanes; see *Passing lanes*

Placement of vehicles within, 2-3

Reduction, 10-149–150

Right-turn; see *Auxiliary lanes*

Turning; see *Auxiliary lanes*

Two-way left-turn, 4-39–40

Widths, 4-9–10

Widths with curb and gutter, 4-21–22

Lateral Offset, 4-18

Left Turns; see *Auxiliary lanes*

Lengths

Auxiliary lanes at intersections, 9-19

Curves

intersection; see *Curves–Intersection*

vertical, 3-168–176

Design vehicles; see *Design vehicles*

Grades; see *Grades*

Median openings; see *Median openings*

Sight distance; see *Sight distance*

Spirals, 3-74–75

Storage, 9-96–99

Superelevation runoff, 3-62–69

Superelevation runout; see *Lengths—Tangent runout*

Taper, 10-94

Tangent runout, 3-70; see also *Tangent runout*

Vehicles, see *Vehicles*

Weaving sections; see *Weaving sections*

Levels of Service

Definition, 2-36

Design capacity; see *Capacity*

Selection of, 9-10

Lighting

Arterials; see *Arterials*

Benefits, 3-188–189

Breakaway, 3-190

Design, 3-188

Freeways; see *Freeways*

Guide, 3-188

General, 3-188–190

Heights of luminaires, 3-189–190

Interchanges, 3-189, 10-152

Intersections, 3-189

Location of luminaire supports, 3-190

Movable bridges, 3-189

Objects, 3-188–190

Pedestrian, 10-152

Railroad–highway grade crossing, 3-189

Signs, 3-190

Toll plazas, 3-189

Tunnels, 3-189, 4-59

Uniformity, 3-189

Warrants, 3-188

Work zones, 3-195

Local roads and streets; see also *Collector roads and streets*

General, 5-1–2, 6-1

Low-volume roads, 5-2, 5-10, 5-39, 6-1–2

Recreational roads, 5-27–37

Resource recovery and local service roads,
5-37–39

Rural areas, 1-13, 5-2

- alignment, 5-3
 - bicycle facilities, 5-6, 5-8
 - clearances, 5-9
 - clear zones, 4-17, 5-10
 - cross slope, 5-4
 - curbs, 5-8
 - design speed, 5-2-3
 - design traffic volumes, 5-3
 - drainage, 5-12
 - driveways, 4-54, 5-8
 - erosion control and landscaping, 5-12
 - foreslopes, 5-10
 - intersection design, 5-11
 - grades, 5-3-4
 - lane width, 5-6
 - lateral offset, 5-10
 - levels of service, 5-3
 - medians, 5-7
 - number of lanes, 5-6
 - railroad-highway grade crossings, 5-11
 - right-of-way width, 5-7
 - sight distance, 5-4-5
 - signs and markings, 5-12
 - shoulder width, 5-6
 - structures, 5-9-12
 - superelevation, 4-33, 5-4
 - traffic control devices, 5-12
 - vertical clearance, 5-9
 - width of roadway, 5-6-7
- Urban areas, 1-15, 5-12-13
- alignment, 5-14
 - alleys, 5-20-22
 - bicycle facilities, 5-16, 5-18-19
 - border area, 4-1, 5-17
 - clearances, 5-23
 - clear zones, 4-17, 5-23
 - cross slope, 5-15
 - curb return radius, 5-24
 - curbs, 5-17
 - cul-de-sacs and turnarounds, 5-19-20
 - definition, 5-12-13
 - design speed, 5-14
 - design traffic volume, 5-14
 - drainage, 5-25
 - driveways, 4-54, 5-21
 - erosion control, 5-25-26
 - general, 1-15-16, 5-13
 - grades, 5-15
 - intersection design, 5-23-24
 - landscaping, 5-26
 - lane width, 5-16
 - lateral offset, 4-18, 5-23
 - levels of service, 2-36-37, 5-14
 - lighting, 5-25
 - medians, 5-17
 - number of lanes, 5-16
 - parking lanes, 5-16-17
 - railroad-highway grade crossings, 5-25
 - right-of-way width, 5-17
 - sidewalk curb ramps, 4-70-76, 5-18-19
 - sidewalks, 5-18-19
 - sight distance, 5-16
 - structures, 5-22-23
 - superelevation, 4-33, 5-15
 - traffic control devices, 5-25
 - transit facilities, 5-19
 - utilities, 5-17
 - vertical clearance, 5-23
 - width of roadway, 5-16
 - widths for bridges, 5-22
- Rural town context, 5-12
- Loops;** see *Ramps*
- Low-volume roads;** see *Local roads and streets*
- Mailboxes,** 4-55-57
- Maintenance**
- Interchanges, 10-11
 - Sideslopes, 4-29-31
 - Traffic, during construction, 3-195
- Major forks;** see *Interchanges*
- Managed lanes;** see *Interchanges*
- Markings**
- Approach nose treatment (gore), 10-114-115

- Auxiliary lanes, 10-93
- Centerline, 4-16-17
- Collectors; see *Collector roads and streets*
- Climbing lanes, 3-141; see also *Climbing lanes*
- Curbs, reflectorized, 4-19; see also *Curbs*
- Delineators, 9-70, 9-75-77
- Edge lines, 4-15
- General, 3-193-194
- Islands, 4-19, 9-69, 9-74-75
- Local roads and streets, 5-12
- Median lanes, 9-24
- No passing, 3-10
- Parking lanes, 4-87
- Passing lanes; see *Passing lanes*
- Pavement, 3-193-194
- Pedestrian, 2-51, 3-193-194, 4-71
- Railroad-highway grade crossings, 9-161-162
- Recreational roads, 5-37
- Resource recovery and local service roads, 5-38;
see also *Local roads and streets*
- Shoulders, 4-15; see also *Markings—Edge lines*
- Turnouts for slow vehicles, 4-79

Mass transit, see *Public transit*

Medians

- Arterials, divided; see *Arterials*
- Barrier, 4-35-37
- Collectors; see *Collector roads and streets*
- Contrast, 7-43
- Crashes, 7-44
- Cross section, 4-2-6
- Curbs, 4-21
- Definition, 4-38
- Depressed, 4-39
- Deterrent to wrong-way movements, 10-102
- Drainage channels, 4-5-6, 4-27
- End, shape or treatment of, 9-113
- Flush, 4-39
- For ultimate development of divided arterial,
7-12; see also *Arterials*
- Freeways; see *Freeways*
- Frontage roads, 4-42, 9-158-159

- General, 4-38-41
- Islands; see *Islands*
- Lane; see *Median lanes*
- Local roads and streets, 6-7
- On overpass, 10-27
- Openings; see *Median openings*
- Raised, 4-39; see also *Medians—Curbs*
- Slopes; see *Sideslopes*
- Summary, 4-38
- Transversable; see *Medians—Flush*
- Types, 4-39
- Variation in width of, 4-38-39
- Width, 4-38-40
 - at intersections, 4-38-39
- U-turns, design for, 9-124-125; see also *U-turns*

Median barriers

- Arterials, 7-16-7-18, 7-44-45
- Curbs; see *Curbs*
- Freeways, 4-36; see also *Freeways*
- General, 4-35-37
- Types, 4-36

Median lanes

- Left-turn, 9-110-113
- Special designs for left turns, 9-111-112
- Storage, 9-96-99
- Two-way left-turn, 4-39-40
- Width, 4-39; see also *Auxiliary lanes*

Median openings

- Bullet nose, 9-120
- Control radii, 9-119-120, 9-122-123
- Design for cross traffic, 9-123
- Designs for left turns, 9-110-113
- Emergency crossovers, 9-118
- General, 9-118-119
- Higher speed left turns, 9-122-123
- Intersections, 9-118-123
- Length (and shape), 9-120-123
- Minimum length, 9-122-123
- On arterials, 7-18, 7-41
- On collector roads and streets, 6-17-18

- Semicircular, 9-120–121
 - Shape of median end, 9-113, 9-120–121
 - Skew, effect of, 9-121
 - Space between, U-turns, 9-133–135; see also *U-Turns*
 - With median lanes; see *Median lanes*
- Multilane Highways;** see also *Arterials, Divided highways*
- Climbing lanes, 3-142; see also *Climbing lanes*
 - Cross slope, 4-5
 - Intersections with, 2-33
 - Safety, 3-36
 - Sight distance, 3-14
 - Undivided; see *Control of access and access management*
- Multimodal Considerations,** 1-6–7
- New Construction Projects;** see *Project Types*
- Noise**
- Abatement criteria, 4-47–48
 - Barriers, 4-48–51
 - Design noise levels, 2-89–90
 - Design procedure to control, 4-47
 - From vehicles, 2-89–90
 - General considerations, 2-89–90; 4-46–47
 - Human reactions, 4-46–47
 - Landscaping, effect on, 4-51
 - Location, effect on, 4-49–51
 - Physical measurement, decibels, 4-47
 - Reduction design, 4-48–51
- Nose;** see *Approach nose*
- Offset;** see *Clearances*
- One-way roadways;** see *Divided highways*
- One-way streets,** 7-59–60
- Operating speed,** 2-22
- Outer separations**
- Arterials, 4-45–46
 - Definition, 4-45
 - Designs, 4-46
 - Drainage, 4-45
 - Freeways; see *Freeways*
 - Frontage roads, 4-44
 - General, 4-45
 - Width, 4-45
- Overpasses;** see *Grade separations*
- Parking**
- Central business district, 4-87
 - Curb, 4-85–87
 - Design, 4-85–87
 - Lanes, 4-86
 - Lane width, 4-86
 - on arterials, 4-86; see also *Arterials*
 - on collectors, 4-86, 6-7, 6-16–17
 - on local roads and streets, 4-86–87, 5-16–17
 - On-street, 4-85–87
 - Park-and-ride facilities, 4-82–84
 - Residential areas, 4-85
 - Rest areas; see *Rest areas*
- Passenger cars**
- Acceleration, 2-86–87
 - Design vehicles; see *Design vehicles*
 - Traffic, composition of, 2-19
 - Turning path, 2-58–64
- Passing lanes**
- Definition, 3-145
 - Examples, 3-147
 - General, 3-145–149
 - Length, 3-147–149
 - Location, 3-145–146
 - Need for, 3-145–146, 7-11
 - Number of lanes, 3-147–148
 - Operational benefits, 3-145
 - Shoulders, 3-147–148
 - Sight distance, 3-10–14
 - Tapers, 3-148
 - Transitions, 3-148
 - Traffic control devices, 3-148
- Passing sections**
- Frequency, 3-137
 - Lanes; see *Passing lanes*
 - No-passing zones, 3-10, 3-13
 - Shoulder driving, 3-153–154
 - Shoulder use sections, 3-154
 - Sight distance, 3-10–14

Turnouts, 3-152–153, 4-16

Passing sight distance

Arterials, see *Arterials*

Collectors; see *Collector roads and streets*

Criteria for design, 3-10

Definition, 3-10

Design values, 3-10–12

Effect of grade, 3-12

Elements of, 3-10–14

Frequency and length, 3-12–14

Height of eye, 3-15

Height of object, 3-15

Local roads and streets; see *Local roads and streets*

Measuring, 3-15–19

Multilane highways, 3-14

On horizontal curves, 3-119

On recreational roads, 5-32–33

On resource recovery and local service roads; see
Local roads and streets

On vertical curves, 3-11

Relation to stopping sight distance, 3-10

Paths, see also *Turning* or *Turning roadways*

Pavement, 4-1–7; see also *Traveled way*

Contrasts; see *Contrasting surfaces*

Cross slope, 4-2; see also *Cross slope*

Edge lines, 4-16

General, 4-1–7

Lane widths; see *Lanes*

Markings; see *Markings*

Railroad–highway grade crossings, 6-10

Recreational roads, 5-29, 5-31

Resource recovery and local service roads; see
Local roads and streets

Skid resistance, 4-8

Surface (types), 4-1–2

Unpaved surfaces, 4-7–8

Widening on curves, 3-101

Widths

lane; see *Width*

ramps; see *Ramps*

turning roadways; *Turning roadways*

Peak-hour factor (PHF), 2-35; see also *Capacity*

Peak-hour traffic

Design, 2-14

Directional distribution, 2-18

Future, 2-14

General, 2-14–19

Maximum, 2-14

Thirtieth highest, 2-14

Pedestrians; see also *Pedestrian facilities* and
Sidewalks

Capacity (walkway), 2-52

Characteristics, 2-50–51

Crosswalks; see *Crosswalks*

Disabilities, accommodating persons with, 1-24–
25, 2-53–54, 4-8, 4-13, 4-66, 4-70–77,
4-81–83, 5-6, 5-8, 5-15, 5-18–19, 6-16,
6-19–20, 7-9, 8-42, 8-44–47, 8-49

General, 1-24–25, 2-50

Safety, 2-51

Walking speeds, 2-52

Pedestrian facilities; see also *Pedestrians*

Arterials; see *Arterials*

At-grade crossings, 4-65–66

Crossing distance, effect of radii on, 9-61

Crosswalks; see *Crosswalks*

Depressed freeways; see *Freeways*

Disabilities, accommodating persons with, 1-24–
25, 2-53–54, 4-8, 4-13, 4-66, 4-70–77,
4-81–83, 5-6, 5-8, 5-15, 5-18–19, 6-16,
6-19–20, 7-9, 8-42, 8-44–47, 8-49

Grade separations; see *Grade separations*

Intersections, 2-52–53, 9-156

Interchanges, 10-151–152

Pedestrian overpasses, 2-50, 4-67–69

Pedestrian underpasses, 2-50–51, 4-67–68

Protective screens, 4-68–69

Ramps, 4-70–77; see also *Sidewalk curb ramps*

Restricted Crossing (RCUT); see *U-turns*

Separations; see *Grade separations*

Sidewalks; see *Sidewalks*

Signals, 2-51, 3-193–194

Signs, 2-51, 3-193–194

- Stairs (stairways), 8-42, 8-46
- Width, 2-52
- Perception–reaction time**, 9-94–96
- Performance-based design**, 2-86
- Persons with disabilities**, 1-24–25, 2-53–54, 4-8, 4-13, 4-66, 4-70–77, 4-81–83, 5-6, 5-8, 5-15, 5-18–19, 6-16, 6-19–20, 7-9, 8-42, 8-44–47, 8-49
- Planning**
 - Freeway, 8-2
 - Functional classification; see *Classification, functional*
 - Land use, 2-38
 - Transportation improvements, 1-26, 2-17
 - Ultimate development of four-lane divided arterials; see *Arterials*
- Pollution Control**; see also *Noise*
 - Vehicular emissions, 2-89–90
- Project purpose and need**, 1-3–5
- Project types**, 1-28–32
 - New construction projects, 1-28–29
 - Reconstruction projects, 1-29–30
 - Construction projects on existing roads, 1-30–32
- Public transit**
 - Buses, 4-78–84
 - Bus lanes, 7-68
 - Bus stops, 4-79–84, 7-66–67
 - General, 4-77–78
 - High-occupancy vehicle (HOV) facilities, 4-82–84
 - Joint use of right-of-way, 8-40
 - On arterials, 4-80–82; see also *Arterials*
 - On freeways, 4-79–80; see also *Freeways*
 - Rail, 8-47–51
 - Rapid transit, 4-77–78
 - Stairs, ramps, and escalators, 8-46–47
 - Station location and spacing, 8-49–50
 - Turnouts, bus, 4-79–82
- Profile**; see *Alignment—Vertical*
- Radii**
 - Curb return, 9-65–67
 - Intersection, 9-64, 9-117–120
 - Islands, ends of, 9-76; see also *Islands*
 - Minimum, 3-33–36
 - Minimum radius curves without superelevation, 3-20
 - Minimum turning, 2-58–85, 9-119–120
 - Tables, 3-34–35
 - Turning roadways, 3-61, 9-61
- Railroad–highway grade crossings**
 - Alignment and profile, 9-159–160
 - Arterials; see *Arterials*
 - Collectors, 6-10
 - Design, 9-161–162
 - Lighting, 3-189
 - Local roads and streets, 6-10
 - Protective devices, 9-161
 - Sight distance, 9-162–168
 - Surface types, 9-168
 - Traffic control, 6-10, 9-161–162
 - Widths, 6-10
- Rail transit**; see *Public transit*
- Ramps**
 - Alignment, 10-102, 10-107–111
 - Approach nose, 10-109, 10-123–125
 - Button-hooked, 10-127–128
 - Clearances
 - at structures, 10-110
 - horizontal; see *Clearances*
 - Components, 10-102
 - Compound curves, 10-107
 - Connection to frontage roads, 4-44, 10-42
 - Contrasting surface, 10-122
 - Controlling feature, 2-43
 - Crossover crown line, 10-111
 - Cross section, 10-121
 - Cross slope, 10-111–114
 - Curbs, 4-70–76, 10-122
 - Curvature, 10-107–109
 - Definition, 10-102
 - Design speed, 10-105–106
 - Diagonal, 10-102–103

- Direct connection, 10-103, 10-106
- Distance between successive ramp terminals, 10-126–128
- Emergency escape, 3-154–164
 - example, 3-163
 - maintenance, 3-164
- Entrances and exits, 10-128–150
- Examples, 10-102–105
- Gores, 8-20, 10-37, 10-114–120
- Grades, 10-109–110
- Lane reductions; see *Lanes*
- Left, 10-32, 10-123
- Lengths, 10-109–112
- Loop, 10-103, 10-106, 10-124
- Metering; see *Interchanges*
- Number; see *Interchanges—Configurations*
- Outer connection, 10-103
- Partial cloverleaf, 10-60–63
- Pedestrians; see *Pedestrian facilities*
- Profile, 10-109–110
- Radii; see *Radii*
- Right turns, 10-105
- Semidirect, 10-103, 10-106
- Shapes, 10-102–105
- Shoulders, 10-121–122
- Sidewalk curb, 4-70–76
- Sight distance, 10-102, 10-109, 10-123–124
- Slip, 10-108
- Speed-change lanes, 10-128
- Spiral curves; see *Transitions*
- Superelevation, 10-111–114
- Terminal design, 2-34–35, 10-106–107, 10-123–128
- Traffic control, 2-34–35, 2-43, 10-124–125
- Tapers, 10-118, 10-128–130
- Traveled-way widths, 10-121–122
- Types, 10-102–105
- Vertical curves, 10-111
- Weaving; see *Weaving sections*
- Wheelchair, 9-74
- Widths, 10-121
 - Wrong-way entry, 10-98–102
- Ramp metering**; see *Interchanges*
- Rapid transit**; see *Public transit*
- Reconstruction projects**, see *Project types*
- Recovery area**; see *Clear zones*
- Recreational roads**, 5-27–37; see also *Local roads and streets*
- Recreational vehicles**, 2-55–57, 2-86
 - Climbing lanes for, 3-144
 - Effects on volume, 2-35
 - On grades, 3-126, 3-129, 3-133–136
- Resource recovery and local service roads**, 5-37–39; see also *Local roads and streets*
- Rest areas**, 3-187–188
 - Definition, 3-187
 - Information centers, 3-187
 - Scenic overlooks, 3-187
- Retaining walls**
 - Effect on traffic operations, 4-9, 7-48
 - Lateral clearances; see *Clearances*
 - Need for, 4-29, 8-6–7, 8-14
 - On depressed freeways, 8-14
 - Sight distance, 3-118, 10-81
- Reverse-flow roadways**, 8-33–36
 - Advantages, 8-33–34
 - Cross section, 8-33
 - Examples, 8-35–36
 - Terminals, 8-34–36
- Right turns**; see *Auxiliary lanes*
- Right-of-way**
 - Arterials; see *Arterials*
 - Collectors; see *Local roads and streets*
 - Drainage, 4-23–26
 - Freeways; see *Freeways*
 - Interchanges; see *Interchanges*
 - Local roads and streets; see *Local roads and streets*
 - Two-lane highways, 7-7, 7-11–12
 - Utilities, accommodating, 3-190–193
 - Width, 5-7, 6-7, 7-6–7, 7-24–27
 - With frontage roads, 9-153–154

Roadside

- Access control; see *Control of access and access management*
- Borders and sidewalks; see *Borders or Sidewalks*
- Clear zones; see *Clear zones*
- Driveways, 4-52–55
- Erosion control, 4-28
- Fencing, 4-57
- Mailboxes, 4-55–57
- Recovery areas; see *Clear zones*
- Seeding and planting; see *Erosion control*
- Sideslopes, 4-28–32
- Sight distance; see *Sight distance*

Roadway, definition, 4-1**Roadway width; see Lanes****Road user benefit analyses; see Economic evaluation****Roundabouts; see Intersections****Rounding**

- Shoulders, 4-32
- Sideslopes, 4-30–32

Runoff; see Superelevation**Runout, superelevation; see Tangent runout****Safety**

- Alignment; see *Alignment—Horizontal or Alignment—Vertical*
- Auxiliary lanes, 4-17
- Bicycles, 2-54–55
- Borders, 6-19
- Bus stops; see *Buses*
- Causal factors for crashes, multiple, 2-90–2-91
- Climbing lanes, 3-137
- Clear zones, 2-92, 4-17
- Control of access, 2-45–49, 2-91–93
- Crashes, 2-94
- Curbs, 4-19–21
- Decisions, frequency of, 2-8
- Driver errors, 2-8–9
- Driver expectancy, 2-8
- Day versus night, 3-170–171
- Emergency escape ramps, 3-154–164
- Frontage roads, 4-41, 9-151–157

General, 2-90

Grade, 3-130–136

Grade separations; see *Grade separation*

Guardrail, 2-93

Interchanges, 10-9

Intersections, 9-2

Lane width, 4-9

Lighting, 3-188–190

Local roads and streets; see *Local roads and streets*

Low-volume roads, 4-10

Mailboxes, 4-55–57

Maneuvers, traffic, 3-7–9

Medians, 4-35–37

Older drivers, 2-2

Pavement skid resistance, 4-8

Pedestrians; see *Pedestrians*

Rail transit, 8-47–51

Ramps, 10-102–105

Range/variance of speeds; see *Speed*

Relation to geometric design, 1-3–5

Responsibility, 2-90

Rest areas, 3-188

Reverse-flow operation, 7-60–62

Roadside design, 2-92–93, 4-17–18

Roadside development, 3-189

Roundabouts, 9-146

Rumble strips, 4-16–17, 10-115

Sight distance; see *Sight distance*

Slope breaks, 4-2–4

Speed, 2-91–92

Speed-change lanes, 10-128

Traffic barriers, 2-92–93, 4-21

Traffic control devices, 2-93, 3-193–194

Trucks, 3-2–7

Two-way left-turn lanes, 9-116

Tunnels, 4-57–58

Work zones, 3-195

Scenic overlooks; see Rest areas**Shoulders**

- Adjacent to climbing lanes; see *Climbing lanes*
- islands, 9-76–79

- passing lanes; see *Passing lanes*
- Arterials; see *Arterials*
- Continuous, 4-12–13
- Contrasting surfaces, 4-15–16
- Cross section, 4-13–14
- Cross slope, design values, 4-14
- Cross slope, maximum slope break; see *Cross slope*
- Curb, 4-12
- Curb, along outer edge, 4-12
- Definition, 4-10
- Divided highways; see *Divided highways*
- Driving, 3-153–154, 4-10
- Freeways; see *Freeways*
- General characteristics, 4-10–12
- Graded width, 4-10, 4-12–13
- Intermittent, 4-12–13
- Left shoulder, divided highways, 8-3, 8-9, 8-21, 8-34
- Local roads and streets; see *Local roads and streets*
- On structure, 4-13, 10-22
- Paved, 4-10
- Ramps; see *Ramps*
- Sidewalks; see *Sidewalks*
- Stability, 4-14–15
- Superelevation; see *Cross slope*
- Turnouts; see *Turnouts*
- Useable width, 4-10, 4-12–13
- Use sections, 3-154
- Vertical clearance; see *Clearances*
- Width, 3-112–113, 4-10–12
- With guardrail; see *Guardrails*
- Sideslopes**
 - Channels, drainage, 4-28–32
 - Collectors; see *Collector roads and streets*
 - Earth slopes, 4-29
 - Erosion prevention; see *Erosion control*
 - Freeways, 4-30
 - General, 4-23, 4-28
 - Local roads and streets, see *Local roads and streets*
 - Regions, 4-28
 - Roadside recovery area, 4-28–31
 - Rock slopes, 4-31
 - Rounding, 4-30–31
 - Safety, 4-28–29
 - Sight distance; see *Sight distance*
 - Treatment to avoid snowdrifting, 4-31
- Sidewalks**
 - Along roadways, 4-32
 - Location, 4-65–4-67
 - Overpasses, 4-67–4-69, 10-25–10-26
 - Pedestrians; see *Pedestrians* or *Pedestrian facilities*
 - Roundabouts, 9-150–151
 - Underpasses, 4-67–4-68
 - Widths, 2-52, 4-65, 6-19, 9-8
- Sidewalk curb ramps, 4-70–76**
- Sight distance**
 - Arterials; see *Arterials*
 - Collectors; see *Collector roads and streets*
 - Criteria for measuring, 3-15
 - Decision, 3-7–9
 - Definition, 3-15
 - Design for, 3-1–3-19
 - Design speed, in relation to, 3-4–6, 3-8–9, 3-11–14
 - General, 3-1–3-2
 - Headlight, 3-15–16
 - Height of eye, 3-15
 - Height of object, 3-15
 - Horizontal curves, 3-113–119; see also *Curves—Horizontal*
 - Interchanges; see *Interchanges*
 - Intersections; see *Intersections*
 - Local roads and streets; see *Local roads and streets*
 - Measuring and recording, 3-15–19
 - Multilane highways, 3-14
 - No control, intersections with, 9-40–42
 - Passing; see *Passing sight distance*
 - Perception–reaction, 3-12
 - Railroad–highway grade crossings, 6-10
 - Recreational roads, 5-31–32
 - Resource recovery and local service roads; see *Local roads and streets*

- Roundabouts, 9-151
 - Signal control, intersections with, 9-55-56
 - Skew, 9-58-59
 - Stop control, intersections with, 9-42-47
 - Stopping; see *Stopping sight distance*
 - Underpasses, 3-177-179, 10-20
 - Vertical curves, 3-166-179
 - Yield control, intersections with, 9-50-55
- Sight triangles**, 9-36-39
- Signal control**
- Arterials; see *Arterials*
 - Effect on intersection design, 3-193-194
 - Location, 3-193-194
 - Pedestrians, 3-193-194, 9-63
 - Warrants, 3-193-194
- Signs**
- Arterials, 7-9, 7-34, 7-57, 7-61
 - Climbing lanes; see *Climbing lanes*
 - Collectors; see *Collector roads and streets*
 - Construction, 3-195
 - Detours, 3-195
 - Escape ramps, 3-161
 - General, 3-193-194
 - Intersections, 9-24, 9-37
 - Islands, 9-70, 9-75
 - Local roads and streets; see *Local roads and streets*
 - Location, 3-193-194
 - Passing lanes; see *Passing lanes*
 - Railroad-highway grade crossings, 6-10
 - Recreational roads, 5-37
 - Resource recovery and local service roads; see *Local roads and streets*
 - Relationship to design, 3-193-194
 - Shoulder use sections, 3-154
 - Types, 2-4
- Single-point diamond interchange**; see *Interchanges*
- Skid resistance**; see *Pavement*
- Sloping curbs**; see *Curbs*
- Speed**
- Curve speed, 3-21-30
 - Design; see *Design speed*
 - Function, 2-22-27
 - Operating, 2-22
 - Pedestrian, walking, 2-52
 - Running, 2-22-23, 3-30, 3-36
 - Safety, 2-91-92
 - Spot, 2-23
 - Trucks, on grades, 3-6-7, 3-122-126, 3-133-136
- Speed-change lanes**
- Acceleration lanes, 4-79, 9-63, 9-94
 - Bus turnouts, 4-79
 - Deceleration lanes, 9-62, 9-94
 - Definition, 10-128
 - General, 10-128
 - Intersections, 9-62
 - Length, 10-130-142
 - Ramps; see *Ramps*
 - Taper; see *Tapers*
 - Warrants, 9-105-109
 - Width, 10-27
- Spirals**; see *Transitions*
- Spline**
- For runoff, 10-111
 - For vertical curves, 9-91, 10-111
- Stage construction**
- Grade separation structures, 10-10
 - Interchanges, 10-10
 - Ultimate development of four-lane divided arterials; see *Arterials*
- Stop control**
- Intersections; see *Intersections*
 - Ramp terminals; see *Ramps*
- Stopping sight distance**
- Arterials; see *Arterials*
 - Barriers, noise, 4-49
 - Brake reaction time, 3-2-3
 - Braking distance, 3-3-5
 - Collectors, 6-5, 6-15
 - Deceleration rate, 3-3-4
 - Design values, 3-5-6
 - Effect of grade, 3-5-6
 - General, 3-2

- Height of eye, 3-15
 - Height of object, 3-15
 - Intersections; see also *Intersections—Sight distance*
 - Local roads and streets; see *Local roads and streets*
 - Multilane highways, 3-14
 - Measuring and recording, 3-15–19
 - On horizontal curves, 3-114–119
 - On vertical curves
 - crest, 3-7, 3-15, 3-166
 - sag, 3-172
 - Perception–reaction time, 9-94–96
 - Recreational roads, 5-31–32
 - Resource recovery and local service roads; see *Local roads and streets*
 - Trucks, 3-6–7
 - Wet pavement, 3-4–5
- Structures;** see also *Grade separations*
- Clearances; see *Clearances*
 - Collectors; see *Collector roads and streets*
 - Freeways; see *Freeways*
 - Local roads and streets; see *Local roads and streets*
 - Lighting; see *Lighting*
 - Pedestrian accommodations; see *Pedestrian facilities*
 - Railings, 10-25–26
 - Roadway width, 10-21
 - Structural capacity, 5-9
- Superelevation**
- Accelerometer, 3-24
 - Arterials; see *Arterials*
 - Axis of rotation with medians, 3-86–87
 - Ball-bank indicator, 3-23
 - Collectors; see *Collector roads and streets*
 - Design rates, 3-41–52
 - Development of finalized *e* distribution, 3-37
 - Distribution of *e* and *f*, 3-37–41
 - Effect of grades, 3-35–36
 - Freeways, 3-36; see also *Freeways*
 - General considerations, 3-20–21
 - Intersection curves, 9-59, 9-83
 - maximum rate, 3-32
 - runoff, 9-83–84
 - Limiting rates, 3-20–21, 3-72–73, 3-78–79
 - Local roads and streets; see *Local roads and streets*
 - Low-speed design, 3-62
 - Maximum rates, 3-31–33
 - Ramps; see *Ramps*
 - Rates for design, 3-41–52
 - Recreational roads, 5-31–32
 - Resource recovery and local service roads; see *Local roads and streets*
 - Runoff, 3-61–85
 - definition, 3-61
 - design, smooth profiles, 3-85
 - length, 3-62–69
 - location with respect to end of curve, 3-81
 - methods of attainment, 3-81–85
 - with medians, 4-6
 - Runout, tangent, 3-70; see also *Tangent runout*
 - Sharpest curve without, 3-58
 - Side friction factor, 3-21–30
 - Theoretical considerations, 3-72
 - Typical cross sections, 4-4
 - Turning roadway terminals, 3-60, 9-84–91
 - Urban streets, low speed, 3-53–59
- Surface;** see *Pavement*
- Systems;** see *Classification, functional*
- Tangent runout,** 3-70, 3-79–81
- Tapers**
- Auxiliary lanes; see *Auxiliary lanes*
 - Beyond offset nose, 10-118
 - Climbing lanes; see *Climbing lanes*
 - Passing lanes; see *Passing lanes*
 - Speed-change lanes, 9-100–104
 - Turnouts, 3-152–153, 4-16
- Terminals**
- Capacity; see *Capacity*
 - Distance between, 10-126–128
 - Distance from structure, 10-125–126
 - Elevated freeways, 8-20; see also *Freeways*
 - Entrance, 10-128–134, 10-143–145
 - Exit, 10-135–139, 10-146–147

Gore areas, 8-20; see also *Ramps*

Multilane free-flow, 10-143

Ramp; see *Ramps*

Sight distance; see *Sight distance*

Single-lane free-flow, 10-128-143

Superelevation, 3-60

Terrain, 3-121-122

Topography

- Effect on alignment, 3-119-122, 3-181
 - climbing lanes, 3-137-139
 - design speed, 9-160
 - grade separation structures, 10-18-22
 - interchange design, 10-2-4, 10-7
 - passing lanes, 3-147
 - widely separated roadways, 7-12-13, 7-28
 - warrants for grade separation, 10-18

Traffic

- Average daily (ADT), 2-13-14, 2-18
- Characteristics, 2-13-29
- Composition, 2-19-20
- Control devices; see *Traffic control devices*
- Current, 2-20
- Design hourly volume (DHV), 2-13, 2-16-18
- Design traffic conditions, 2-13
- Design year, 2-13
- Directional distribution, 2-18-19
- Flow, 2-27-29, 2-37-41
- General considerations, 2-13
- Highest hourly volume (HV), 2-14-18
- Lane assignment, 9-4, 9-145
- Maintenance during construction, 3-195
- Passenger car, 2-19
- Passenger-car equivalency, 2-35
- Peak-hour, 2-35
- Projection, 2-20-21
- Seasonal fluctuation, 2-16
- Speed, 2-21-29
- Thirtieth highest hourly volume (30 HV), 2-14-16
- Truck, 2-19; see also *Trucks*
- Volume, 2-13-17

Traffic barriers

- Bridge railings, 4-37, 10-25-26
- Curbs, 4-21, 4-23
- Crash cushions, 2-92, 4-36, 4-38
- General, 4-33-34
- Longitudinal, 4-34-37
- Median, 4-35-37
- Roadside, 4-12, 4-34-35

Traffic control devices

- Arterials; see *Arterials*
- Collectors, 6-11
- General, 2-4, 2-93, 3-193-194
- Intersections, 3-194, 9-39-9-40
- Local roads and streets, 6-11
- Markings; see *Markings*
- Reverse-flow roadways, 8-36
- Railroad-highway grade crossings; see *Railroad-highway grade crossings*
- Sight distance at intersections, relationship to, 3-8, 9-37, 9-47
- Signals; see *Signal control*
- Signs; see *Signs*

Traffic regulation, 9-67

Transit facilities, see *Public transit*

Transitions

- Advantages, 3-61-62
- Adjustment factors, 3-63-64
- Compound curves, 3-81, 3-88-91
- Definition, 3-61
- General, 3-61-62
- Minimum grades, 3-87-88
- Runoff, superelevation; see *Superelevation*
- Runout, tangent, 3-70, 3-79-80
- Spiral curves, 3-62, 3-73-85, 3-89, 10-32, 10-107
- Traveled way widening, 3-74, 3-91-104
- Turning roadways, 3-88-89
- Types, 3-61
- Two-lane and four-lane sections, 3-63-64

Traveled way, 4-1-9

- Definition, 4-1

Ramp width; see *Ramps*
 Traffic conditions, 3-111
 Widening on curves, 3-91–103
 Width; see *Width*

Trucks; see also *Design vehicles*

Acceleration on grades, 3-122–126
 Brake-check areas, 3-164
 Climbing lanes; see *Climbing lanes*
 Combination, 2-61
 Control grades, 3-130–136
 Critical length of grade, 3-126, 3-130–136
 Deceleration on grades, 3-6–7
 Definition for operational analysis, 2-19
 Height of eye, 3-15
 Minimum turning radius, 2-58–85
 Off-tracking, 2-61, 3-91–96
 Operating characteristics on grades, 3-122–126
 Single unit, 2-62, 2-65–66
 Stopping sight distance, 3-2–7
 Weight/power ratio, 3-123, 3-126, 3-136

Tunnels

Alignment, 4-59
 Clearances, 4-62
 Costs, 4-58
 Cross section, 4-61, 4-63
 Design considerations, 4-59–60
 Examples, 4-63–64
 General, 4-57–58
 Grades, 4-59
 Lighting, 3-189, 4-59
 Sidewalks, 4-21
 Types, 4-58
 Ventilation, 4-59

Turning; see also *Design vehicles*

Design vehicles, 2-58–85
 Indirect left turns, 9-124–141
 Lanes; see *Auxiliary Lanes*
 Movements; see *Intersections*
 Operation on curves, 3-98
 Radius, minimum, 2-58–59, 9-119–120
 Simultaneous left turns, 9-115–117

Speed, 9-122–123
 Track width, 3-92–96

Turning roadways

Approach nose, 9-76–80, 9-84
 Curvature, 3-59–61
 Crosswalk, 9-60–61
 Design, 3-59, 9-63–65
 Effect of curb radii, 9-65–67
 General, 3-59, 9-60
 Islands, 9-61, 9-82; see also *Islands*
 Pedestrians, 9-63
 Radii, 3-61, 9-61
 Right-angle turns, 9-65
 Shoulders, 3-112–113
 Stopping sight distance, 9-91–92
 Superelevation, 3-59–61, 9-83–91
 Terminal design, 3-77–78, 9-83–90
 Widths, 3-103–112, 9-60

Turnouts

Bus, see also *Buses*
 Definition, 3-152
 On two-lane roads, 3-152–153

Two-lane highways

2+1 roadways, 3-149–152
 Arterials; see *Arterials*
 Climbing lanes, 3-137–142
 Collectors, 6-2
 Local roads and streets, 5-6–7
 Passing lanes; see *Passing lanes*
 Passing sight distance, 3-10–14
 Shoulder driving, 3-153–154
 Shoulder use sections, 3-154
 Turnouts, 3-152–153, 5-34

Ultimate development; see *Arterials*

Underpasses; see *Grade separations*

Utilities

Adjacent to clear zones, 3-192
 General, 3-190–192
 Location, 3-191–192
 Rural, 3-192
 Urban, 3-192–193, 6-19, 7-56

U-turns

- Crossovers, 9-130–135
- Designs for, 9-126–135
- Median openings, 9-136–139
- Restricted crossing (RCUT), 9-131–135
- Spacing, 9-136–140
- Special designs, 9-141

Vehicles; see *Design vehicles, Recreational vehicles, Trucks, and Turning*

Vertical alignment, see *Alignment—Vertical*

Vertical curbs; see *Curbs*

Vertical curves; see *Curves—Vertical*

Viaducts; see *Freeways*

Walkways; see *Sidewalks*

Warrants

- Climbing lanes; see *Climbing lanes*
- Grade separations, 10-3–5
- Interchanges, 10-3–5
- Passing lanes; see *Passing lanes*
- Shoulders, 4-10–12
- Sidewalks, 2-50–54, 4-65–67

Weaving sections

- Capacity, 2-38
- Cloverleafs, 10-95
- Definition, 2-32, 2-34, 10-94
- Design volumes, 2-38
- Examples, 2-39
- General, 2-32, 2-38
- Length, 2-38–40
- Multiple, 2-40
- Simple, 2-40
- Types, 2-38–40

Widening

- Design values, 3-91–97
- To introduce divisional islands, 9-73
- Traveled way, on curves, 3-91–104

Width

- Arterials; see *Arterials*
- Borders, 6-19
- Bridges and drainage structures; see *Structures*
- Climbing lanes; see *Climbing lanes*

Collectors; see *Collector roads and streets*

Extra allowance for operation on curves, 3-98

Gutter, 4-21–22

Lanes, 4-9–10; see also *Lanes*

Local roads and streets, 5-6–7

Medians, 4-38–40

Median lanes, see also *Median lanes*

Outside traveled way, 3-112–113

Pavement; see *Pavement*

Ramps, 3-160

Right-of-way, see also *Right-of-way*

Shoulders; see *Shoulders*

Sidewalks; see *Sidewalks*

Track, 3-92

Traveled way, 3-96–110

Turning roadways; see *Turning roadways*

Wrong-way entry

Design to discourage, 9-69, 10-102

Zoning; see *Land use*

Access control, 2-45–46