

# AASHTO LRFD Bridge Design Specifications Customary U.S. Units

## DETAILED TABLE OF CONTENTS

### SECTION 1: INTRODUCTION

- 1.1—SCOPE OF THE SPECIFICATIONS
- 1.2—DEFINITIONS
- 1.3—DESIGN PHILOSOPHY
  - 1.3.1—General
  - 1.3.2—Limit States
    - 1.3.2.1—General
    - 1.3.2.2—Service Limit State
    - 1.3.2.3—Fatigue and Fracture Limit State
    - 1.3.2.4—Strength Limit State
    - 1.3.2.5—Extreme Event Limit States
  - 1.3.3—Ductility
  - 1.3.4—Redundancy
  - 1.3.5—Operational Importance
- 1.4—REFERENCES

### SECTION 2: GENERAL DESIGN AND LOCATION FEATURES

- 2.1—SCOPE
- 2.2—DEFINITIONS
- 2.3—LOCATION FEATURES
  - 2.3.1—Route Location
    - 2.3.1.1—General
    - 2.3.1.2—Waterway and Floodplain Crossings
  - 2.3.2—Bridge Site Arrangement
    - 2.3.2.1—General
    - 2.3.2.2—Traffic Safety
      - 2.3.2.2.1—Protection of Structures
      - 2.3.2.2.2—Protection of Users
      - 2.3.2.2.3—Geometric Standards
      - 2.3.2.2.4—Road Surfaces
      - 2.3.2.2.5—Vessel Collisions
  - 2.3.3—Clearances
    - 2.3.3.1—Navigational
    - 2.3.3.2—Highway Vertical
    - 2.3.3.3—Highway Horizontal
    - 2.3.3.4—Railroad Overpass
  - 2.3.4—Environment
- 2.4—FOUNDATION INVESTIGATION
  - 2.4.1—General
  - 2.4.2—Topographic Studies
- 2.5—DESIGN OBJECTIVES
  - 2.5.1—Safety
  - 2.5.2—Serviceability
    - 2.5.2.1—Durability
      - 2.5.2.1.1—Materials
      - 2.5.2.1.2—Self-Protecting Measures
    - 2.5.2.2—Inspectability
    - 2.5.2.3—Maintainability
    - 2.5.2.4—Rideability
    - 2.5.2.5—Utilities
    - 2.5.2.6—Deformations
      - 2.5.2.6.1—General

- 2.5.2.6.2—Criteria for Deflection
- 2.5.2.6.3—Optional Criteria for Span-to-Depth Ratios
- 2.5.2.7—Consideration of Future Widening
  - 2.5.2.7.1—Exterior Beams on Multibeam Bridges
  - 2.5.2.7.2—Substructure
- 2.5.3—Constructibility
- 2.5.4—Economy
  - 2.5.4.1—General
  - 2.5.4.2—Alternative Plans
- 2.5.5—Bridge Aesthetics
- 2.6—HYDROLOGY AND HYDRAULICS
  - 2.6.1—General
  - 2.6.2—Site Data
  - 2.6.3—Hydrologic Analysis
  - 2.6.4—Hydraulic Analysis
    - 2.6.4.1—General
    - 2.6.4.2—Stream Stability
    - 2.6.4.3—Bridge Waterway
    - 2.6.4.4—Bridge Foundations
      - 2.6.4.4.1—General
      - 2.6.4.4.2—Bridge Scour
    - 2.6.4.5—Roadway Approaches to Bridge
  - 2.6.5—Culvert Location, Length, and Waterway Area
  - 2.6.6—Roadway Drainage
    - 2.6.6.1—General
    - 2.6.6.2—Design Storm
    - 2.6.6.3—Type, Size, and Number of Drains
    - 2.6.6.4—Discharge from Deck Drains
    - 2.6.6.5—Drainage of Structures
- 2.7—BRIDGE SECURITY
  - 2.7.1—General
  - 2.7.2—Design Demand
- 2.8—REFERENCES

### **SECTION 3: LOADS AND LOAD FACTORS**

- 3.1—SCOPE
- 3.2—DEFINITIONS
- 3.3—NOTATION
  - 3.3.1—General
  - 3.3.2—Load and Load Designation
- 3.4—LOAD FACTORS AND COMBINATIONS
  - 3.4.1—Load Factors and Load Combinations
  - 3.4.2—Load Factors for Construction Loads
    - 3.4.2.1—Evaluation at the Strength Limit State
    - 3.4.2.2—Evaluation of Deflection at the Service Limit State
  - 3.4.3—Load Factors for Jacking and Post-Tensioning Forces
    - 3.4.3.1—Jacking Forces
    - 3.4.3.2—Force for Post-Tensioning Anchorage Zones
- 3.5—PERMANENT LOADS
  - 3.5.1—Dead Loads: *DC*, *DW*, and *EV*
  - 3.5.2—Earth Loads: *EH*, *ES*, and *DD*
- 3.6—LIVE LOADS
  - 3.6.1—Gravity Loads: *LL* and *PL*
    - 3.6.1.1—Vehicular Live Load
      - 3.6.1.1.1—Number of Design Lanes
      - 3.6.1.1.2—Multiple Presence of Live Load
    - 3.6.1.2—Design Vehicular Live Load
      - 3.6.1.2.1—General

- 3.6.1.2.2—Design Truck
- 3.6.1.2.3—Design Tandem
- 3.6.1.2.4—Design Lane Load
- 3.6.1.2.5—Tire Contact Area
- 3.6.1.2.6—Distribution of Wheel Loads through Earth Fills
- 3.6.1.3—Application of Design Vehicular Live Loads
  - 3.6.1.3.1—General
  - 3.6.1.3.2—Loading for Optional Live Load Deflection Evaluation
  - 3.6.1.3.3—Design Loads for Decks, Deck Systems, and the Top Slabs of Box Culverts
  - 3.6.1.3.4—Deck Overhang Load
- 3.6.1.4—Fatigue Load
  - 3.6.1.4.1—Magnitude and Configuration
  - 3.6.1.4.2—Frequency
  - 3.6.1.4.3—Load Distribution for Fatigue
    - 3.6.1.4.3a—Refined Methods
    - 3.6.1.4.3b—Approximate Methods
- 3.6.1.5—Rail Transit Load
- 3.6.1.6—Pedestrian Loads
- 3.6.1.7—Loads on Railings
- 3.6.2—Dynamic Load Allowance: *IM*
  - 3.6.2.1—General
  - 3.6.2.2—Buried Components
  - 3.6.2.3—Wood Components
- 3.6.3—Centrifugal Forces: *CE*
- 3.6.4—Braking Force: *BR*
- 3.6.5—Vehicular Collision Force: *CT*
  - 3.6.5.1—Protection of Structures
  - 3.6.5.2—Vehicle Collision with Barriers
- 3.7—WATER LOADS: *WA*
  - 3.7.1—Static Pressure
  - 3.7.2—Buoyancy
  - 3.7.3—Stream Pressure
    - 3.7.3.1—Longitudinal
    - 3.7.3.2—Lateral
  - 3.7.4—Wave Load
  - 3.7.5—Change in Foundations Due to Limit State for Scour
- 3.8—WIND LOAD: *WL AND WS*
  - 3.8.1—Horizontal Wind Pressure
    - 3.8.1.1—General
    - 3.8.1.2—Wind Pressure on Structures: *WS*
      - 3.8.1.2.1—General
      - 3.8.1.2.2—Loads from Superstructures
      - 3.8.1.2.3—Forces Applied Directly to the Substructure
    - 3.8.1.3—Wind Pressure on Vehicles: *WL*
  - 3.8.2—Vertical Wind Pressure
  - 3.8.3—Aeroelastic Instability
    - 3.8.3.1—General
    - 3.8.3.2—Aeroelastic Phenomena
    - 3.8.3.3—Control of Dynamic Responses
    - 3.8.3.4—Wind Tunnel Tests
- 3.9—ICE LOADS: *IC*
  - 3.9.1—General
  - 3.9.2—Dynamic Ice Forces on Piers
    - 3.9.2.1—Effective Ice Strength
    - 3.9.2.2—Crushing and Flexing
    - 3.9.2.3—Small Streams
    - 3.9.2.4—Combination of Longitudinal and Transverse Forces
      - 3.9.2.4.1—Piers Parallel to Flow
      - 3.9.2.4.2—Piers Skewed to Flow
    - 3.9.2.5—Slender and Flexible Piers

- 3.9.3—Static Ice Loads on Piers
- 3.9.4—Hanging Dams and Ice Jams
- 3.9.5—Vertical Forces Due to Ice Adhesion
- 3.9.6—Ice Accretion and Snow Loads on Superstructures
- 3.10—EARTHQUAKE EFFECTS: *EQ*
  - 3.10.1—General
  - 3.10.2—Seismic Hazard
    - 3.10.2.1—General Procedure
    - 3.10.2.2—Site Specific Procedure
  - 3.10.3—Site Effects
    - 3.10.3.1—Site Class Definitions
    - 3.10.3.2—Site Factors
  - 3.10.4—Seismic Hazard Characterization
    - 3.10.4.1—Design Response Spectrum
    - 3.10.4.2—Elastic Seismic Response Coefficient
  - 3.10.5—Operational Classification
  - 3.10.6—Seismic Performance Zones
  - 3.10.7—Response Modification Factors
    - 3.10.7.1—General
    - 3.10.7.2—Application
  - 3.10.8—Combination of Seismic Force Effects
  - 3.10.9—Calculation of Design Forces
    - 3.10.9.1—General
    - 3.10.9.2—Seismic Zone 1
    - 3.10.9.3—Seismic Zone 2
    - 3.10.9.4—Seismic Zones 3 and 4
      - 3.10.9.4.1—General
      - 3.10.9.4.2—Modified Design Forces
      - 3.10.9.4.3—Inelastic Hinging Forces
        - 3.10.9.4.3a—General
        - 3.10.9.4.3b—Single Columns and Piers
        - 3.10.9.4.3c—Piers with Two or More Columns
        - 3.10.9.4.3d—Column and Pile Bent Design Forces
        - 3.10.9.4.3e—Pier Design Forces
        - 3.10.9.4.3f—Foundation Design Forces
    - 3.10.9.5—Longitudinal Restrainers
    - 3.10.9.6—Hold-Down Devices
  - 3.10.10—Requirements for Temporary Bridges and Stage Construction
- 3.11—EARTH PRESSURE: *EH, ES, LS, AND DD*
  - 3.11.1—General
  - 3.11.2—Compaction
  - 3.11.3—Presence of Water
  - 3.11.4—Effect of Earthquake
  - 3.11.5—Earth Pressure: *EH*
    - 3.11.5.1—Lateral Earth Pressure
    - 3.11.5.2—At-Rest Lateral Earth Pressure Coefficient,  $k_o$
    - 3.11.5.3—Active Lateral Earth Pressure Coefficient,  $k_a$
    - 3.11.5.4—Passive Lateral Earth Pressure Coefficient,  $k_p$
    - 3.11.5.5—Equivalent-Fluid Method of Estimating Rankine Lateral Earth Pressures
    - 3.11.5.6—Lateral Earth Pressures for Nongravity Cantilevered Walls
    - 3.11.5.7—Apparent Earth Pressure (*AEP*) for Anchored Walls
      - 3.11.5.7.1—Cohesionless Soils
      - 3.11.5.7.2—Cohesive Soils
        - 3.11.5.7.2a—Stiff to Hard
        - 3.11.5.7.2b—Soft to Medium Stiff
    - 3.11.5.8—Lateral Earth Pressures for Mechanically Stabilized Earth Walls
      - 3.11.5.8.1—General
      - 3.11.5.8.2—Internal Stability
    - 3.11.5.9—Lateral Earth Pressures for Prefabricated Modular Walls
  - 3.11.6—Surcharge Loads: *ES* and *LS*

- 3.11.6.1—Uniform Surcharge Loads (*ES*)
- 3.11.6.2—Point, Line, and Strip Loads (*ES*)—Walls Restrained from Movement
- 3.11.6.3—Strip Loads (*ES*)—Flexible Walls
- 3.11.6.4—Live Load Surcharge (*LS*)
- 3.11.6.5—Reduction of Surcharge
- 3.11.7—Reduction Due to Earth Pressure
- 3.11.8—Downdrag
- 3.12—FORCE EFFECTS DUE TO SUPERIMPOSED DEFORMATIONS: *TU, TG, SH, CR, SE, PS*
  - 3.12.1—General
  - 3.12.2—Uniform Temperature
    - 3.12.2.1—Temperature Range for Procedure A
    - 3.12.2.2—Temperature Range for Procedure B
    - 3.12.2.3—Design Thermal Movements
  - 3.12.3—Temperature Gradient
  - 3.12.4—Differential Shrinkage
  - 3.12.5—Creep
  - 3.12.6—Settlement
  - 3.12.7—Secondary Forces from Post-Tensioning, *PS*
- 3.13—FRICTION FORCES: *FR*
- 3.14—VESSEL COLLISION: *CV*
  - 3.14.1—General
  - 3.14.2—Owner’s Responsibility
  - 3.14.3—Operational Classification
  - 3.14.4—Design Vessel
  - 3.14.5—Annual Frequency of Collapse
    - 3.14.5.1—Vessel Frequency Distribution
    - 3.14.5.2—Probability of Aberrancy
      - 3.14.5.2.1—General
      - 3.14.5.2.2—Statistical Method
      - 3.14.5.2.3—Approximate Method
    - 3.14.5.3—Geometric Probability
    - 3.14.5.4—Probability of Collapse
    - 3.14.5.5—Protection Factor
  - 3.14.6—Design Collision Velocity
  - 3.14.7—Vessel Collision Energy
  - 3.14.8—Ship Collision Force on Pier
  - 3.14.9—Ship Bow Damage Length
  - 3.14.10—Ship Collision Force on Superstructure
    - 3.14.10.1—Collision with Bow
    - 3.14.10.2—Collision with Deck House
    - 3.14.10.3—Collision with Mast
  - 3.14.11—Barge Collision Force on Pier
  - 3.14.12—Barge Bow Damage Length
  - 3.14.13—Damage at the Extreme Limit State
  - 3.14.14—Application of Impact Force
    - 3.14.14.1—Substructure Design
    - 3.14.14.2—Superstructure Design
  - 3.14.15—Protection of Substructures
  - 3.14.16—Security Considerations
- 3.15—BLAST LOADING
  - 3.15.1—Introduction
- 3.16—REFERENCES

APPENDIX A3—SEISMIC DESIGN FLOWCHARTS

APPENDIX B3—OVERSTRENGTH RESISTANCE

## SECTION 4: STRUCTURAL ANALYSIS AND EVALUATION

### 4.1—SCOPE

### 4.2—DEFINITIONS

### 4.3—NOTATION

### 4.4—ACCEPTABLE METHODS OF STRUCTURAL ANALYSIS

### 4.5—MATHEMATICAL MODELING

#### 4.5.1—General

#### 4.5.2—Structural Material Behavior

##### 4.5.2.1—Elastic Versus Inelastic Behavior

##### 4.5.2.2—Elastic Behavior

##### 4.5.2.3—Inelastic Behavior

#### 4.5.3—Geometry

##### 4.5.3.1—Small Deflection Theory

##### 4.5.3.2—Large Deflection Theory

###### 4.5.3.2.1—General

###### 4.5.3.2.2—Approximate Methods

###### 4.5.3.2.2a—General

###### 4.5.3.2.2b—Moment Magnification—Beam Columns

###### 4.5.3.2.2c—Moment Magnification—Arches

###### 4.5.3.2.3—Refined Methods

#### 4.5.4—Modeling Boundary Conditions

#### 4.5.5—Equivalent Members

### 4.6—STATIC ANALYSIS

#### 4.6.1—Influence of Plan Geometry

##### 4.6.1.1—Plan Aspect Ratio

##### 4.6.1.2—Structures Curved in Plan

###### 4.6.1.2.1—General

###### 4.6.1.2.2—Single-Girder Torsionally Stiff Superstructures

###### 4.6.1.2.3—Multicell Concrete Box Girders

###### 4.6.1.2.4—Steel Multiple-Beam Superstructures

###### 4.6.1.2.4a—General

###### 4.6.1.2.4b—I-Girders

###### 4.6.1.2.4c—Closed Box and Tub Girders

#### 4.6.2—Approximate Methods of Analysis

##### 4.6.2.1—Decks

###### 4.6.2.1.1—General

###### 4.6.2.1.2—Applicability

###### 4.6.2.1.3—Width of Equivalent Interior Strips

###### 4.6.2.1.4—Width of Equivalent Strips at Edges of Slabs

###### 4.6.2.1.4a—General

###### 4.6.2.1.4b—Longitudinal Edges

###### 4.6.2.1.4c—Transverse Edges

###### 4.6.2.1.5—Distribution of Wheel Loads

###### 4.6.2.1.6—Calculation of Force Effects

###### 4.6.2.1.7—Cross-Sectional Frame Action

###### 4.6.2.1.8—Live Load Force Effects for Fully and Partially Filled Grids and for Unfilled Grid Decks Composite with Reinforced Concrete Slabs

###### 4.6.2.1.9—Inelastic Analysis

##### 4.6.2.2—Beam-Slab Bridges

###### 4.6.2.2.1—Application

###### 4.6.2.2.2—Distribution Factor Method for Moment and Shear

###### 4.6.2.2.2a—Interior Beams with Wood Decks

###### 4.6.2.2.2b—Interior Beams with Concrete Decks

###### 4.6.2.2.2c—Interior Beams with Corrugated Steel Decks

###### 4.6.2.2.2d—Exterior Beams

###### 4.6.2.2.2e—Skewed Bridges

###### 4.6.2.2.2f—Flexural Moments and Shear in Transverse Floorbeams

###### 4.6.2.2.3—Distribution Factor Method for Shear

###### 4.6.2.2.3a—Interior Beams

- 4.6.2.2.3b—Exterior Beams
      - 4.6.2.2.3c—Skewed Bridges
    - 4.6.2.2.4—Curved Steel Bridges
    - 4.6.2.2.5—Special Loads with Other Traffic
  - 4.6.2.3—Equivalent Strip Widths for Slab-Type Bridges
  - 4.6.2.4—Truss and Arch Bridges
  - 4.6.2.5—Effective Length Factor,  $K$
  - 4.6.2.6—Effective Flange Width
    - 4.6.2.6.1—General
    - 4.6.2.6.2—Segmental Concrete Box Beams and Single-Cell, Cast-in-Place Box Beams
    - 4.6.2.6.3—Cast-in-Place Multicell Superstructures
    - 4.6.2.6.4—Orthotropic Steel Decks
    - 4.6.2.6.5—Transverse Floorbeams and Integral Bent Caps
  - 4.6.2.7—Lateral Wind Load Distribution in Multibeam Bridges
    - 4.6.2.7.1—I-Sections
    - 4.6.2.7.2—Box Sections
    - 4.6.2.7.3—Construction
  - 4.6.2.8—Seismic Lateral Load Distribution
    - 4.6.2.8.1—Applicability
    - 4.6.2.8.2—Design Criteria
    - 4.6.2.8.3—Load Distribution
  - 4.6.2.9—Analysis of Segmental Concrete Bridges
    - 4.6.2.9.1—General
    - 4.6.2.9.2—Strut-and-Tie Models
    - 4.6.2.9.3—Effective Flange Width
    - 4.6.2.9.4—Transverse Analysis
    - 4.6.2.9.5—Longitudinal Analysis
      - 4.6.2.9.5a—General
      - 4.6.2.9.5b—Erection Analysis
      - 4.6.2.9.5c—Analysis of the Final Structural System
  - 4.6.2.10—Equivalent Strip Widths for Box Culverts
    - 4.6.2.10.1—General
    - 4.6.2.10.2—Case 1: Traffic Travels Parallel to Span
    - 4.6.2.10.3—Case 2: Traffic Travels Perpendicular to Span
    - 4.6.2.10.4—Precast—Box Culverts
- 4.6.3—Refined Methods of Analysis
  - 4.6.3.1—General
  - 4.6.3.2—Decks
    - 4.6.3.2.1—General
    - 4.6.3.2.2—Isotropic Plate Model
    - 4.6.3.2.3—Orthotropic Plate Model
  - 4.6.3.3—Beam-Slab Bridges
    - 4.6.3.3.1—General
    - 4.6.3.3.2—Curved Steel Bridges
  - 4.6.3.4—Cellular and Box Bridges
  - 4.6.3.5—Truss Bridges
  - 4.6.3.6—Arch Bridges
  - 4.6.3.7—Cable-Stayed Bridges
  - 4.6.3.8—Suspension Bridges
- 4.6.4—Redistribution of Negative Moments in Continuous Beam Bridges
  - 4.6.4.1—General
  - 4.6.4.2—Refined Method
  - 4.6.4.3—Approximate Procedure
- 4.6.5—Stability
- 4.6.6—Analysis for Temperature Gradient
- 4.7—DYNAMIC ANALYSIS
  - 4.7.1—Basic Requirements of Structural Dynamics
    - 4.7.1.1—General
    - 4.7.1.2—Distribution of Masses
    - 4.7.1.3—Stiffness

- 4.7.1.4—Damping
- 4.7.1.5—Natural Frequencies
- 4.7.2—Elastic Dynamic Responses
  - 4.7.2.1—Vehicle-Induced Vibration
  - 4.7.2.2—Wind-Induced Vibration
    - 4.7.2.2.1—Wind Velocities
    - 4.7.2.2.2—Dynamic Effects
    - 4.7.2.2.3—Design Considerations
- 4.7.3—Inelastic Dynamic Responses
  - 4.7.3.1—General
  - 4.7.3.2—Plastic Hinges and Yield Lines
- 4.7.4—Analysis for Earthquake Loads
  - 4.7.4.1—General
  - 4.7.4.2—Single-Span Bridges
  - 4.7.4.3—Multispan Bridges
    - 4.7.4.3.1—Selection of Method
    - 4.7.4.3.2—Single-Mode Methods of Analysis
      - 4.7.4.3.2a—General
      - 4.7.4.3.2b—Single-Mode Spectral Method
      - 4.7.4.3.2c—Uniform Load Method
    - 4.7.4.3.3—Multimode Spectral Method
    - 4.7.4.3.4—Time-History Method
      - 4.7.4.3.4a—General
      - 4.7.4.3.4b—Acceleration Time Histories
  - 4.7.4.4—Minimum Support Length Requirements
  - 4.7.4.5— $P$ - $\Delta$  Requirements
- 4.7.5—Analysis for Collision Loads
- 4.7.6—Analysis of Blast Effects
- 4.8—ANALYSIS BY PHYSICAL MODELS
  - 4.8.1—Scale Model Testing
  - 4.8.2—Bridge Testing
- 4.9—REFERENCES

#### APPENDIX A4—DECK SLAB DESIGN TABLE

### SECTION 5: CONCRETE STRUCTURES

- 5.1—SCOPE
- 5.2—DEFINITIONS
- 5.3—NOTATION
- 5.4—MATERIAL PROPERTIES
  - 5.4.1—General
  - 5.4.2—Normal Weight and Structural Lightweight Concrete
    - 5.4.2.1—Compressive Strength
    - 5.4.2.2—Coefficient of Thermal Expansion
    - 5.4.2.3—Shrinkage and Creep
      - 5.4.2.3.1—General
      - 5.4.2.3.2—Creep
      - 5.4.2.3.3—Shrinkage
    - 5.4.2.4—Modulus of Elasticity
    - 5.4.2.5—Poisson's Ratio
    - 5.4.2.6—Modulus of Rupture
    - 5.4.2.7—Tensile Strength
  - 5.4.3—Reinforcing Steel
    - 5.4.3.1—General
    - 5.4.3.2—Modulus of Elasticity
    - 5.4.3.3—Special Applications
  - 5.4.4—Prestressing Steel
    - 5.4.4.1—General

- 5.4.4.2—Modulus of Elasticity
- 5.4.5—Post-Tensioning Anchorages and Couplers
- 5.4.6—Ducts
  - 5.4.6.1—General
  - 5.4.6.2—Size of Ducts
  - 5.4.6.3—Ducts at Deviation Saddles
- 5.5—LIMIT STATES
  - 5.5.1—General
  - 5.5.2—Service Limit State
  - 5.5.3—Fatigue Limit State
    - 5.5.3.1—General
    - 5.5.3.2—Reinforcing Bars
    - 5.5.3.3—Prestressing Tendons
    - 5.5.3.4—Welded or Mechanical Splices of Reinforcement
  - 5.5.4—Strength Limit State
    - 5.5.4.1—General
    - 5.5.4.2—Resistance Factors
      - 5.5.4.2.1—Conventional Construction
      - 5.5.4.2.2—Segmental Construction
      - 5.5.4.2.3—Special Requirements for Seismic Zones 2, 3, and 4
    - 5.5.4.3—Stability
  - 5.5.5—Extreme Event Limit State
- 5.6—DESIGN CONSIDERATIONS
  - 5.6.1—General
  - 5.6.2—Effects of Imposed Deformation
  - 5.6.3—Strut-and-Tie Model
    - 5.6.3.1—General
    - 5.6.3.2—Structural Modeling
    - 5.6.3.3—Proportioning of Compressive Struts
      - 5.6.3.3.1—Strength of Unreinforced Strut
      - 5.6.3.3.2—Effective Cross-Sectional Area of Strut
      - 5.6.3.3.3—Limiting Compressive Stress in Strut
      - 5.6.3.3.4—Reinforced Strut
    - 5.6.3.4—Proportioning of Tension Ties
      - 5.6.3.4.1—Strength of Tie
      - 5.6.3.4.2—Anchorage of Tie
    - 5.6.3.5—Proportioning of Node Regions
    - 5.6.3.6—Crack Control Reinforcement
- 5.7—DESIGN FOR FLEXURAL AND AXIAL FORCE EFFECTS
  - 5.7.1—Assumptions for Service and Fatigue Limit States
  - 5.7.2—Assumptions for Strength and Extreme Event Limit States
    - 5.7.2.1—General
    - 5.7.2.2—Rectangular Stress Distribution
  - 5.7.3—Flexural Members
    - 5.7.3.1—Stress in Prestressing Steel at Nominal Flexural Resistance
      - 5.7.3.1.1—Components with Bonded Tendons
      - 5.7.3.1.2—Components with Unbonded Tendons
      - 5.7.3.1.3—Components with Both Bonded and Unbonded Tendons
        - 5.7.3.1.3a—Detailed Analysis
        - 5.7.3.1.3b—Simplified Analysis
    - 5.7.3.2—Flexural Resistance
      - 5.7.3.2.1—Factored Flexural Resistance
      - 5.7.3.2.2—Flanged Sections
      - 5.7.3.2.3—Rectangular Sections
      - 5.7.3.2.4—Other Cross-Sections
      - 5.7.3.2.5—Strain Compatibility Approach
    - 5.7.3.3—Limits for Reinforcement
      - 5.7.3.3.1—Maximum Reinforcement
      - 5.7.3.3.2—Minimum Reinforcement
    - 5.7.3.4—Control of Cracking by Distribution of Reinforcement

- 5.7.3.5—Moment Redistribution
- 5.7.3.6—Deformations
  - 5.7.3.6.1—General
  - 5.7.3.6.2—Deflection and Camber
  - 5.7.3.6.3—Axial Deformation
- 5.7.4—Compression Members
  - 5.7.4.1—General
  - 5.7.4.2—Limits for Reinforcement
  - 5.7.4.3—Approximate Evaluation of Slenderness Effects
  - 5.7.4.4—Factored Axial Resistance
  - 5.7.4.5—Biaxial Flexure
  - 5.7.4.6—Spirals and Ties
  - 5.7.4.7—Hollow Rectangular Compression Members
    - 5.7.4.7.1—Wall Slenderness Ratio
    - 5.7.4.7.2—Limitations on the Use of the Rectangular Stress Block Method
      - 5.7.4.7.2a—General
      - 5.7.4.7.2b—Refined Method for Adjusting Maximum Usable Strain Limit
      - 5.7.4.7.2c—Approximate Method for Adjusting Factored Resistance
- 5.7.5—Bearing
- 5.7.6—Tension Members
  - 5.7.6.1—Factored Tension Resistance
  - 5.7.6.2—Resistance to Combinations of Tension and Flexure
- 5.8—SHEAR AND TORSION
  - 5.8.1—Design Procedures
    - 5.8.1.1—Flexural Regions
    - 5.8.1.2—Regions Near Discontinuities
    - 5.8.1.3—Interface Regions
    - 5.8.1.4—Slabs and Footings
  - 5.8.2—General Requirements
    - 5.8.2.1—General
    - 5.8.2.2—Modifications for Lightweight Concrete
    - 5.8.2.3—Transfer and Development Lengths
    - 5.8.2.4—Regions Requiring Transverse Reinforcement
    - 5.8.2.5—Minimum Transverse Reinforcement
    - 5.8.2.6—Types of Transverse Reinforcement
    - 5.8.2.7—Maximum Spacing of Transverse Reinforcement
    - 5.8.2.8—Design and Detailing Requirements
    - 5.8.2.9— Shear Stress on Concrete
  - 5.8.3—Sectional Design Model
    - 5.8.3.1 General
    - 5.8.3.2—Sections Near Supports
    - 5.8.3.3—Nominal Shear Resistance
    - 5.8.3.4—Procedures for Determining Shear Resistance
      - 5.8.3.4.1—Simplified Procedure for Nonprestressed Sections
      - 5.8.3.4.2—General Procedure
      - 5.8.3.4.3 Simplified Procedure for Prestressed and Nonprestressed Sections
    - 5.8.3.5—Longitudinal Reinforcement
    - 5.8.3.6—Sections Subjected to Combined Shear and Torsion
      - 5.8.3.6.1—Transverse Reinforcement
      - 5.8.3.6.2—Torsional Resistance
      - 5.8.3.6.3—Longitudinal Reinforcement
  - 5.8.4—Interface Shear Transfer—Shear Friction
    - 5.8.4.1—General
    - 5.8.4.2—Computation of the Factored Interface Shear Force,  $V_{ui}$ , for Girder/Slab Bridges
    - 5.8.4.3—Cohesion and Friction Factors
    - 5.8.4.4—Minimum Area of Interface Shear Reinforcement
  - 5.8.5—Principal Stresses in Webs of Segmental Concrete Bridges
  - 5.8.6—Shear and Torsion for Segmental Box Girder Bridges
    - 5.8.6.1 General
    - 5.8.6.2—Loading

- 5.8.6.3—Regions Requiring Consideration of Torsional Effects
- 5.8.6.4—Torsional Reinforcement
- 5.8.6.5—Nominal Shear Resistance
- 5.8.6.6—Reinforcement Details
- 5.9—PRESTRESSING AND PARTIAL PRESTRESSING
  - 5.9.1—General Design Considerations
    - 5.9.1.1—General
    - 5.9.1.2—Specified Concrete Strengths
    - 5.9.1.3—Buckling
    - 5.9.1.4—Section Properties
    - 5.9.1.5—Crack Control
    - 5.9.1.6—Tendons with Angle Points or Curves
  - 5.9.2—Stresses Due to Imposed Deformation
  - 5.9.3—Stress Limitations for Prestressing Tendons
  - 5.9.4—Stress Limits for Concrete
    - 5.9.4.1—For Temporary Stresses before Losses—Fully Prestressed Components
      - 5.9.4.1.1—Compression Stresses
      - 5.9.4.1.2—Tension Stresses
    - 5.9.4.2—For Stresses at Service Limit State after Losses—Fully Prestressed Components
      - 5.9.4.2.1—Compression Stresses
      - 5.9.4.2.2—Tension Stresses
    - 5.9.4.3—Partially Prestressed Components
  - 5.9.5—Loss of Prestress
    - 5.9.5.1—Total Loss of Prestress
    - 5.9.5.2—Instantaneous Losses
      - 5.9.5.2.1—Anchorage Set
      - 5.9.5.2.2—Friction
        - 5.9.5.2.2a—Pretensioned Construction
        - 5.9.5.2.2b—Post-Tensioned Construction
      - 5.9.5.2.3—Elastic Shortening
        - 5.9.5.2.3a—Pretensioned Members
        - 5.9.5.2.3b—Post-Tensioned Members
        - 5.9.5.2.3c—Combined Pretensioning and Post-Tensioning
    - 5.9.5.3—Approximate Estimate of Time-Dependent Losses
    - 5.9.5.4—Refined Estimates of Time-Dependent Losses
      - 5.9.5.4.1—General
      - 5.9.5.4.2—Losses: Time of Transfer to Time of Deck Placement
        - 5.9.5.4.2a—Shrinkage of Girder Concrete
        - 5.9.5.4.2b—Creep of Girder Concrete
        - 5.9.5.4.2c—Relaxation of Prestressing Strands
      - 5.9.5.4.3—Losses: Time of Deck Placement to—Final Time
        - 5.9.5.4.3a—Shrinkage of Girder Concrete
        - 5.9.5.4.3b—Creep of Girder Concrete
        - 5.9.5.4.3c—Relaxation of Prestressing Strands
        - 5.9.5.4.3d—Shrinkage of Deck Concrete
      - 5.9.5.4.4—Precast Pretensioned Girders without Composite Topping
      - 5.9.5.4.5—Post-Tensioned Nonsegmental Girders
    - 5.9.5.5—Losses for Deflection Calculations
- 5.10—DETAILS OF REINFORCEMENT
  - 5.10.1—Concrete Cover
  - 5.10.2—Hooks and Bends
    - 5.10.2.1—Standard Hooks
    - 5.10.2.2—Seismic Hooks
    - 5.10.2.3—Minimum Bend Diameters
  - 5.10.3—Spacing of Reinforcement
    - 5.10.3.1—Minimum Spacing of Reinforcing Bars
      - 5.10.3.1.1—Cast-in-Place Concrete
      - 5.10.3.1.2—Precast Concrete
      - 5.10.3.1.3—Multilayers
      - 5.10.3.1.4—Splices

- 5.10.3.1.5—Bundled Bars
- 5.10.3.2—Maximum Spacing of Reinforcing Bars
- 5.10.3.3—Minimum Spacing of Prestressing Tendons and Ducts
  - 5.10.3.3.1—Pretensioning Strand
  - 5.10.3.3.2—Post-Tensioning Ducts—Girders Straight in Plan
  - 5.10.3.3.3—Post-Tensioning Ducts—Girders Curved—in Plan
- 5.10.3.4—Maximum Spacing of Prestressing Tendons and Ducts in Slabs
- 5.10.3.5—Couplers in Post-Tensioning Tendons
- 5.10.4—Tendon Confinement
  - 5.10.4.1—General
  - 5.10.4.2—Wobble Effect in Slabs
  - 5.10.4.3—Effects of Curved Tendons
    - 5.10.4.3.1—In-Plane Force Effects
    - 5.10.4.3.2—Out-of-Plane Force Effects
- 5.10.5—External Tendon Supports
- 5.10.6—Transverse Reinforcement for Compression Members
  - 5.10.6.1—General
  - 5.10.6.2—Spirals
  - 5.10.6.3—Ties
- 5.10.7—Transverse Reinforcement for Flexural Members
- 5.10.8—Shrinkage and Temperature Reinforcement
- 5.10.9—Post-Tensioned Anchorage Zones
  - 5.10.9.1—General
  - 5.10.9.2—General Zone and Local Zone
    - 5.10.9.2.1—General
    - 5.10.9.2.2—General Zone
    - 5.10.9.2.3—Local Zone
    - 5.10.9.2.4—Responsibilities
  - 5.10.9.3—Design of the General Zone
    - 5.10.9.3.1—Design Methods
    - 5.10.9.3.2—Design Principles
    - 5.10.9.3.3—Special Anchorage Devices
    - 5.10.9.3.4—Intermediate Anchorages
      - 5.10.9.3.4a—General
      - 5.10.9.3.4b—Tie-Backs
      - 5.10.9.3.4c—Blister and Rib Reinforcement
    - 5.10.9.3.5 Diaphragms
    - 5.10.9.3.6—Multiple Slab Anchorages
    - 5.10.9.3.7—Deviation Saddles
  - 5.10.9.4—Application of the Strut-and-Tie Model to the Design of General Zone
    - 5.10.9.4.1—General
    - 5.10.9.4.2—Nodes
    - 5.10.9.4.3—Struts
    - 5.10.9.4.4—Ties
  - 5.10.9.5—Elastic Stress Analysis
  - 5.10.9.6—Approximate Stress Analyses and Design
    - 5.10.9.6.1—Limitations of Application
    - 5.10.9.6.2—Compressive Stresses
    - 5.10.9.6.3—Bursting Forces
    - 5.10.9.6.4—Edge Tension Forces
  - 5.10.9.7—Design of Local Zones
    - 5.10.9.7.1—Dimensions of Local Zone
    - 5.10.9.7.2—Bearing Resistance
    - 5.10.9.7.3—Special Anchorage Devices
- 5.10.10—Pretensioned Anchorage Zones
  - 5.10.10.1—Splitting Resistance
  - 5.10.10.2—Confinement Reinforcement
- 5.10.11—Provisions for Seismic Design
  - 5.10.11.1—General
  - 5.10.11.2—Seismic Zone 1

- 5.10.11.3—Seismic Zone 2
- 5.10.11.4—Seismic Zones 3 and 4
  - 5.10.11.4.1—Column Requirements
    - 5.10.11.4.1a—Longitudinal Reinforcement
    - 5.10.11.4.1b—Flexural Resistance
    - 5.10.11.4.1c—Column Shear and Transverse Reinforcement
    - 5.10.11.4.1d—Transverse Reinforcement for Confinement at Plastic Hinges
    - 5.10.11.4.1e—Spacing of Transverse Reinforcement for Confinement
    - 5.10.11.4.1f—Splices
  - 5.10.11.4.2—Requirements for Wall-Type Piers
  - 5.10.11.4.3—Column Connections
  - 5.10.11.4.4—Construction Joints in Piers and Columns
- 5.10.12—Reinforcement for Hollow Rectangular Compression Members
  - 5.10.12.1—General
  - 5.10.12.2—Spacing of Reinforcement
  - 5.10.12.3—Ties
  - 5.10.12.4—Splices
  - 5.10.12.5—Hoops
- 5.11—DEVELOPMENT AND SPLICES OF REINFORCEMENT
  - 5.11.1—General
    - 5.11.1.1—Basic Requirements
    - 5.11.1.2—Flexural Reinforcement
      - 5.11.1.2.1—General
      - 5.11.1.2.2—Positive Moment Reinforcement
      - 5.11.1.2.3—Negative Moment Reinforcement
      - 5.11.1.2.4—Moment Resisting Joints
  - 5.11.2—Development of Reinforcement
    - 5.11.2.1—Deformed Bars and Deformed Wire in Tension
      - 5.11.2.1.1—Tension Development Length
      - 5.11.2.1.2—Modification Factors which Increase  $\ell_d$
      - 5.11.2.1.3—Modification Factors which Decrease  $\ell_d$
    - 5.11.2.2—Deformed Bars in Compression
      - 5.11.2.2.1—Compressive Development Length
      - 5.11.2.2.2—Modification Factors
    - 5.11.2.3—Bundled Bars
    - 5.11.2.4—Standard Hooks in Tension
      - 5.11.2.4.1—Basic Hook Development Length
      - 5.11.2.4.2—Modification Factors
      - 5.11.2.4.3—Hooked-Bar Tie Requirements
    - 5.11.2.5—Welded Wire Fabric
      - 5.11.2.5.1—Deformed Wire Fabric
      - 5.11.2.5.2—Plain Wire Fabric
    - 5.11.2.6—Shear Reinforcement
      - 5.11.2.6.1—General
      - 5.11.2.6.2—Anchorage of Deformed Reinforcement
      - 5.11.2.6.3—Anchorage of Wire Fabric Reinforcement
      - 5.11.2.6.4—Closed Stirrups
  - 5.11.3—Development by Mechanical Anchorages
  - 5.11.4—Development of Prestressing Strand
    - 5.11.4.1—General
    - 5.11.4.2—Bonded Strand
    - 5.11.4.3—Partially Debonded Strands
  - 5.11.5—Splices of Bar Reinforcement
    - 5.11.5.1—Detailing
    - 5.11.5.2—General Requirements
      - 5.11.5.2.1—Lap Splices
      - 5.11.5.2.2—Mechanical Connections
      - 5.11.5.2.3—Welded Splices
    - 5.11.5.3—Splices of Reinforcement in Tension
      - 5.11.5.3.1—Lap Splices in Tension

- 5.11.5.3.2—Mechanical Connections or Welded Splices in Tension
- 5.11.5.4—Splices in Tension Tie Members
- 5.11.5.5—Splices of Bars in Compression
  - 5.11.5.5.1—Lap Splices in Compression
  - 5.11.5.5.2—Mechanical Connections or Welded Splices in Compression
  - 5.11.5.5.3—End-Bearing Splices
- 5.11.6—Splices of Welded Wire Fabric
  - 5.11.6.1—Splices of Welded Deformed Wire Fabric in Tension
  - 5.11.6.2—Splices of Welded Smooth Wire Fabric in Tension
- 5.12—DURABILITY
  - 5.12.1—General
  - 5.12.2—Alkali-Silica Reactive Aggregates
  - 5.12.3—Concrete Cover
  - 5.12.4—Protective Coatings
  - 5.12.5—Protection for Prestressing Tendons
- 5.13—SPECIFIC MEMBERS
  - 5.13.1—Deck Slabs
  - 5.13.2—Diaphragms, Deep Beams, Brackets, Corbels, and Beam Ledges
    - 5.13.2.1—General
    - 5.13.2.2—Diaphragms
    - 5.13.2.3—Detailing Requirements for Deep Beams
    - 5.13.2.4—Brackets and Corbels
      - 5.13.2.4.1—General
      - 5.13.2.4.2—Alternative to Strut-and-Tie Model
    - 5.13.2.5—Beam Ledges
      - 5.13.2.5.1—General
      - 5.13.2.5.2—Design for Shear
      - 5.13.2.5.3—Design for Flexure and Horizontal Force
      - 5.13.2.5.4—Design for Punching Shear
      - 5.13.2.5.5—Design of Hanger Reinforcement
      - 5.13.2.5.6—Design for Bearing
  - 5.13.3—Footings
    - 5.13.3.1—General
    - 5.13.3.2—Loads and Reactions
    - 5.13.3.3—Resistance Factors
    - 5.13.3.4—Moment in Footings
    - 5.13.3.5—Distribution of Moment Reinforcement
    - 5.13.3.6—Shear in Slabs and Footings
      - 5.13.3.6.1—Critical Sections for Shear
      - 5.13.3.6.2—One-Way Action
      - 5.13.3.6.3—Two-Way Action
    - 5.13.3.7—Development of Reinforcement
    - 5.13.3.8—Transfer of Force at Base of Column
  - 5.13.4—Concrete Piles
    - 5.13.4.1—General
    - 5.13.4.2—Splices
    - 5.13.4.3—Precast Reinforced Piles
      - 5.13.4.3.1—Pile Dimensions
      - 5.13.4.3.2—Reinforcing Steel
    - 5.13.4.4—Precast Prestressed Piles
      - 5.13.4.4.1—Pile Dimensions
      - 5.13.4.4.2—Concrete Quality
      - 5.13.4.4.3—Reinforcement
    - 5.13.4.5—Cast-in-Place Piles
      - 5.13.4.5.1—Pile Dimensions
      - 5.13.4.5.2—Reinforcing Steel
    - 5.13.4.6—Seismic Requirements
      - 5.13.4.6.1—Zone 1
      - 5.13.4.6.2—Zone 2
        - 5.13.4.6.2a—General

- 5.13.4.6.2b—Cast-in-Place Piles
- 5.13.4.6.2c—Precast Reinforced Piles
- 5.13.4.6.2d—Precast Prestressed Piles
- 5.13.4.6.3—Zones 3 and 4
  - 5.13.4.6.3a—General
  - 5.13.4.6.3b—Confinement Length
  - 5.13.4.6.3c—Volumetric Ratio for Confinement
  - 5.13.4.6.3d—Cast-in-Place Piles
  - 5.13.4.6.3e—Precast Piles
- 5.14—PROVISIONS FOR STRUCTURE TYPES
  - 5.14.1—Beams and Girders
    - 5.14.1.1—General
    - 5.14.1.2—Precast Beams
      - 5.14.1.2.1—Preservice Conditions
      - 5.14.1.2.2—Extreme Dimensions
      - 5.14.1.2.3—Lifting Devices
      - 5.14.1.2.4—Detail Design
      - 5.14.1.2.5—Concrete Strength
    - 5.14.1.3—Spliced Precast Girders
      - 5.14.1.3.1—General
      - 5.14.1.3.2—Joints between Segments
        - 5.14.1.3.2a—General
        - 5.14.1.3.2b—Details of Closure Joints
        - 5.14.1.3.2c—Details of Match-Cast Joints
        - 5.14.1.3.2d—Joint Design
      - 5.14.1.3.3—Girder Segment Design
      - 5.14.1.3.4—Post-Tensioning
    - 5.14.1.4—Bridges Composed of Simple Span Precast Girders Made Continuous
      - 5.14.1.4.1—General
      - 5.14.1.4.2—Restraint Moments
      - 5.14.1.4.3—Material Properties
      - 5.14.1.4.4—Age of Girder When Continuity Is Established
      - 5.14.1.4.5—Degree of Continuity at Various Limit States
      - 5.14.1.4.6—Service Limit State
      - 5.14.1.4.7—Strength Limit State
      - 5.14.1.4.8—Negative Moment Connections
      - 5.14.1.4.9—Positive Moment Connections
        - 5.14.1.4.9a—General
        - 5.14.1.4.9b—Positive Moment Connection Using Mild Reinforcement
        - 5.14.1.4.9c—Positive Moment Connection Using Prestressing Strand
        - 5.14.1.4.9d—Details of Positive Moment Connection
      - 5.14.1.4.10—Continuity Diaphragms
    - 5.14.1.5—Cast-in-Place Girders and Box and T-Beams
      - 5.14.1.5.1—Flange and Web Thickness
        - 5.14.1.5.1a—Top Flange
        - 5.14.1.5.1b—Bottom Flange
        - 5.14.1.5.1c—Web
      - 5.14.1.5.2—Reinforcement
        - 5.14.1.5.2a—Deck Slab Reinforcement Cast-in-Place in T-Beams and Box Girders
        - 5.14.1.5.2b—Bottom Slab Reinforcement in Cast-in-Place Box Girders
  - 5.14.2—Segmental Construction
    - 5.14.2.1—General
    - 5.14.2.2—Analysis of Segmental Bridges
      - 5.14.2.2.1—General
      - 5.14.2.2.2—Construction Analysis
      - 5.14.2.2.3—Analysis of the Final Structural System
    - 5.14.2.3—Design
      - 5.14.2.3.1—Loads
      - 5.14.2.3.2—Construction Loads
      - 5.14.2.3.3—Construction Load Combinations at the Service Limit State

- 5.14.2.3.4—Construction Load Combinations at Strength Limit States
  - 5.14.2.3.4a—Superstructures
  - 5.14.2.3.4b—Substructures
- 5.14.2.3.5—Thermal Effects During Construction
- 5.14.2.3.6—Creep and Shrinkage
- 5.14.2.3.7—Prestress Losses
- 5.14.2.3.8—Provisional Post-Tensioning Ducts and Anchorages
  - 5.14.2.3.8a—General
  - 5.14.2.3.8b—Bridges with Internal Ducts
  - 5.14.2.3.8c—Provision for Future Dead Load or Deflection Adjustment
- 5.14.2.3.9—Plan Presentation
- 5.14.2.3.10—Box Girder Cross-Section Dimensions and Details
  - 5.14.2.3.10a—Minimum Flange Thickness
  - 5.14.2.3.10b—Minimum Web Thickness
  - 5.14.2.3.10c—Length of Top Flange Cantilever
  - 5.14.2.3.10d—Overall Cross-Section Dimensions
  - 5.14.2.3.10e—Overlays
- 5.14.2.3.11—Seismic Design
- 5.14.2.4—Types of Segmental Bridges
  - 5.14.2.4.1—General
  - 5.14.2.4.2—Details for Precast Construction
  - 5.14.2.4.3—Details for Cast-in-Place Construction
  - 5.14.2.4.4—Cantilever Construction
  - 5.14.2.4.5—Span-by-Span Construction
  - 5.14.2.4.6—Incrementally Launched Construction
    - 5.14.2.4.6a—General
    - 5.14.2.4.6b—Force Effects Due to Construction Tolerances
    - 5.14.2.4.6c—Design Details
    - 5.14.2.4.6d—Design of Construction Equipment
- 5.14.2.5—Use of Alternative Construction Methods
- 5.14.2.6—Segmental Bridge Substructures
  - 5.14.2.6.1—General
  - 5.14.2.6.2—Construction Load Combinations
  - 5.14.2.6.3—Longitudinal Reinforcement of Hollow, Rectangular Precast Segmental Piers
- 5.14.3—Arches
  - 5.14.3.1—General
  - 5.14.3.2—Arch Ribs
- 5.14.4—Slab Superstructures
  - 5.14.4.1—Cast-in-Place Solid Slab Superstructures
  - 5.14.4.2—Cast-in-Place Voids Slab Superstructures
    - 5.14.4.2.1—Cross-Section Dimensions
    - 5.14.4.2.2—Minimum Number of Bearings
    - 5.14.4.2.3—Solid End Sections
    - 5.14.4.2.4—General Design Requirements
    - 5.14.4.2.5—Compressive Zones in Negative Moment Area
    - 5.14.4.2.6—Drainage of Voids
  - 5.14.4.3—Precast Deck Bridges
    - 5.14.4.3.1—General
    - 5.14.4.3.2—Shear Transfer Joints
    - 5.14.4.3.3—Shear-Flexure Transfer Joints
      - 5.14.4.3.3a—General
      - 5.14.4.3.3b—Design
      - 5.14.4.3.3c—Post-Tensioning
      - 5.14.4.3.3d—Longitudinal Construction Joints
      - 5.14.4.3.3e—Cast-in-Place Closure Joint
      - 5.14.4.3.3f—Structural Overlay
- 5.14.5—Additional Provisions for Culverts
  - 5.14.5.1—General
  - 5.14.5.2—Design for Flexure
  - 5.14.5.3—Design for Shear in Slabs of Box Culverts

## 5.15—REFERENCES

### APPENDIX A5—BASIC STEPS FOR CONCRETE BRIDGES

#### A5.1—GENERAL

#### A5.2—GENERAL CONSIDERATIONS

#### A5.3—BEAM AND GIRDER SUPERSTRUCTURE DESIGN

#### A5.4—SLAB BRIDGES

#### A5.5—SUBSTRUCTURE DESIGN

### APPENDIX B5—GENERAL PROCEDURE FOR SHEAR DESIGN WITH TABLES

#### B5.1—BACKGROUND

#### B5.2—SECTIONAL DESIGN MODEL—GENERAL PROCEDURE

### APPENDIX C5—UPPER LIMITS FOR ARTICLES AFFECTED BY CONCRETE COMPRESSIVE STRENGTH

## SECTION 6: STEEL STRUCTURES

### 6.1—SCOPE

### 6.2—DEFINITIONS

### 6.3—NOTATION

### 6.4—MATERIALS

#### 6.4.1—Structural Steels

#### 6.4.2—Pins, Rollers, and Rockers

#### 6.4.3—Bolts, Nuts, and Washers

##### 6.4.3.1—Bolts

##### 6.4.3.2—Nuts

##### 6.4.3.2.1—Nuts Used with Structural Fasteners

##### 6.4.3.2.2—Nuts Used with Anchor Bolts

##### 6.4.3.3—Washers

##### 6.4.3.4—Alternative Fasteners

##### 6.4.3.5—Load Indicator Devices

#### 6.4.4—Stud Shear Connectors

#### 6.4.5—Weld Metal

#### 6.4.6—Cast Metal

##### 6.4.6.1—Cast Steel and Ductile Iron

##### 6.4.6.2—Malleable Castings

##### 6.4.6.3—Cast Iron

#### 6.4.7—Stainless Steel

#### 6.4.8—Cables

##### 6.4.8.1—Bright Wire

##### 6.4.8.2—Galvanized Wire

##### 6.4.8.3—Epoxy-Coated Wire

##### 6.4.8.4—Bridge Strand

### 6.5—LIMIT STATES

#### 6.5.1—General

#### 6.5.2—Service Limit State

#### 6.5.3—Fatigue and Fracture Limit State

#### 6.5.4—Strength Limit State

##### 6.5.4.1—General

##### 6.5.4.2—Resistance Factors

#### 6.5.5—Extreme Event Limit State

### 6.6—FATIGUE AND FRACTURE CONSIDERATIONS

#### 6.6.1—Fatigue

##### 6.6.1.1—General

##### 6.6.1.2—Load-Induced Fatigue

##### 6.6.1.2.1—Application

##### 6.6.1.2.2—Design Criteria

##### 6.6.1.2.3—Detail Categories

##### 6.6.1.2.4—Detailing to Reduce Constraint

##### 6.6.1.2.5—Fatigue Resistance

- 6.6.1.3—Distortion-Induced Fatigue
  - 6.6.1.3.1—Transverse Connection Plates
  - 6.6.1.3.2—Lateral Connection Plates
  - 6.6.1.3.3—Orthotropic Decks
- 6.6.2—Fracture
- 6.7—GENERAL DIMENSION AND DETAIL REQUIREMENTS
  - 6.7.1—Effective Length of Span
  - 6.7.2—Dead Load Camber
  - 6.7.3—Minimum Thickness of Steel
  - 6.7.4—Diaphragms and Cross-Frames
    - 6.7.4.1—General
    - 6.7.4.2—I-Section Members
    - 6.7.4.3—Box Section Members
    - 6.7.4.4—Trusses and Arches
  - 6.7.5—Lateral Bracing
    - 6.7.5.1—General
    - 6.7.5.2—I-Section Members
    - 6.7.5.3—Tub Section Members
    - 6.7.5.4—Trusses
  - 6.7.6—Pins
    - 6.7.6.1—Location
    - 6.7.6.2—Resistance
      - 6.7.6.2.1—Combined Flexure and Shear
      - 6.7.6.2.2—Bearing
    - 6.7.6.3—Minimum Size Pin for Eyebars
    - 6.7.6.4—Pins and Pin Nuts
  - 6.7.7—Heat-Curved Rolled Beams and Welded Plate Girders
    - 6.7.7.1—Scope
    - 6.7.7.2—Minimum Radius of Curvature
    - 6.7.7.3—Camber
- 6.8—TENSION MEMBERS
  - 6.8.1—General
  - 6.8.2—Tensile Resistance
    - 6.8.2.1—General
    - 6.8.2.2—Reduction Factor,  $U$
    - 6.8.2.3—Combined Tension and Flexure
  - 6.8.3—Net Area
  - 6.8.4—Limiting Slenderness Ratio
  - 6.8.5—Builtup Members
    - 6.8.5.1—General
    - 6.8.5.2—Perforated Plates
  - 6.8.6—Eyebars
    - 6.8.6.1—Factored Resistance
    - 6.8.6.2—Proportions
    - 6.8.6.3—Packing
  - 6.8.7—Pin-Connected Plates
    - 6.8.7.1—General
    - 6.8.7.2—Pin Plates
    - 6.8.7.3—Proportions
    - 6.8.7.4—Packing
- 6.9—COMPRESSION MEMBERS
  - 6.9.1—General
  - 6.9.2—Compressive Resistance
    - 6.9.2.1—Axial Compression
    - 6.9.2.2—Combined Axial Compression and Flexure
  - 6.9.3—Limiting Slenderness Ratio
  - 6.9.4—Noncomposite Members
    - 6.9.4.1—Nominal Compressive Resistance
      - 6.9.4.1.1—General
      - 6.9.4.1.2—Elastic Flexural Buckling Resistance

- 6.9.4.1.3—Elastic Torsional Buckling and Flexural-Torsional Buckling Resistance
- 6.9.4.2—Nonslender and Slender Member Elements
  - 6.9.4.2.1—Nonslender Member Elements
- 6.9.4.3—Builtup Members
  - 6.9.4.3.1—General
  - 6.9.4.3.2—Perforated Plates
- 6.9.5—Composite Members
  - 6.9.5.1—Nominal Compressive Resistance
  - 6.9.5.2—Limitations
    - 6.9.5.2.1—General
    - 6.9.5.2.2—Concrete-Filled Tubes
    - 6.9.5.2.3—Concrete-Encased Shapes
- 6.10—I-SECTION FLEXURAL MEMBERS
  - 6.10.1—General
    - 6.10.1.1—Composite Sections
      - 6.10.1.1.1—Stresses
        - 6.10.1.1.1a—Sequence of Loading
        - 6.10.1.1.1b—Stresses for Sections in Positive Flexure
        - 6.10.1.1.1c—Stresses for Sections in Negative Flexure
        - 6.10.1.1.1d—Concrete Deck Stresses
        - 6.10.1.1.1e—Effective Width of Concrete Deck
    - 6.10.1.2—Noncomposite Sections
    - 6.10.1.3—Hybrid Sections
    - 6.10.1.4—Variable Web Depth Members
    - 6.10.1.5—Stiffness
    - 6.10.1.6—Flange Stresses and Member Bending Moments
    - 6.10.1.7—Minimum Negative Flexure Concrete Deck Reinforcement
    - 6.10.1.8—Net Section Fracture
    - 6.10.1.9—Web Bend-Buckling Resistance
      - 6.10.1.9.1—Webs without Longitudinal Stiffeners
      - 6.10.1.9.2—Webs with Longitudinal Stiffeners
    - 6.10.1.10—Flange-Strength Reduction Factors
      - 6.10.1.10.1—Hybrid Factor,  $R_h$
      - 6.10.1.10.2—Web Load-Shedding Factor,  $R_b$
  - 6.10.2—Cross-Section Proportion Limits
    - 6.10.2.1—Web Proportions
      - 6.10.2.1.1—Webs without Longitudinal Stiffeners
      - 6.10.2.1.2—Webs with Longitudinal Stiffeners
    - 6.10.2.2 Flange Proportions
  - 6.10.3—Constructibility
    - 6.10.3.1—General
    - 6.10.3.2—Flexure
      - 6.10.3.2.1—Discretely Braced Flanges in Compression
      - 6.10.3.2.2—Discretely Braced Flanges in Tension
      - 6.10.3.2.3 Continuously Braced Flanges in Tension or Compression
      - 6.10.3.2.4 Concrete Deck
    - 6.10.3.3—Shear
    - 6.10.3.4—Deck Placement
    - 6.10.3.5—Dead Load Deflections
  - 6.10.4—Service Limit State
    - 6.10.4.1—Elastic Deformations
    - 6.10.4.2—Permanent Deformations
      - 6.10.4.2.1—General
      - 6.10.4.2.2—Flexure
  - 6.10.5—Fatigue and Fracture Limit State
    - 6.10.5.1—Fatigue
    - 6.10.5.2—Fracture
    - 6.10.5.3—Special Fatigue Requirement for Webs
  - 6.10.6—Strength Limit State
    - 6.10.6.1—General

- 6.10.6.2—Flexure
  - 6.10.6.2.1—General
  - 6.10.6.2.2—Composite Sections in Positive Flexure
  - 6.10.6.2.3—Composite Sections in Negative Flexure and Noncomposite Sections
- 6.10.6.3—Shear
- 6.10.6.4—Shear Connectors
- 6.10.7—Flexural Resistance—Composite Sections in Positive Flexure
  - 6.10.7.1—Compact Sections
    - 6.10.7.1.1—General
    - 6.10.7.1.2—Nominal Flexural Resistance
  - 6.10.7.2—Noncompact Sections
    - 6.10.7.2.1—General
    - 6.10.7.2.2—Nominal Flexural Resistance
  - 6.10.7.3—Ductility Requirement
- 6.10.8—Flexural Resistance—Composite Sections in Negative Flexure and Noncomposite Sections
  - 6.10.8.1—General
    - 6.10.8.1.1 Discretely Braced Flanges in Compression
    - 6.10.8.1.2—Discretely Braced Flanges in Tension
    - 6.10.8.1.3—Continuously Braced Flanges in Tension or Compression
  - 6.10.8.2 Compression-Flange Flexural Resistance
    - 6.10.8.2.1—General
    - 6.10.8.2.2—Local Buckling Resistance
    - 6.10.8.2.3—Lateral Torsional Buckling Resistance
  - 6.10.8.3—Tension-Flange Flexural Resistance
- 6.10.9—Shear Resistance
  - 6.10.9.1 General
  - 6.10.9.2 Nominal Resistance of Unstiffened Webs
  - 6.10.9.3 Nominal Resistance of Stiffened Webs
    - 6.10.9.3.1 General
    - 6.10.9.3.2—Interior Panels
    - 6.10.9.3.3—End Panels
- 6.10.10 Shear Connectors
  - 6.10.10.1—General
    - 6.10.10.1.1 Types
    - 6.10.10.1.2—Pitch
    - 6.10.10.1.3—Transverse Spacing
    - 6.10.10.1.4—Cover and Penetration
  - 6.10.10.2—Fatigue Resistance
  - 6.10.10.3—Special Requirements for Points of Permanent Load Contraflexure
  - 6.10.10.4—Strength Limit State
    - 6.10.10.4.1—General
    - 6.10.10.4.2—Nominal Shear Force
    - 6.10.10.4.3—Nominal Shear Resistance
- 6.10.11 Stiffeners
  - 6.10.11.1—Transverse Stiffeners
    - 6.10.11.1.1—General
    - 6.10.11.1.2—Projecting Width
    - 6.10.11.1.3—Moment of Inertia
  - 6.10.11.2—Bearing Stiffeners
    - 6.10.11.2.1—General
    - 6.10.11.2.2—Projecting Width
    - 6.10.11.2.3—Bearing Resistance
    - 6.10.11.2.4—Axial Resistance of Bearing Stiffeners
      - 6.10.11.2.4a—General
      - 6.10.11.2.4b—Effective Section
  - 6.10.11.3—Longitudinal Stiffeners
    - 6.10.11.3.1—General
    - 6.10.11.3.2—Projecting Width
    - 6.10.11.3.3—Moment of Inertia and Radius of Gyration

- 6.10.12—Cover Plates
  - 6.10.12.1—General
  - 6.10.12.2—End Requirements
    - 6.10.12.2.1—General
    - 6.10.12.2.2—Welded Ends
    - 6.10.12.2.3—Bolted Ends
- 6.11—BOX-SECTION FLEXURAL MEMBERS
  - 6.11.1—General
    - 6.11.1.1—Stress Determinations
    - 6.11.1.2—Bearings
    - 6.11.1.3—Flange-to-Web Connections
    - 6.11.1.4—Access and Drainage
  - 6.11.2—Cross-Section Proportion Limits
    - 6.11.2.1—Web Proportions
      - 6.11.2.1.1—General
      - 6.11.2.1.2—Webs without Longitudinal Stiffeners
      - 6.11.2.1.3—Webs with Longitudinal Stiffeners
    - 6.11.2.2—Flange Proportions
    - 6.11.2.3—Special Restrictions on Use of Live Load Distribution Factor for Multiple Box Sections
  - 6.11.3—Constructibility
    - 6.11.3.1—General
    - 6.11.3.2—Flexure
    - 6.11.3.3—Shear
  - 6.11.4—Service Limit State
  - 6.11.5—Fatigue and Fracture Limit State
  - 6.11.6—Strength Limit State
    - 6.11.6.1—General
    - 6.11.6.2—Flexure
      - 6.11.6.2.1—General
      - 6.11.6.2.2—Sections in Positive Flexure
      - 6.11.6.2.3—Sections in Negative Flexure
    - 6.11.6.3—Shear
    - 6.11.6.4—Shear Connectors
  - 6.11.7—Flexural Resistance—Sections in Positive Flexure
    - 6.11.7.1—Compact Sections
      - 6.11.7.1.1—General
      - 6.11.7.1.2—Nominal Flexural Resistance
    - 6.11.7.2—Noncompact Sections
      - 6.11.7.2.1—General
      - 6.11.7.2.2—Nominal Flexural Resistance
  - 6.11.8—Flexural Resistance—Sections in Negative Flexure
    - 6.11.8.1—General
      - 6.11.8.1.1—Box Flanges in Compression
      - 6.11.8.1.2—Continuously Braced Flanges in Tension
    - 6.11.8.2—Flexural Resistance of Box Flanges in Compression
      - 6.11.8.2.1—General
      - 6.11.8.2.2—Unstiffened Flanges
      - 6.11.8.2.3—Longitudinally Stiffened Flanges
    - 6.11.8.3—Tension-Flange Flexural Resistance
  - 6.11.9—Shear Resistance
  - 6.11.10—Shear Connectors
  - 6.11.11—Stiffeners
    - 6.11.11.1—Web Stiffeners
    - 6.11.11.2—Longitudinal Compression-Flange Stiffeners
- 6.12—MISCELLANEOUS FLEXURAL MEMBERS
  - 6.12.1—General
    - 6.12.1.1—Scope
    - 6.12.1.2—Strength Limit State
      - 6.12.1.2.1—Flexure
      - 6.12.1.2.2—Combined Flexure and Axial Load

- 6.12.1.2.3—Shear
  - 6.12.1.2.3a—General
  - 6.12.1.2.3b—Square and Rectangular HSS
  - 6.12.1.2.3c—Circular Tubes
- 6.12.2—Nominal Flexural Resistance
  - 6.12.2.1—General
  - 6.12.2.2—Noncomposite Members
    - 6.12.2.2.1—I- and H-Shaped Members
    - 6.12.2.2.2—Box-Shaped Members
    - 6.12.2.2.3—Circular Tubes
    - 6.12.2.2.4—Tees and Double Angles
    - 6.12.2.2.5—Channels
    - 6.12.2.2.6—Single Angles
    - 6.12.2.2.7—Rectangular Bars and Solid Rounds
  - 6.12.2.3—Composite Members
    - 6.12.2.3.1—Concrete-Encased Shapes
    - 6.12.2.3.2—Concrete-Filled Tubes
- 6.12.3—Nominal Shear Resistance of Composite Members
  - 6.12.3.1—Concrete-Encased Shapes
  - 6.12.3.2—Concrete-Filled Tubes
    - 6.12.3.2.1—Rectangular Tubes
    - 6.12.3.2.2—Circular Tubes
- 6.13—CONNECTIONS AND SPLICES
  - 6.13.1—General
  - 6.13.2—Bolted Connections
    - 6.13.2.1—General
      - 6.13.2.1.1—Slip-Critical Connections
      - 6.13.2.1.2—Bearing-Type Connections
    - 6.13.2.2—Factored Resistance
    - 6.13.2.3—Bolts, Nuts, and Washers
      - 6.13.2.3.1—Bolts and Nuts
      - 6.13.2.3.2—Washers
    - 6.13.2.4—Holes
      - 6.13.2.4.1—Type
        - 6.13.2.4.1a—General
        - 6.13.2.4.1b—Oversize Holes
        - 6.13.2.4.1c—Short-Slotted Holes
        - 6.13.2.4.1d—Long-Slotted Holes
      - 6.13.2.4.2—Size
    - 6.13.2.5—Size of Bolts
    - 6.13.2.6—Spacing of Bolts
      - 6.13.2.6.1—Minimum Spacing and Clear Distance
      - 6.13.2.6.2—Maximum Spacing for Sealing Bolts
      - 6.13.2.6.3—Maximum Pitch for Stitch Bolts
      - 6.13.2.6.4—Maximum Pitch for Stitch Bolts at the End of Compression Members
      - 6.13.2.6.5—End Distance
      - 6.13.2.6.6—Edge Distances
    - 6.13.2.7—Shear Resistance
    - 6.13.2.8—Slip Resistance
    - 6.13.2.9—Bearing Resistance at Bolt Holes
    - 6.13.2.10—Tensile Resistance
      - 6.13.2.10.1—General
      - 6.13.2.10.2—Nominal Tensile Resistance
      - 6.13.2.10.3—Fatigue Resistance
      - 6.13.2.10.4—Prying Action
    - 6.13.2.11—Combined Tension and Shear
    - 6.13.2.12—Shear Resistance of Anchor Bolts
  - 6.13.3—Welded Connections
    - 6.13.3.1—General
    - 6.13.3.2—Factored Resistance

- 6.13.3.2.1—General
- 6.13.3.2.2—Complete Penetration Groove-Welded Connections
  - 6.13.3.2.2a—Tension and Compression
  - 6.13.3.2.2b—Shear
- 6.13.3.2.3—Partial Penetration Groove-Welded Connections
  - 6.13.3.2.3a—Tension or Compression
  - 6.13.3.2.3b—Shear
- 6.13.3.2.4—Fillet-Welded Connections
  - 6.13.3.2.4a—Tension and Compression
  - 6.13.3.2.4b—Shear
- 6.13.3.3—Effective Area
- 6.13.3.4—Size of Fillet Welds
- 6.13.3.5—Minimum Effective Length of Fillet Welds
- 6.13.3.6—Fillet Weld End Returns
- 6.13.3.7—Seal Welds
- 6.13.4—Block Shear Rupture Resistance
- 6.13.5—Connection Elements
  - 6.13.5.1—General
  - 6.13.5.2—Tension
  - 6.13.5.3—Shear
- 6.13.6—Splices
  - 6.13.6.1—Bolted Splices
    - 6.13.6.1.1—General
    - 6.13.6.1.2—Tension Members
    - 6.13.6.1.3—Compression Members
    - 6.13.6.1.4—Flexural Members
      - 6.13.6.1.4a—General
      - 6.13.6.1.4b—Web Splices
      - 6.13.6.1.4c—Flange Splices
    - 6.13.6.1.5—Fillers
  - 6.13.6.2—Welded Splices
- 6.13.7—Rigid Frame Connections
  - 6.13.7.1—General
  - 6.13.7.2—Webs
- 6.14—PROVISIONS FOR STRUCTURE TYPES
  - 6.14.1—Through-Girder Spans
  - 6.14.2—Trusses
    - 6.14.2.1—General
    - 6.14.2.2—Truss Members
    - 6.14.2.3—Secondary Stresses
    - 6.14.2.4—Diaphragms
    - 6.14.2.5—Camber
    - 6.14.2.6—Working Lines and Gravity Axes
    - 6.14.2.7—Portal and Sway Bracing
      - 6.14.2.7.1—General
      - 6.14.2.7.2—Through-Truss Spans
      - 6.14.2.7.3—Deck Truss Spans
    - 6.14.2.8—Gusset Plates
    - 6.14.2.9—Half Through-Trusses
    - 6.14.2.10—Factored Resistance
  - 6.14.3—Orthotropic Deck Superstructures
    - 6.14.3.1—General
    - 6.14.3.2—Effective Width of Deck
    - 6.14.3.3—Superposition of Global and Local Effects
      - 6.14.3.3.1—General
      - 6.14.3.3.2—Decks in Global Tension
      - 6.14.3.3.3—Decks in Global Compression
    - 6.14.3.4—Transverse Flexure
    - 6.14.3.5—Diaphragms
  - 6.14.4—Solid Web Arches

- 6.14.4.1—Moment Amplification for Deflection
- 6.14.4.2—Web Slenderness
- 6.14.4.3—Flange Stability
- 6.15—PILES
  - 6.15.1—General
  - 6.15.2—Structural Resistance
  - 6.15.3—Compressive Resistance
    - 6.15.3.1—Axial Compression
    - 6.15.3.2—Combined Axial Compression and Flexure
    - 6.15.3.3—Buckling
  - 6.15.4—Maximum Permissible Driving Stresses
- 6.16—REFERENCES

## APPENDIX A6—FLEXURAL RESISTANCE OF STRAIGHT COMPOSITE I-SECTIONS IN NEGATIVE FLEXURE AND STRAIGHT NONCOMPOSITE I-SECTIONS—WITH COMPACT OR NONCOMPACT WEBS

- A6.1—GENERAL
  - A6.1.1 Sections with Discretely Braced Compression Flanges
  - A6.1.2 Sections with Discretely Braced Tension Flanges
  - A6.1.3 Sections with Continuously Braced Compression Flanges
  - A6.1.4 Sections with Continuously Braced Tension Flanges
- A6.2—WEB PLASTIFICATION FACTORS
  - A6.2.1—Compact Web Sections
  - A6.2.2—Noncompact Web Sections
- A6.3—FLEXURAL RESISTANCE BASED ON THE COMPRESSION FLANGE
  - A6.3.1—General
  - A6.3.2—Local Buckling Resistance
  - A6.3.3—Lateral Torsional Buckling Resistance
- A6.4—FLEXURAL RESISTANCE BASED ON TENSION FLANGE YIELDING

## APPENDIX B6—MOMENT REDISTRIBUTION FROM INTERIOR-PIER I-SECTIONS IN STRAIGHT CONTINUOUS-SPAN BRIDGES

- B6.1—GENERAL
- B6.2—SCOPE
  - B6.2.1—Web Proportions
  - B6.2.2—Compression Flange Proportions
  - B6.2.3—Section Transitions
  - B6.2.4—Compression Flange Bracing
  - B6.2.5—Shear
  - B6.2.6—Bearing Stiffeners
- B6.3—SERVICE LIMIT STATE
  - B6.3.1—General
  - B6.3.2—Flexure
    - B6.3.2.1—Adjacent to Interior-Pier Sections
    - B6.3.2.2—At All Other Locations
  - B6.3.3—Redistribution Moments
    - B6.3.3.1—At Interior-Pier Sections
    - B6.3.3.2—At All Other Locations
- B6.4—STRENGTH LIMIT STATE
  - B6.4.1—Flexural Resistance
    - B6.4.1.1—Adjacent to Interior-Pier Sections
    - B6.4.1.2—At All Other Locations
  - B6.4.2—Redistribution Moments
    - B6.4.2.1—At Interior-Pier Sections
    - B6.4.2.2—At All Other Sections
- B6.5—EFFECTIVE PLASTIC MOMENT
  - B6.5.1—Interior-Pier Sections with Enhanced Moment-Rotation Characteristics
  - B6.5.2—All Other Interior-Pier Sections
- B6.6—REFINED METHOD
  - B6.6.1—General
  - B6.6.2—Nominal Moment-Rotation Curves

## APPENDIX C6—BASIC STEPS FOR STEEL BRIDGE SUPERSTRUCTURES

### C6.1—GENERAL

### C6.2—GENERAL CONSIDERATIONS

### C6.3—SUPERSTRUCTURE DESIGN

### C6.4—FLOWCHARTS FOR FLEXURAL DESIGN OF I-SECTIONS

C6.4.1—Flowchart for LRFD Article 6.10.3

C6.4.2—Flowchart for LRFD Article 6.10.4

C6.4.3—Flowchart for LRFD Article 6.10.5

C6.4.4—Flowchart for LRFD Article 6.10.6

C6.4.5—Flowchart for LRFD Article 6.10.7

C6.4.6—Flowchart for LRFD Article 6.10.8

C6.4.7—Flowchart for Appendix A6

C6.4.8—Flowchart for Article D6.4.1

C6.4.9—Flowchart for Article D6.4.2

C6.4.10—Moment Gradient Modifier,  $C_b$  (Sample Cases)

## APPENDIX D6—FUNDAMENTAL CALCULATIONS FOR FLEXURAL MEMBERS

### D6.1—PLASTIC MOMENT

### D6.2—YIELD MOMENT

D6.2.1—Noncomposite Sections

D6.2.2—Composite Sections in Positive Flexure

D6.2.3 Composite Sections in Negative Flexure

D6.2.4 Sections with Cover Plates

### D6.3—DEPTH OF THE WEB IN COMPRESSION

D6.3.1—In the Elastic Range ( $D_c$ )

D6.3.2—At Plastic Moment ( $D_{cp}$ )

### D6.4—LATERAL TORSIONAL BUCKLING EQUATIONS FOR $C_B > 1.0$ , WITH EMPHASIS ON UNBRACED LENGTH REQUIREMENTS FOR DEVELOPMENT OF THE MAXIMUM FLEXURAL RESISTANCE

D6.4.1—By the Provisions of Article 6.10.8.2.3

D6.4.2—By the Provisions of Article A6.3.3

### D6.5—CONCENTRATED LOADS APPLIED TO WEBS WITHOUT BEARING STIFFENERS

D6.5.1—General

D6.5.2—Web Local Yielding

D6.5.3—Web Crippling

## SECTION 7: ALUMINUM STRUCTURES

### 7.1—SCOPE

### 7.2—DEFINITIONS

### 7.3—NOTATION

### 7.4—MATERIALS

7.4.1—General

7.4.2—Aluminum Sheet, Plate, and Shapes

7.4.2.1—Extrusions and Mechanically Fastened Builtup Members

7.4.2.2—Welded Builtup Members

7.4.3—Material for Pins, Rollers, and Expansion Rockers

7.4.4—Fasteners—Rivets and Bolts

7.4.5—Weld Metal

7.4.6—Aluminum Castings

7.4.7—Aluminum Forgings

### 7.5—LIMIT STATES

7.5.1—Service Limit State

7.5.1.1—Appearance of Buckling

7.5.1.2—Effective Width for Calculation of Deflection of Thin Gage Sections

7.5.1.3—Web Crippling

7.5.1.4—Live Load Deflection

7.5.2—Fatigue and Fracture Limit State

7.5.3—Strength Limit State

- 7.5.4—Resistance Factors
- 7.6—FATIGUE AND FRACTURE CONSIDERATIONS
  - 7.6.1—Fatigue
    - 7.6.1.1—General
    - 7.6.1.2—Load-Induced Fatigue
      - 7.6.1.2.1—Application
      - 7.6.1.2.2—Design Criteria
      - 7.6.1.2.3—Detail Categories
      - 7.6.1.2.4—Fatigue Resistance
    - 7.6.1.3—Distortion-Induced Fatigue
      - 7.6.1.3.1—Transverse Connection Plates
      - 7.6.1.3.2—Lateral Connection Plates
  - 7.6.2—Fracture
- 7.7—DESIGN CONSIDERATIONS
  - 7.7.1—Dead Load Camber
  - 7.7.2—Welding Requirements
  - 7.7.3—Welding Procedures
  - 7.7.4—Nondestructive Testing
  - 7.7.5—Uplift and Slip of Deck Slabs
  - 7.7.6—Composite Sections
- 7.8—GENERAL DIMENSION AND DETAIL REQUIREMENTS
  - 7.8.1—Effective Length of Span
  - 7.8.2—Slenderness Ratios for Tension and Compression Members
  - 7.8.3—Minimum Thickness of Aluminum
  - 7.8.4—Diaphragms and Cross-Frames
  - 7.8.5—Lateral Bracing
    - 7.8.5.1 General
    - 7.8.5.2—Through-Spans
  - 7.8.6—Pins and Pin-Connected Elements
- 7.9—TENSION MEMBERS
  - 7.9.1—General
  - 7.9.2—Tensile Resistance
  - 7.9.3—Effective Area of Angle and T-Sections
  - 7.9.4—Net Area
- 7.10—COMPRESSION MEMBERS
  - 7.10.1—General
  - 7.10.2—Compressive Resistance of Columns
  - 7.10.3—Compressive Resistance of Components of Columns—Outstanding Flanges and Legs
  - 7.10.4—Compressive Resistance of Components of Columns, Gross Section—Flat Plates with Both Edges Supported
    - 7.10.4.1—General
    - 7.10.4.2—Effect of Local Buckling of Elements on Column Strength
  - 7.10.5—Compressive Resistance of Components of Columns, Gross Section—Curved Plates Supported on Both Edges, Walls of Round, or Oval Tubes
- 7.11—FLEXURAL MEMBERS
  - 7.11.1 Tensile Resistance of Flexural Member
    - 7.11.1.1 Net Section
    - 7.11.1.2—Tension in Extreme Fibers of Beams, Structural Shapes Bent about Strong Axis, Rectangular Tubes
    - 7.11.1.3—Tension in Extreme Fibers of Beams, Round, or Oval Tubes
    - 7.11.1.4—Tension in Extreme Fibers of Beams—Shapes Bent about Weak Axis, Rectangular Bars, Plates
  - 7.11.2—Compressive Resistance of Flexural Members
    - 7.11.2.1—Compression in Beams, Extreme Fiber, Gross Section, Single-Web Beams Bent about Strong Axis
    - 7.11.2.2—Compression in Beams, Extreme Fiber, Gross Section, Round or Oval Tubes
    - 7.11.2.3—Compression in Beams, Extreme Fiber, Gross Section, Solid Rectangular Beams
    - 7.11.2.4—Compression in Beams, Extreme Fiber, Gross Section, Rectangular Tubes, and Box Sections
  - 7.11.3—Compressive Resistance of Flexural Members Limited by Plate Slenderness
    - 7.11.3.1—General
    - 7.11.3.2—Compression in Components of Beams with Component under Uniform Compression, Gross Section, Outstanding Flanges
      - 7.11.3.2.1—General
      - 7.11.3.2.2—Effect of Local Buckling of Elements on Resistance

- 7.11.3.3—Compression in Components of Beams with Component under Uniform Compression, Gross Section, Flat Plates with Both Edges Supported
- 7.11.3.4—Compression in Components of Beams—Curved Sections
- 7.11.3.5—Compression in Components of Beams with Component under Bending in Own Plane, Gross Section, Flat Plates with Compression Edge Free, Tension Edge Supported
- 7.11.3.6—Webs of Beams, Gross Section, Flat Plates with Both Edges Supported
- 7.11.3.7—Webs of Beams with Longitudinal Stiffener, Both Edges Supported
- 7.11.4—Shear Resistance
  - 7.11.4.1—Shear—Unstiffened Flat Webs
  - 7.11.4.2—Shear in Webs—Stiffened Flat Webs
- 7.11.5—Design of Stiffeners
  - 7.11.5.1—Longitudinal Stiffeners for Webs
  - 7.11.5.2—Transverse Stiffeners for Shear in Webs
  - 7.11.5.3—Stiffeners For Outstanding Flanges
  - 7.11.5.4—Bearing Stiffeners
- 7.12—TORSION
  - 7.12.1—General
  - 7.12.2—Compression Members Subjected to Torsion
    - 7.12.2.1—Members With Double-Axis Symmetry
    - 7.12.2.2—Members With Single-Axis Symmetry
  - 7.12.3—St. Venant Torsion
    - 7.12.3.1—Open Section
    - 7.12.3.2—Box Section
  - 7.12.4—Warping Torsion
    - 7.12.4.1 Open Sections
    - 7.12.4.2—Box Section
- 7.13—COMBINED FORCE EFFECTS
  - 7.13.1—Combined Compression and Flexure
  - 7.13.2—Combined Shear, Compression, and Flexure
  - 7.13.3—Torsion and Shear in Tubes
  - 7.13.4—Combined Compression and Flexure—Webs
- 7.14—CONNECTIONS AND SPLICES
  - 7.14.1—General
  - 7.14.2—Bolted Connections
    - 7.14.2.1—Bolts and Nuts
    - 7.14.2.2—Holes
    - 7.14.2.3—Size of Fasteners
    - 7.14.2.4—Spacing of Fasteners
      - 7.14.2.4.1—Minimum Pitch and Clear Distance
      - 7.14.2.4.2—Maximum Pitch for Sealing Fasteners
      - 7.14.2.4.3—Maximum Pitch for Stitch Fasteners
      - 7.14.2.4.4—Stitch Fasteners at the End of—Compression Members
      - 7.14.2.4.5—End and Edge Distances
    - 7.14.2.5—Shear Resistance of Fasteners
    - 7.14.2.6—Slip-Critical Connections
    - 7.14.2.7—Bearing Resistance at Fastener Holes
      - 7.14.2.7.1—General
      - 7.14.2.7.2—Bearing Resistance at Rivet and Bolt Holes
      - 7.14.2.7.3—Bearing on Flat Surfaces and Pins
    - 7.14.2.8—Tension
  - 7.14.3—Block Shear or End Rupture
  - 7.14.4—Splices
    - 7.14.4.1—General
    - 7.14.4.2—Tension Members
    - 7.14.4.3—Compression Members
    - 7.14.4.4—Flexural Members
    - 7.14.4.5—Welding
- 7.15—PROVISIONS FOR STRUCTURE TYPES
  - 7.15.1—Floor System
  - 7.15.2—Lateral Bracing

- 7.15.3—Beam and Girder Framing
- 7.15.4—Trusses
  - 7.15.4.1—General
  - 7.15.4.2—Portal and Sway Bracing
- 7.15.5—Arches
- 7.16—REFERENCES

## SECTION 8: WOOD STRUCTURES

- 8.1—SCOPE
- 8.2—DEFINITIONS
- 8.3—NOTATION
- 8.4—MATERIALS
  - 8.4.1—Wood Products
    - 8.4.1.1—Sawn Lumber
      - 8.4.1.1.1—General
      - 8.4.1.1.2—Dimensions
      - 8.4.1.1.3—Moisture Content
      - 8.4.1.1.4—Reference Design Values
    - 8.4.1.2—Structural Glued Laminated Timber (Glulam)
      - 8.4.1.2.1—General
      - 8.4.1.2.2—Dimensions
      - 8.4.1.2.3 Reference Design Values
    - 8.4.1.3—Tension-Reinforced Glulams
      - 8.4.1.3.1—General
      - 8.4.1.3.2—Dimensions
      - 8.4.1.3.3—Fatigue
      - 8.4.1.3.4—Reference Design Values for Tension-Reinforced Glulams
      - 8.4.1.3.5—Volume Effect
      - 8.4.1.3.6—Preservative Treatment
    - 8.4.1.4—Piles
  - 8.4.2—Metal Fasteners and Hardware
    - 8.4.2.1—General
    - 8.4.2.2—Minimum Requirements
      - 8.4.2.2.1—Fasteners
      - 8.4.2.2.2—Prestressing Bars
      - 8.4.2.2.3—Split Ring Connectors
      - 8.4.2.2.4—Shear Plate Connectors
      - 8.4.2.2.5—Nails and Spikes
      - 8.4.2.2.6—Drift Pins and Bolts
      - 8.4.2.2.7—Spike Grids
      - 8.4.2.2.8—Toothed Metal Plate Connectors
    - 8.4.2.3—Corrosion Protection
      - 8.4.2.3.1—Metallic Coating
      - 8.4.2.3.2—Alternative Coating
  - 8.4.3—Preservative Treatment
    - 8.4.3.1—Requirement for Treatment
    - 8.4.3.2—Treatment Chemicals
    - 8.4.3.3—Inspection and Marking
    - 8.4.3.4—Fire Retardant Treatment
  - 8.4.4—Adjustment Factors for Reference Design Values
    - 8.4.4.1—General
    - 8.4.4.2 Format Conversion Factor,  $C_{KF}$
    - 8.4.4.3 Wet Service Factor,  $C_M$
    - 8.4.4.4 Size Factor,  $C_F$ , for Sawn Lumber
    - 8.4.4.5 Volume Factor,  $C_V$ ,—(Glulam)
    - 8.4.4.6 Flat-Use Factor,  $C_{fu}$
    - 8.4.4.7 Incising Factor,  $C_i$
    - 8.4.4.8 Deck Factor,  $C_d$

- 8.4.4.9 Time Effect Factor,  $C_t$
- 8.5—LIMIT STATES
  - 8.5.1—Service Limit State
  - 8.5.2—Strength Limit State
    - 8.5.2.1—General
    - 8.5.2.2—Resistance Factors
    - 8.5.2.3—Stability
  - 8.5.3—Extreme Event Limit State
- 8.6—COMPONENTS IN FLEXURE
  - 8.6.1—General
  - 8.6.2—Rectangular Section
  - 8.6.3—Circular Section
- 8.7—COMPONENTS UNDER SHEAR
- 8.8—COMPONENTS IN COMPRESSION
  - 8.8.1—General
  - 8.8.2—Compression Parallel to Grain
  - 8.8.3—Compression Perpendicular to Grain
- 8.9—COMPONENTS IN TENSION PARALLEL TO GRAIN
- 8.10—COMPONENTS IN COMBINED FLEXURE AND AXIAL LOADING
  - 8.10.1—Components in Combined Flexure and Tension
  - 8.10.2—Components in Combined Flexure and Compression Parallel to Grain
- 8.11—BRACING REQUIREMENTS
  - 8.11.1—General
  - 8.11.2—Sawn Wood Beams
  - 8.11.3—Glued Laminated Timber Girders
  - 8.11.4—Bracing of Trusses
- 8.12—CAMBER REQUIREMENTS
  - 8.12.1—Glued Laminated Timber Girders
  - 8.12.2—Trusses
  - 8.12.3—Stress Laminated Timber Deck Bridge
- 8.13—CONNECTION DESIGN
- 8.14—REFERENCES

## **SECTION 9: DECKS AND DECK SYSTEMS**

- 9.1—SCOPE
- 9.2—DEFINITIONS
- 9.3—NOTATION
- 9.4—GENERAL DESIGN REQUIREMENTS
  - 9.4.1—Interface Action
  - 9.4.2—Deck Drainage
  - 9.4.3—Concrete Appurtenances
  - 9.4.4—Edge Supports
  - 9.4.5—Stay-in-Place Formwork for Overhangs
- 9.5—LIMIT STATES
  - 9.5.1—General
  - 9.5.2—Service Limit States
  - 9.5.3—Fatigue and Fracture Limit State
  - 9.5.4—Strength Limit States
  - 9.5.5—Extreme Event Limit States
- 9.6—ANALYSIS
  - 9.6.1—Methods of Analysis
  - 9.6.2—Loading
- 9.7—CONCRETE DECK SLABS
  - 9.7.1—General
    - 9.7.1.1—Minimum Depth and Cover
    - 9.7.1.2—Composite Action
    - 9.7.1.3—Skewed Decks

- 9.7.1.4—Edge Support
- 9.7.1.5—Design of Cantilever Slabs
- 9.7.2—Empirical Design
  - 9.7.2.1—General
  - 9.7.2.2—Application
  - 9.7.2.3—Effective Length
  - 9.7.2.4—Design Conditions
  - 9.7.2.5—Reinforcement Requirements
  - 9.7.2.6—Deck with Stay-in-Place Formwork
- 9.7.3—Traditional Design
  - 9.7.3.1—General
  - 9.7.3.2—Distribution Reinforcement
- 9.7.4—Stay-in-Place Formwork
  - 9.7.4.1—General
  - 9.7.4.2—Steel Formwork
  - 9.7.4.3—Concrete Formwork
    - 9.7.4.3.1—Depth
    - 9.7.4.3.2—Reinforcement
    - 9.7.4.3.3—Creep and Shrinkage Control
    - 9.7.4.3.4—Bedding of Panels
- 9.7.5—Precast Deck Slabs on Girders
  - 9.7.5.1—General
  - 9.7.5.2—Transversely Joined Precast Decks
  - 9.7.5.3—Longitudinally Post-Tensioned Precast Decks
- 9.7.6—Deck Slabs in Segmental Construction
  - 9.7.6.1—General
  - 9.7.6.2—Joints in Decks
- 9.8—METAL DECKS
  - 9.8.1—General
  - 9.8.2—Metal Grid Decks
    - 9.8.2.1—General
    - 9.8.2.2—Open Grid Floors
    - 9.8.2.3—Filled and Partially Filled Grid Decks
      - 9.8.2.3.1—General
      - 9.8.2.3.2—Design Requirements
      - 9.8.2.3.3—Fatigue and Fracture Limit State
    - 9.8.2.4—Unfilled Grid Decks Composite with Reinforced Concrete Slabs
      - 9.8.2.4.1—General
      - 9.8.2.4.2—Design
      - 9.8.2.4.3—Fatigue Limit State
  - 9.8.3—Orthotropic Steel Decks
    - 9.8.3.1—General
    - 9.8.3.2—Wheel Load Distribution
    - 9.8.3.3—Wearing Surface
    - 9.8.3.4—Refined Analysis
    - 9.8.3.5—Approximate Analysis
      - 9.8.3.5.1—Effective Width
      - 9.8.3.5.2—Decks with Open Ribs
      - 9.8.3.5.3—Decks with Closed Ribs
    - 9.8.3.6—Design
      - 9.8.3.6.1—Superposition of Local and Global Effects
      - 9.8.3.6.2—Limit States
    - 9.8.3.7—Detailing Requirements
      - 9.8.3.7.1—Minimum Plate Thickness
      - 9.8.3.7.2—Closed Ribs
      - 9.8.3.7.3—Unauthorized Welding to Orthotropic Decks
      - 9.8.3.7.4—Deck and Rib Details
  - 9.8.4—Orthotropic Aluminum Decks
    - 9.8.4.1—General
    - 9.8.4.2—Approximate Analysis

- 9.8.4.3—Limit States
- 9.8.5—Corrugated Metal Decks
  - 9.8.5.1—General
  - 9.8.5.2—Distribution of Wheel Loads
  - 9.8.5.3—Composite Action
- 9.9—WOOD DECKS AND DECK SYSTEMS
  - 9.9.1—Scope
  - 9.9.2—General
  - 9.9.3—Design Requirements
    - 9.9.3.1—Load Distribution
    - 9.9.3.2—Shear Design
    - 9.9.3.3—Deformation
    - 9.9.3.4—Thermal Expansion
    - 9.9.3.5—Wearing Surfaces
    - 9.9.3.6—Skewed Decks
  - 9.9.4—Glued Laminated Decks
    - 9.9.4.1—General
    - 9.9.4.2—Deck Tie-Downs
    - 9.9.4.3—Interconnected Decks
      - 9.9.4.3.1—Panels Parallel to Traffic
      - 9.9.4.3.2—Panels Perpendicular to Traffic
    - 9.9.4.4—Noninterconnected Decks
  - 9.9.5—Stress Laminated Decks
    - 9.9.5.1—General
    - 9.9.5.2—Nailing
    - 9.9.5.3—Staggered Butt Joints
    - 9.9.5.4—Holes in Laminations
    - 9.9.5.5—Deck Tie-Downs
    - 9.9.5.6—Stressing
      - 9.9.5.6.1—Prestressing System
      - 9.9.5.6.2—Prestressing Materials
      - 9.9.5.6.3—Design Requirements
      - 9.9.5.6.4—Corrosion Protection
      - 9.9.5.6.5—Railings
  - 9.9.6—Spike Laminated Decks
    - 9.9.6.1—General
    - 9.9.6.2—Deck Tie-Downs
    - 9.9.6.3—Panel Decks
  - 9.9.7—Plank Decks
    - 9.9.7.1—General
    - 9.9.7.2—Deck Tie-Downs
  - 9.9.8—Wearing Surfaces for Wood Decks
    - 9.9.8.1—General
    - 9.9.8.2—Plant Mix Asphalt
    - 9.9.8.3—Chip Seal
- 9.10—REFERENCES

## **SECTION 10: FOUNDATIONS**

- 10.1—SCOPE
- 10.2—DEFINITIONS
- 10.3—NOTATION
- 10.4—SOIL AND ROCK PROPERTIES
  - 10.4.1—Informational Needs
  - 10.4.2—Subsurface Exploration
  - 10.4.3—Laboratory Tests
    - 10.4.3.1—Soil Tests
    - 10.4.3.2—Rock Tests
  - 10.4.4—In-Situ Tests

- 10.4.5—Geophysical Tests
- 10.4.6—Selection of Design Properties
  - 10.4.6.1—General
  - 10.4.6.2—Soil Strength
    - 10.4.6.2.1—General
    - 10.4.6.2.2—Undrained Strength of Cohesive Soils
    - 10.4.6.2.3—Drained Strength of Cohesive Soils
    - 10.4.6.2.4—Drained Strength of Granular Soils
  - 10.4.6.3—Soil Deformation
  - 10.4.6.4—Rock Mass Strength
  - 10.4.6.5—Rock Mass Deformation
  - 10.4.6.6—Erodibility of Rock
- 10.5 LIMIT STATES AND RESISTANCE FACTORS
  - 10.5.1—General
  - 10.5.2—Service Limit States
    - 10.5.2.1—General
    - 10.5.2.2—Tolerable Movements and Movement Criteria
    - 10.5.2.3—Overall Stability
    - 10.5.2.4—Abutment Transitions
  - 10.5.3—Strength Limit States
    - 10.5.3.1—General
    - 10.5.3.2—Spread Footings
    - 10.5.3.3—Driven Piles
    - 10.5.3.4—Drilled Shafts
    - 10.5.3.5—Micropiles
  - 10.5.4—Extreme Events Limit States
    - 10.5.4.1—Extreme Events Design
    - 10.5.4.2—Liquefaction Design Requirements
  - 10.5.5—Resistance Factors
    - 10.5.5.1—Service Limit States
    - 10.5.5.2—Strength Limit States
      - 10.5.5.2.1—General
      - 10.5.5.2.2—Spread Footings
      - 10.5.5.2.3—Driven Piles
      - 10.5.5.2.4—Drilled Shafts
      - 10.5.5.2.5—Micropiles
    - 10.5.5.3—Extreme Limit States
      - 10.5.5.3.1—General
      - 10.5.5.3.2—Scour
      - 10.5.5.3.3—Other Extreme Limit States
- 10.6—SPREAD FOOTINGS
  - 10.6.1—General Considerations
    - 10.6.1.1—General
    - 10.6.1.2—Bearing Depth
    - 10.6.1.3—Effective Footing Dimensions
    - 10.6.1.4—Bearing Stress Distributions
    - 10.6.1.5—Anchorage of Inclined Footings
    - 10.6.1.6—Groundwater
    - 10.6.1.7—Uplift
    - 10.6.1.8—Nearby Structures
  - 10.6.2—Service Limit State Design
    - 10.6.2.1—General
    - 10.6.2.2—Tolerable Movements
    - 10.6.2.3—Loads
    - 10.6.2.4—Settlement Analyses
      - 10.6.2.4.1—General
      - 10.6.2.4.2—Settlement of Footings on Cohesionless Soils
      - 10.6.2.4.3—Settlement of Footings on Cohesive Soils
      - 10.6.2.4.4—Settlement of Footings on Rock
    - 10.6.2.5—Overall Stability

- 10.6.2.6—Bearing Resistance at the Service Limit State
  - 10.6.2.6.1—Presumptive Values for Bearing Resistance
  - 10.6.2.6.2—Semiempirical Procedures for Bearing Resistance
- 10.6.3—Strength Limit State Design
  - 10.6.3.1—Bearing Resistance of Soil
    - 10.6.3.1.1—General
    - 10.6.3.1.2—Theoretical Estimation
      - 10.6.3.1.2a—Basic Formulation
      - 10.6.3.1.2b—Considerations for Punching Shear
      - 10.6.3.1.2c—Considerations for Footings on Slopes
      - 10.6.3.1.2d—Considerations for Two-Layer Soil Systems—Critical Depth
      - 10.6.3.1.2e—Two-Layered Soil System in Undrained Loading
      - 10.6.3.1.2f—Two-Layered Soil System in Drained Loading
    - 10.6.3.1.3—Semiempirical Procedures
    - 10.6.3.1.4—Plate Load Tests
  - 10.6.3.2—Bearing Resistance of Rock
    - 10.6.3.2.1—General
    - 10.6.3.2.2—Semiempirical Procedures
    - 10.6.3.2.3—Analytic Method
    - 10.6.3.2.4—Load Test
  - 10.6.3.3—Eccentric Load Limitations
  - 10.6.3.4—Failure by Sliding
- 10.6.4—Extreme Event Limit State Design
  - 10.6.4.1—General
  - 10.6.4.2—Eccentric Load Limitations
- 10.6.5—Structural Design
- 10.7—DRIVEN PILES
  - 10.7.1—General
    - 10.7.1.1—Application
    - 10.7.1.2—Minimum Pile Spacing, Clearance, and Embedment into Cap
    - 10.7.1.3—Piles through Embankment Fill
    - 10.7.1.4—Batter Piles
    - 10.7.1.5—Pile Design Requirements
    - 10.7.1.6—Determination of Pile Loads
      - 10.7.1.6.1—General
      - 10.7.1.6.2—Downdrag
      - 10.7.1.6.3—Uplift Due to Expansive Soils
      - 10.7.1.6.4—Nearby Structures
  - 10.7.2—Service Limit State Design
    - 10.7.2.1—General
    - 10.7.2.2—Tolerable Movements
    - 10.7.2.3—Settlement
      - 10.7.2.3.1—Equivalent Footing Analogy
      - 10.7.2.3.2—Pile Groups in Cohesive Soil
    - 10.7.2.4—Horizontal Pile Foundation Movement
    - 10.7.2.5—Settlement Due to Downdrag
    - 10.7.2.6—Lateral Squeeze
  - 10.7.3—Strength Limit State Design
    - 10.7.3.1—General
    - 10.7.3.2—Point Bearing Piles on Rock
      - 10.7.3.2.1—General
      - 10.7.3.2.2—Piles Driven to Soft Rock
      - 10.7.3.2.3—Piles Driven to Hard Rock
    - 10.7.3.3—Pile Length Estimates for Contract Documents
    - 10.7.3.4—Nominal Axial Resistance Change after Pile Driving
      - 10.7.3.4.1—General
      - 10.7.3.4.2—Relaxation
      - 10.7.3.4.3—Setup
    - 10.7.3.5—Groundwater Effects and Buoyancy
    - 10.7.3.6—Scour

- 10.7.3.7—Downdrag
- 10.7.3.8—Determination of Nominal Axial Pile Resistance in Compression
  - 10.7.3.8.1—General
  - 10.7.3.8.2—Static Load Test
  - 10.7.3.8.3—Dynamic Testing
  - 10.7.3.8.4—Wave Equation Analysis
  - 10.7.3.8.5—Dynamic Formula
  - 10.7.3.8.6—Static Analysis
    - 10.7.3.8.6a—General
    - 10.7.3.8.6b— $\alpha$ -Method
    - 10.7.3.8.6c— $\beta$ -Method
    - 10.7.3.8.6d— $\lambda$ -Method
    - 10.7.3.8.6e—Tip Resistance in Cohesive Soils
    - 10.7.3.8.6f—Nordlund/Thurman Method in Cohesionless Soils
    - 10.7.3.8.6g—Using SPT or CPT in Cohesionless Soils
- 10.7.3.9—Resistance of Pile Groups in Compression
- 10.7.3.10—Uplift Resistance of Single Piles
- 10.7.3.11—Uplift Resistance of Pile Groups
- 10.7.3.12—Nominal Horizontal Resistance of Pile Foundations
- 10.7.3.13—Pile Structural Resistance
  - 10.7.3.13.1—Steel Piles
  - 10.7.3.13.2—Concrete Piles
  - 10.7.3.13.3—Timber Piles
  - 10.7.3.13.4—Buckling and Lateral Stability
- 10.7.4—Extreme Event Limit State
- 10.7.5—Corrosion and Deterioration
- 10.7.6—Determination of Minimum Pile Penetration
- 10.7.7 Determination of  $R_{ndr}$  Used to Establish Contract Driving Criteria for Bearing
- 10.7.8—Drivability Analysis
- 10.7.9—Test Piles
- 10.8—DRILLED SHAFTS
  - 10.8.1—General
    - 10.8.1.1—Scope
    - 10.8.1.2—Shaft Spacing, Clearance, and Embedment into Cap
    - 10.8.1.3—Shaft Diameter and Enlarged Bases
    - 10.8.1.4—Battered Shafts
    - 10.8.1.5—Drilled Shaft Resistance
    - 10.8.1.6—Determination of Shaft Loads
      - 10.8.1.6.1—General
      - 10.8.1.6.2—Downdrag
      - 10.8.1.6.3—Uplift
  - 10.8.2—Service Limit State Design
    - 10.8.2.1—Tolerable Movements
    - 10.8.2.2—Settlement
      - 10.8.2.2.1—General
      - 10.8.2.2.2—Settlement of Single-Drilled Shaft
      - 10.8.2.2.3—Intermediate Geo Materials (IGMs)
      - 10.8.2.2.4—Group Settlement
    - 10.8.2.3—Horizontal Movement of Shafts and Shaft Groups
    - 10.8.2.4—Settlement Due to Downdrag
    - 10.8.2.5—Lateral Squeeze
  - 10.8.3—Strength Limit State Design
    - 10.8.3.1—General
    - 10.8.3.2—Groundwater Table and Bouyancy
    - 10.8.3.3—Scour
    - 10.8.3.4—Downdrag
    - 10.8.3.5—Nominal Axial Compression Resistance of Single Drilled Shafts
      - 10.8.3.5.1—Estimation of Drilled Shaft Resistance in Cohesive Soils
        - 10.8.3.5.1a—General

- 10.8.3.5.1b—Side Resistance
- 10.8.3.5.1c—Tip Resistance
- 10.8.3.5.2—Estimation of Drilled Shaft Resistance in Cohesionless Soils
  - 10.8.3.5.2a—General
  - 10.8.3.5.2b—Side Resistance
  - 10.8.3.5.2c—Tip Resistance
- 10.8.3.5.3—Shafts in Strong Soil Overlying Weaker Compressible Soil
- 10.8.3.5.4—Estimation of Drilled Shaft Resistance in Rock
  - 10.8.3.5.4a—General
  - 10.8.3.5.4b—Side Resistance
  - 10.8.3.5.4c—Tip Resistance
  - 10.8.3.5.4d—Combined Side and Tip Resistance
- 10.8.3.5.5—Estimation of Drilled Shaft Resistance in Intermediate Geo Materials (IGMs)
- 10.8.3.5.6—Shaft Load Test
- 10.8.3.6—Shaft Group Resistance
  - 10.8.3.6.1—General
  - 10.8.3.6.2—Cohesive Soil
  - 10.8.3.6.3—Cohesionless Soil
  - 10.8.3.6.4—Shaft Groups in Strong Soil Overlying Weak Soil
- 10.8.3.7—Uplift Resistance
  - 10.8.3.7.1—General
  - 10.8.3.7.2—Uplift Resistance of Single Drilled Shaft
  - 10.8.3.7.3—Group Uplift Resistance
  - 10.8.3.7.4—Uplift Load Test
- 10.8.3.8—Nominal Horizontal Resistance of Shaft and Shaft Groups
- 10.8.3.9—Shaft Structural Resistance
  - 10.8.3.9.1—General
  - 10.8.3.9.2—Buckling and Lateral Stability
  - 10.8.3.9.3—Reinforcement
  - 10.8.3.9.4—Transverse Reinforcement
  - 10.8.3.9.5—Concrete
  - 10.8.3.9.6—Reinforcement into Superstructure
  - 10.8.3.9.7—Enlarged Bases
- 10.8.4—Extreme Event Limit State
- 10.9—MICROPILES
  - 10.9.1—General
    - 10.9.1.1—Scope
    - 10.9.1.2—Minimum Micropile Spacing, Clearance, and Embedment into Cap
    - 10.9.1.3—Micropiles through Embankment Fill
    - 10.9.1.4—Battered Micropiles
    - 10.9.1.5—Micropile Design Requirements
    - 10.9.1.6—Determination of Micropile Loads
      - 10.9.1.6.1—Downdrag
      - 10.9.1.6.2—Uplift Due to Expansive Soils
      - 10.9.1.6.3—Nearby Structures
  - 10.9.2—Service Limit State Design
    - 10.9.2.1—General
    - 10.9.2.2—Tolerable Movements
    - 10.9.2.3—Settlement
      - 10.9.2.3.1—Micropile Groups in Cohesive Soil
      - 10.9.2.3.2—Micropile Groups in Cohesionless Soil
    - 10.9.2.4—Horizontal Micropile Foundation Movement
    - 10.9.2.5—Settlement Due to Downdrag
    - 10.9.2.6—Lateral Squeeze
  - 10.9.3—Strength Limit State Design
    - 10.9.3.1—General
    - 10.9.3.2—Ground Water Table and Buoyancy
    - 10.9.3.3—Scour
    - 10.9.3.4—Downdrag
    - 10.9.3.5—Nominal Axial Compression Resistance of a Single Micropile

- 10.9.3.5.1—General
- 10.9.3.5.2—Estimation of Grout-to-Ground Bond Resistance
- 10.9.3.5.3—Estimation of Micropile Tip Resistance in Rock
- 10.9.3.5.4—Micropile Load Test
- 10.9.3.6—Resistance of Micropile Groups in Compression
- 10.9.3.7—Nominal Uplift Resistance of a Single Micropile
- 10.9.3.8—Nominal Uplift Resistance of Micropile Groups
- 10.9.3.9—Nominal Horizontal Resistance of Micropiles and Micropile Groups
- 10.9.3.10—Structural Resistance
  - 10.9.3.10.1—General
  - 10.9.3.10.2—Axial Compressive Resistance
    - 10.9.3.10.2a—Cased Length
    - 10.9.3.10.2b—Uncased Length
  - 10.9.3.10.3—Axial Tension Resistance
    - 10.9.3.10.3a—Cased Length
    - 10.9.3.10.3b—Uncased Length
  - 10.9.3.10.4—Plunge Length Transfer Load
  - 10.9.3.10.5—Grout-to-Steel Bond
  - 10.9.3.10.6—Buckling and Lateral Stability
  - 10.9.3.10.7—Reinforcement into Superstructure
- 10.9.4—Extreme Event Limit State
- 10.9.5—Corrosion and Deterioration
- 10.10—REFERENCES

## APPENDIX A10—SEISMIC ANALYSIS AND DESIGN OF FOUNDATIONS

### A10.1—INVESTIGATION

### A10.2—FOUNDATION DESIGN

### A10.3—SPECIAL PILE REQUIREMENTS

## SECTION 11: ABUTMENTS, PIERS, AND WALLS

- 11.1—SCOPE
- 11.2—DEFINITIONS
- 11.3—NOTATION
  - 11.3.1—General
- 11.4—SOIL PROPERTIES AND MATERIALS
  - 11.4.1—General
  - 11.4.2—Determination of Soil Properties
- 11.5—LIMIT STATES AND RESISTANCE FACTORS
  - 11.5.1—General
  - 11.5.2—Service Limit States
  - 11.5.3—Strength Limit State
  - 11.5.4—Resistance Requirement
  - 11.5.5—Load Combinations and Load Factors
  - 11.5.6—Resistance Factors
  - 11.5.7—Extreme Event Limit State
- 11.6—ABUTMENTS AND CONVENTIONAL RETAINING WALLS
  - 11.6.1—General Considerations
    - 11.6.1.1—General
    - 11.6.1.2—Loading
    - 11.6.1.3—Integral Abutments
    - 11.6.1.4—Wingwalls
    - 11.6.1.5—Reinforcement
      - 11.6.1.5.1 Conventional Walls and Abutments
      - 11.6.1.5.2—Wingwalls
    - 11.6.1.6—Expansion and Contraction Joints
  - 11.6.2—Movement and Stability at the Service Limit State
    - 11.6.2.1—Abutments
    - 11.6.2.2—Conventional Retaining Walls

- 11.6.2.3—Overall Stability
- 11.6.3—Bearing Resistance and Stability at the Strength Limit State
  - 11.6.3.1—General
  - 11.6.3.2—Bearing Resistance
  - 11.6.3.3—Overturning
  - 11.6.3.4—Subsurface Erosion
  - 11.6.3.5—Passive Resistance
  - 11.6.3.6—Sliding
- 11.6.4—Safety against Structural Failure
- 11.6.5—Seismic Design
- 11.6.6—Drainage
- 11.7—PIERS
  - 11.7.1—Load Effects in Piers
  - 11.7.2—Pier Protection
    - 11.7.2.1—Collision
    - 11.7.2.2—Collision Walls
    - 11.7.2.3—Scour
    - 11.7.2.4—Facing
- 11.8—NONGRAVITY CANTILEVERED WALLS
  - 11.8.1—General
  - 11.8.2—Loading
  - 11.8.3—Movement and Stability at the Service Limit State
    - 11.8.3.1 Movement
    - 11.8.3.2 Overall Stability
  - 11.8.4—Safety against Soil Failure at the Strength Limit State
    - 11.8.4.1—Overall Stability
  - 11.8.5—Safety against Structural Failure
    - 11.8.5.1—Vertical Wall Elements
    - 11.8.5.2—Facing
  - 11.8.6—Seismic Design
  - 11.8.7—Corrosion Protection
  - 11.8.8—Drainage
- 11.9—ANCHORED WALLS
  - 11.9.1—General
  - 11.9.2—Loading
  - 11.9.3—Movement and Stability at the Service Limit State
    - 11.9.3.1 Movement
    - 11.9.3.2 Overall Stability
  - 11.9.4—Safety against Soil Failure
    - 11.9.4.1—Bearing Resistance
    - 11.9.4.2—Anchor Pullout Capacity
    - 11.9.4.3—Passive Resistance
  - 11.9.5—Safety against Structural Failure
    - 11.9.5.1—Anchors
    - 11.9.5.2—Vertical Wall Elements
    - 11.9.5.3—Facing
  - 11.9.6—Seismic Design
  - 11.9.7—Corrosion Protection
  - 11.9.8—Construction and Installation
    - 11.9.8.1—Anchor Stressing and Testing
  - 11.9.9—Drainage
- 11.10—MECHANICALLY STABILIZED EARTH WALLS
  - 11.10.1—General
  - 11.10.2—Structure Dimensions
    - 11.10.2.1—Minimum Length of Soil Reinforcement
    - 11.10.2.2—Minimum Front Face Embedment
    - 11.10.2.3—Facing
      - 11.10.2.3.1—Stiff or Rigid Concrete, Steel, and Timber Facings
      - 11.10.2.3.2—Flexible Wall Facings
      - 11.10.2.3.3—Corrosion Issues for MSE Facing

- 11.10.3—Loading
- 11.10.4—Movement and Stability at the Service Limit State
  - 11.10.4.1—Settlement
  - 11.10.4.2—Lateral Displacement
  - 11.10.4.3—Overall Stability
- 11.10.5—Safety against Soil Failure (External Stability)
  - 11.10.5.1 General
  - 11.10.5.2 Loading
  - 11.10.5.3—Sliding
  - 11.10.5.4—Bearing Resistance
  - 11.10.5.5—Overturning
- 11.10.6—Safety against Structural Failure (Internal Stability)
  - 11.10.6.1—General
  - 11.10.6.2—Loading
    - 11.10.6.2.1—Maximum Reinforcement Loads
    - 11.10.6.2.2—Reinforcement Loads at Connection to Wall Face
  - 11.10.6.3—Reinforcement Pullout
    - 11.10.6.3.1—Boundary between Active and Resistant Zones
    - 11.10.6.3.2—Reinforcement Pullout Design
  - 11.10.6.4—Reinforcement Strength
    - 11.10.6.4.1 General
    - 11.10.6.4.2—Design Life Considerations
      - 11.10.6.4.2a—Steel Reinforcements
      - 11.10.6.4.2b—Geosynthetic Reinforcements
    - 11.10.6.4.3—Design Tensile Resistance
      - 11.10.6.4.3a—Steel Reinforcements
      - 11.10.6.4.3b—Geosynthetic Reinforcements
    - 11.10.6.4.4—Reinforcement/Facing Connection Design Strength
      - 11.10.6.4.4a Steel Reinforcements
      - 11.10.6.4.4b—Geosynthetic Reinforcements
- 11.10.7—Seismic Design
  - 11.10.7.1—External Stability
  - 11.10.7.2—Internal Stability
  - 11.10.7.3—Facing Reinforcement Connections
- 11.10.8—Drainage
- 11.10.9—Subsurface Erosion
- 11.10.10—Special Loading Conditions
  - 11.10.10.1—Concentrated Dead Loads
  - 11.10.10.2—Traffic Loads and Barriers
  - 11.10.10.3—Hydrostatic Pressures
  - 11.10.10.4—Obstructions in the Reinforced Soil Zone
- 11.10.11—MSE Abutments
- 11.11—PREFABRICATED MODULAR WALLS
  - 11.11.1—General
  - 11.11.2—Loading
  - 11.11.3—Movement at the Service Limit State
  - 11.11.4—Safety against Soil Failure
    - 11.11.4.1—General
    - 11.11.4.2—Sliding
    - 11.11.4.3—Bearing Resistance
    - 11.11.4.4—Overturning
    - 11.11.4.5—Subsurface Erosion
    - 11.11.4.6—Overall Stability
    - 11.11.4.7—Passive Resistance and Sliding
  - 11.11.5—Safety against Structural Failure
    - 11.11.5.1—Module Members
  - 11.11.6—Seismic Design
  - 11.11.7—Abutments
  - 11.11.8—Drainage
- 11.12—REFERENCES

## APPENDIX A11—SEISMIC DESIGN OF ABUTMENTS AND GRAVITY RETAINING STRUCTURES

### A11.1—GENERAL

#### A11.1.1—Free-Standing Abutments

##### A11.1.1.1—Mononobe-Okabe Analysis

##### A11.1.1.2—Design for Displacement

##### A11.1.1.3—Nonyielding Abutments

#### A11.1.2—Monolithic Abutments

### A11.2—APPENDIX REFERENCES

## SECTION 12: BURIED STRUCTURES AND TUNNEL LINERS

### 12.1—SCOPE

### 12.2—DEFINITIONS

### 12.3—NOTATION

### 12.4—SOIL AND MATERIAL PROPERTIES

#### 12.4.1—Determination of Soil Properties

##### 12.4.1.1—General

##### 12.4.1.2—Foundation Soils

##### 12.4.1.3—Envelope Backfill Soils

#### 12.4.2—Materials

##### 12.4.2.1—Aluminum Pipe and Structural Plate Structures

##### 12.4.2.2—Concrete

##### 12.4.2.3—Precast Concrete Pipe

##### 12.4.2.4—Precast Concrete Structures

##### 12.4.2.5—Steel Pipe and Structural Plate Structures

##### 12.4.2.6—Deep Corrugated Structures

##### 12.4.2.7—Steel Reinforcement

##### 12.4.2.8—Thermoplastic Pipe

### 12.5—LIMIT STATES AND RESISTANCE FACTORS

#### 12.5.1—General

#### 12.5.2—Service Limit State

#### 12.5.3—Strength Limit State

#### 12.5.4—Load Modifiers and Load Factors

#### 12.5.5—Resistance Factors

#### 12.5.6—Flexibility Limits and Construction Stiffness

##### 12.5.6.1—Corrugated Metal Pipe and Structural Plate Structures

##### 12.5.6.2—Spiral Rib Metal Pipe and Pipe Arches

##### 12.5.6.3—Thermoplastic Pipe

##### 12.5.6.4—Steel Tunnel Liner Plate

### 12.6—GENERAL DESIGN FEATURES

#### 12.6.1—Loading

#### 12.6.2—Service Limit State

##### 12.6.2.1—Tolerable Movement

##### 12.6.2.2—Settlement

###### 12.6.2.2.1—General

###### 12.6.2.2.2—Longitudinal Differential Settlement

###### 12.6.2.2.3—Differential Settlement between Structure and Backfill

###### 12.6.2.2.4—Footing Settlement

###### 12.6.2.2.5—Unbalanced Loading

##### 12.6.2.3—Uplift

#### 12.6.3—Safety against Soil Failure

##### 12.6.3.1—Bearing Resistance and Stability

##### 12.6.3.2—Corner Backfill for Metal Pipe Arches

#### 12.6.4—Hydraulic Design

#### 12.6.5—Scour

#### 12.6.6—Soil Envelope

##### 12.6.6.1—Trench Installations

##### 12.6.6.2—Embankment Installations

- 12.6.6.3—Minimum Soil Cover
- 12.6.7—Minimum Spacing between Multiple Lines of Pipe
- 12.6.8—End Treatment
  - 12.6.8.1—General
  - 12.6.8.2—Flexible Culverts Constructed on Skew
- 12.6.9—Corrosive and Abrasive Conditions
- 12.7—METAL PIPE, PIPE ARCH, AND ARCH STRUCTURES
  - 12.7.1—General
  - 12.7.2—Safety against Structural Failure
    - 12.7.2.1—Section Properties
    - 12.7.2.2—Thrust
    - 12.7.2.3—Wall Resistance
    - 12.7.2.4—Resistance to Buckling
    - 12.7.2.5—Seam Resistance
    - 12.7.2.6—Handling and Installation Requirements
  - 12.7.3—Smooth Lined Pipe
  - 12.7.4—Stiffening Elements for Structural Plate Structures
  - 12.7.5—Construction and Installation
- 12.8—LONG-SPAN STRUCTURAL PLATE STRUCTURES
  - 12.8.1—General
  - 12.8.2—Service Limit State
  - 12.8.3—Safety against Structural Failure
    - 12.8.3.1—Section Properties
      - 12.8.3.1.1—Cross-Section
      - 12.8.3.1.2—Shape Control
      - 12.8.3.1.3—Mechanical and Chemical Requirements
    - 12.8.3.2—Thrust
    - 12.8.3.3—Wall Area
    - 12.8.3.4—Seam Strength
    - 12.8.3.5—Acceptable Special Features
      - 12.8.3.5.1—Continuous Longitudinal Stiffeners
      - 12.8.3.5.2—Reinforcing Ribs
  - 12.8.4—Safety Against Structural Failure—Foundation Design
    - 12.8.4.1—Settlement Limits
    - 12.8.4.2—Footing Reactions in Arch Structures
    - 12.8.4.3—Footing Design
  - 12.8.5—Safety Against Structural Failure—Soil Envelope Design
    - 12.8.5.1—General
    - 12.8.5.2—Construction Requirements
    - 12.8.5.3—Service Requirements
  - 12.8.6—Safety Against Structural Failure—End Treatment Design
    - 12.8.6.1—General
    - 12.8.6.2—Standard Shell End Types
    - 12.8.6.3—Balanced Support
    - 12.8.6.4—Hydraulic Protection
      - 12.8.6.4.1—General
      - 12.8.6.4.2—Backfill Protection
      - 12.8.6.4.3—Cut-Off (Toe) Walls
      - 12.8.6.4.4—Hydraulic Uplift
      - 12.8.6.4.5—Scour
  - 12.8.7—Concrete Relieving Slabs
  - 12.8.8—Construction and Installation
  - 12.8.9—Deep Corrugated Structural Plate Structures
    - 12.8.9.1—General
    - 12.8.9.2—Width of Structural Backfill
      - 12.8.9.2.1—Deep Corrugated Structures with Ratio of Crown Radius to Haunch Radius  $\leq 5$
      - 12.8.9.2.2—Deep Corrugated Structures with Ratio of Crown Radius to Haunch Radius  $> 5$
    - 12.8.9.3—Safety against Structural Failure
      - 12.8.9.3.1—Structural Plate Requirements
      - 12.8.9.3.2—Structural Analysis

- 12.8.9.4—Minimum Depth of Fill
- 12.8.9.5—Combined Thrust and Moment
- 12.8.9.6—Global Buckling
- 12.8.9.7—Connections
- 12.9—STRUCTURAL PLATE BOX STRUCTURES
  - 12.9.1—General
  - 12.9.2—Loading
  - 12.9.3—Service Limit State
  - 12.9.4—Safety against Structural Failure
    - 12.9.4.1—General
    - 12.9.4.2—Moments Due to Factored Loads
    - 12.9.4.3—Plastic Moment Resistance
    - 12.9.4.4—Crown Soil Cover Factor,  $C_H$
    - 12.9.4.5—Footing Reactions
    - 12.9.4.6—Concrete Relieving Slabs
  - 12.9.5—Construction and Installation
- 12.10—REINFORCED CONCRETE PIPE
  - 12.10.1—General
  - 12.10.2—Loading
    - 12.10.2.1—Standard Installations
    - 12.10.2.2—Pipe Fluid Weight
    - 12.10.2.3—Live Loads
  - 12.10.3—Service Limit State
  - 12.10.4—Safety against Structural Failure
    - 12.10.4.1—General
    - 12.10.4.2—Direct Design Method
      - 12.10.4.2.1—Loads and Pressure Distribution
      - 12.10.4.2.2—Analysis for Force Effects with the Pipe Ring
      - 12.10.4.2.3—Process and Material Factors
      - 12.10.4.2.4—Flexural Resistance at the Strength Limit State
        - 12.10.4.2.4a—Circumferential Reinforcement
        - 12.10.4.2.4b—Minimum Reinforcement
        - 12.10.4.2.4c—Maximum Flexural Reinforcement without Stirrups
        - 12.10.4.2.4d—Reinforcement for Crack Width Control
        - 12.10.4.2.4e—Minimum Concrete Cover
      - 12.10.4.2.5—Shear Resistance without Stirrups
      - 12.10.4.2.6—Shear Resistance with Radial Stirrups
      - 12.10.4.2.7—Stirrup Reinforcement Anchorage
        - 12.10.4.2.7a—Radial Tension Stirrup Anchorage
        - 12.10.4.2.7b—Shear Stirrup Anchorage
        - 12.10.4.2.7c—Stirrup Embedment
    - 12.10.4.3—Indirect Design Method
      - 12.10.4.3.1—Bearing Resistance
      - 12.10.4.3.2—Bedding Factor
        - 12.10.4.3.2a—Earth Load Bedding Factor for Circular Pipe
        - 12.10.4.3.2b—Earth Load Bedding Factor for Arch and Elliptical Pipe
        - 12.10.4.3.2c—Live Load Bedding Factors
    - 12.10.4.4—Development of Quadrant Mat Reinforcement
      - 12.10.4.4.1—Minimum Cage Reinforcement
      - 12.10.4.4.2—Development Length of Welded Wire Fabric
      - 12.10.4.4.3—Development of Quadrant Mat Reinforcement Consisting of Welded Plain Wire Fabric
      - 12.10.4.4.4—Development of Quadrant Mat Reinforcement Consisting of Deformed Bars, Deformed Wire, or Deformed Wire Fabric
  - 12.10.5—Construction and Installation
- 12.11—REINFORCED CONCRETE CAST-IN-PLACE AND PRECAST BOX CULVERTS AND REINFORCED CAST-IN-PLACE ARCHES
  - 12.11.1—General
  - 12.11.2—Loads and Live Load Distribution
    - 12.11.2.1—General
    - 12.11.2.2—Modification of Earth Loads for Soil-Structure Interaction

- 12.11.2.2.1—Embankment and Trench Conditions
- 12.11.2.2.2—Other Installations
- 12.11.2.3—Distribution of Concentrated Loads to Bottom Slab of Box Culvert
- 12.11.2.4—Distribution of Concentrated Loads in Skewed Box Culverts
- 12.11.3—Service Limit State
- 12.11.4—Safety against Structural Failure
  - 12.11.4.1—General
  - 12.11.4.2—Design Moment for Box Culverts
  - 12.11.4.3—Minimum Reinforcement
    - 12.11.4.3.1—Cast-in-Place Structures
    - 12.11.4.3.2—Precast Box Structures
  - 12.11.4.4—Minimum Cover for Precast Box Structures
- 12.11.5—Construction and Installation
- 12.12—THERMOPLASTIC PIPES
  - 12.12.1—General
  - 12.12.2—Service Limit States
  - 12.12.3—Safety against Structural Failure
    - 12.12.3.1—General
    - 12.12.3.2—Section Properties
    - 12.12.3.3—Chemical and Mechanical Requirements
    - 12.12.3.4—Thrust
    - 12.12.3.5—Wall Resistance
      - 12.12.3.5.1—General
      - 12.12.3.5.2—Buckling
      - 12.12.3.5.3—Resistance to Local Buckling of Pipe Wall
        - 12.12.3.5.3a—General
        - 12.12.3.5.3b—Idealized Wall Profile
        - 12.12.3.5.3c—Slenderness and Effective Width
      - 12.12.3.5.4—Combined Strain
        - 12.12.3.5.4a—General
        - 12.12.3.5.4b—Bending Strain
    - 12.12.3.6—Handling and Installation Requirements
- 12.13—STEEL TUNNEL LINER PLATE
  - 12.13.1—General
  - 12.13.2—Loading
    - 12.13.2.1—Earth Loads
    - 12.13.2.2—Live Loads
    - 12.13.2.3—Grouting Pressure
  - 12.13.3—Safety against Structural Failure
    - 12.13.3.1—Section Properties
    - 12.13.3.2—Wall Area
    - 12.13.3.3—Buckling
    - 12.13.3.4—Seam Strength
    - 12.13.3.5—Construction Stiffness
- 12.14—PRECAST REINFORCED CONCRETE THREE-SIDED STRUCTURES
  - 12.14.1—General
  - 12.14.2—Materials
    - 12.14.2.1—Concrete
    - 12.14.2.2—Reinforcement
  - 12.14.3—Concrete Cover for Reinforcement
  - 12.14.4—Geometric Properties
  - 12.14.5—Design
    - 12.14.5.1—General
    - 12.14.5.2—Distribution of Concentrated Load Effects in Top Slab and Sides
    - 12.14.5.3—Distribution of Concentrated Loads in Skewed Culverts
    - 12.14.5.4—Shear Transfer in Transverse Joints between Culvert Sections
    - 12.14.5.5—Span Length
    - 12.14.5.6—Resistance Factors
    - 12.14.5.7—Crack Control
    - 12.14.5.8—Minimum Reinforcement

- 12.14.5.9—Deflection Control at the Service Limit State
- 12.14.5.10—Footing Design
- 12.14.5.11—Structural Backfill
- 12.14.5.12—Scour Protection and Waterway Considerations
- 12.15—REFERENCES

## APPENDIX A12—PLATE, PIPE, AND PIPE ARCH PROPERTIES

### SECTION 13: RAILINGS

- 13.1—SCOPE
- 13.2—DEFINITIONS
- 13.3—NOTATION
- 13.4—GENERAL
- 13.5—MATERIALS
- 13.6—LIMIT STATES AND RESISTANCE FACTORS
  - 13.6.1—Strength Limit State
  - 13.6.2—Extreme Event Limit State
- 13.7—TRAFFIC RAILING
  - 13.7.1—Railing System
    - 13.7.1.1 General
    - 13.7.1.2—Approach Railings
    - 13.7.1.3—End Treatment
  - 13.7.2—Test Level Selection Criteria
  - 13.7.3—Railing Design
    - 13.7.3.1—General
      - 13.7.3.1.1—Application of Previously Tested Systems
      - 13.7.3.1.2—New Systems
    - 13.7.3.2—Height of Traffic Parapet or Railing
- 13.8—PEDESTRIAN RAILING
  - 13.8.1—Geometry
  - 13.8.2—Design Live Loads
- 13.9—BICYCLE RAILINGS
  - 13.9.1—General
  - 13.9.2—Geometry
  - 13.9.3—Design Live Loads
- 13.10—COMBINATION RAILINGS
  - 13.10.1—General
  - 13.10.2—Geometry
  - 13.10.3—Design Live Loads
- 13.11—CURBS AND SIDEWALKS
  - 13.11.1—General
  - 13.11.2—Sidewalks
  - 13.11.3—End Treatment of Separation Railing
- 13.12—REFERENCES

### APPENDIX A13—RAILINGS

- A13.1—GEOMETRY AND ANCHORAGES
  - A13.1.1—Separation of Rail Elements
  - A13.1.2—Anchorages
- A13.2—TRAFFIC RAILING DESIGN FORCES
- A13.3—DESIGN PROCEDURE FOR RAILING TEST SPECIMENS
  - A13.3.1—Concrete Railings
  - A13.3.2—Post-and-Beam Railings
  - A13.3.3—Concrete Parapet and Metal Rail
  - A13.3.4—Wood Barriers
- A13.4—DECK OVERHANG DESIGN
  - A13.4.1—Design Cases
  - A13.4.2—Decks Supporting Concrete Parapet Railings
  - A13.4.3—Decks Supporting Post-and-Beam Railings

- A13.4.3.1—Overhang Design
- A13.4.3.2—Resistance to Punching Shear

## **SECTION 14: JOINTS AND BEARINGS**

- 14.1—SCOPE
- 14.2—DEFINITIONS
- 14.3—NOTATION
- 14.4—MOVEMENTS AND LOADS
  - 14.4.1—General
  - 14.4.2—Design Requirements
    - 14.4.2.1—Elastomeric Pads and Steel Reinforced Elastomeric Bearings
    - 14.4.2.2—High Load Multitrotational (HLMR) Bearings
      - 14.4.2.2.1—Pot Bearings and Curved Sliding Surface Bearings
      - 14.4.2.2.2—Disc Bearings
- 14.5—BRIDGE JOINTS
  - 14.5.1—Requirements
    - 14.5.1.1—General
    - 14.5.1.2—Structural Design
    - 14.5.1.3—Geometry
    - 14.5.1.4—Materials
    - 14.5.1.5—Maintenance
  - 14.5.2—Selection
    - 14.5.2.1—Number of Joints
    - 14.5.2.2—Location of Joints
  - 14.5.3—Design Requirements
    - 14.5.3.1—Movements during Construction
    - 14.5.3.2—Design Movements
    - 14.5.3.3—Protection
    - 14.5.3.4—Bridging Plates
    - 14.5.3.5—Armor
    - 14.5.3.6—Anchors
    - 14.5.3.7—Bolts
  - 14.5.4—Fabrication
  - 14.5.5—Installation
    - 14.5.5.1—Adjustment
    - 14.5.5.2—Temporary Supports
    - 14.5.5.3—Field Splices
  - 14.5.6—Considerations for Specific Joint Types
    - 14.5.6.1—Open Joints
    - 14.5.6.2—Closed Joints
    - 14.5.6.3—Waterproofed Joints
    - 14.5.6.4—Joint Seals
    - 14.5.6.5—Poured Seals
    - 14.5.6.6—Compression and Cellular Seals
    - 14.5.6.7—Sheet and Strip Seals
    - 14.5.6.8—Plank Seals
    - 14.5.6.9—Modular Bridge Joint Systems (MBSJ)
      - 14.5.6.9.1—General
      - 14.5.6.9.2—Performance Requirements
      - 14.5.6.9.3—Testing and Calculation Requirements
      - 14.5.6.9.4—Loads and Load Factors
      - 14.5.6.9.5—Distribution of Wheel Loads
      - 14.5.6.9.6—Strength Limit State Design Requirements
      - 14.5.6.9.7—Fatigue Limit State Design Requirements
        - 14.5.6.9.7a—General
        - 14.5.6.9.7b—Design Stress Range
- 14.6—REQUIREMENTS FOR BEARINGS
  - 14.6.1—General

- 14.6.2—Characteristics
- 14.6.3—Force Effects Resulting from Restraint of Movement at the Bearing
  - 14.6.3.1—Horizontal Force and Movement
  - 14.6.3.2—Moment
- 14.6.4—Fabrication, Installation, Testing, and Shipping
- 14.6.5—Seismic and Other Extreme Event Provisions for Bearings
  - 14.6.5.1—General
  - 14.6.5.2—Applicability
  - 14.6.5.3—Design Criteria
- 14.7—SPECIAL DESIGN PROVISIONS FOR BEARINGS
  - 14.7.1—Metal Rocker and Roller Bearings
    - 14.7.1.1—General
    - 14.7.1.2—Materials
    - 14.7.1.3—Geometric Requirements
    - 14.7.1.4—Contact Stresses
  - 14.7.2—PTFE Sliding Surfaces
    - 14.7.2.1—PTFE Surface
    - 14.7.2.2—Mating Surface
    - 14.7.2.3—Minimum Thickness
      - 14.7.2.3.1—PTFE
      - 14.7.2.3.2—Stainless Steel Mating Surfaces
    - 14.7.2.4—Contact Pressure
    - 14.7.2.5—Coefficient of Friction
    - 14.7.2.6—Attachment
      - 14.7.2.6.1—PTFE
      - 14.7.2.6.2—Mating Surface
  - 14.7.3—Bearings with Curved Sliding Surfaces
    - 14.7.3.1—General
    - 14.7.3.2—Bearing Resistance
    - 14.7.3.3—Resistance to Lateral Load
  - 14.7.4—Pot Bearings
    - 14.7.4.1—General
    - 14.7.4.2—Materials
    - 14.7.4.3—Geometric Requirements
    - 14.7.4.4—Elastomeric Disc
    - 14.7.4.5—Sealing Rings
      - 14.7.4.5.1—General
      - 14.7.4.5.2—Rings with Rectangular Cross-Sections
      - 14.7.4.5.3—Rings with Circular Cross-Sections
    - 14.7.4.6—Pot
    - 14.7.4.7—Piston
  - 14.7.5—Steel-Reinforced Elastomeric Bearings—Method B
    - 14.7.5.1—General
    - 14.7.5.2—Material Properties
    - 14.7.5.3—Design Requirements
      - 14.7.5.3.1—Scope
      - 14.7.5.3.2—Shear Deformations
      - 14.7.5.3.3—Combined Compression, Rotation, and Shear
      - 14.7.5.3.4—Stability of Elastomeric Bearings
      - 14.7.5.3.5—Reinforcement
      - 14.7.5.3.6—Compressive Deflection
      - 14.7.5.3.7—Seismic and Other Extreme Event Provisions
    - 14.7.5.4—Anchorage for Bearings without Bonded External Plates
  - 14.7.6—Elastomeric Pads and Steel-Reinforced Elastomeric Bearings—Method A
    - 14.7.6.1—General
    - 14.7.6.2—Material Properties
    - 14.7.6.3—Design Requirements
      - 14.7.6.3.1—Scope
      - 14.7.6.3.2—Compressive Stress
      - 14.7.6.3.3—Compressive Deflection

- 14.7.6.3.4—Shear
- 14.7.6.3.5—Rotation
  - 14.7.6.3.5a—General
  - 14.7.6.3.5b—Rotation of PEP
  - 14.7.6.3.5c—Rotation of CDP
  - 14.7.6.3.5d—Rotation of FGP and Steel Reinforced Elastomeric Bearings
- 14.7.6.3.6—Stability
- 14.7.6.3.7—Reinforcement
- 14.7.6.3.8—Seismic and Other Extreme Event Provisions
- 14.7.7—Bronze or Copper Alloy Sliding Surfaces
  - 14.7.7.1—Materials
  - 14.7.7.2—Coefficient of Friction
  - 14.7.7.3—Limit on Load
  - 14.7.7.4—Clearances and Mating Surfaces
- 14.7.8—Disc Bearings
  - 14.7.8.1—General
  - 14.7.8.2—Materials
  - 14.7.8.3—Elastomeric Disc
  - 14.7.8.4—Shear Resisting Mechanism
  - 14.7.8.5—Steel Plates
- 14.7.9—Guides and Restraints
  - 14.7.9.1—General
  - 14.7.9.2—Design Loads
  - 14.7.9.3—Materials
  - 14.7.9.4—Geometric Requirements
  - 14.7.9.5—Design Basis
    - 14.7.9.5.1—Load Location
    - 14.7.9.5.2—Contact Stress
  - 14.7.9.6—Attachment of Low-Friction Material
- 14.7.10—Other Bearing Systems
- 14.8—LOAD PLATES AND ANCHORAGE FOR BEARINGS
  - 14.8.1—Plates for Load Distribution
  - 14.8.2—Tapered Plates
  - 14.8.3—Anchorage and Anchor Bolts
    - 14.8.3.1—General
    - 14.8.3.2—Seismic and Other Extreme Event Design and Detailing Requirements
- 14.9—CORROSION PROTECTION
- 14.10—REFERENCES